

CRYSTAL ENVIRONMENTAL LUBRICANTS INC -- MIL-L-53074 -- 9150-00-240-2260

===== Product Identification =====

Product ID:MIL-L-53074

MSDS Date:01/01/1993

FSC:9150

NIIN:00-240-2260

MSDS Number: BTRJR

=== Responsible Party ===

Company Name:CRYSTAL ENVIRONMENTAL LUBRICANTS INC

Address:708 W MORRISON BLVD

City:HAMMOND

State:LA

ZIP:70401

Country:US

Info Phone Num:504-542-7224

Emergency Phone Num:504-542-7224

CAGE:KO659

=== Contractor Identification ===

Company Name:CRYSTAL ENVIRONMENTAL LUBRICANTS INC

Address:708 NORTH MORRISON BLVD

Box:City:HAMMOND

State:LA

ZIP:70404

Country:US

Phone:504-542-7224

CAGE:KO659

Company Name:INTERNATIONAL LUBRICANTS INC

Address:10363 W AIRLINE HWY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940(504-471-0104FAX)

CAGE:0W1H4

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE

:0T5C6

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SEVERLY HYDROTREATED HEAVY NAPHTHENIC DISTILLATE  
CAS:64742-52-5  
RTECS #:PY8035000  
Other REC Limits:NONE RECOMMENDED

Ingred Name:SOLVENT DEASPHALTED RESIDUAL PETROLEUM OIL  
CAS:64741-95-3  
Other REC Limits:NONE RECOMMENDED  
ACGIH TLV:5 MG/M3

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:NO Skin:YES Ingestion  
:YES

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO

Health Hazards Acute and Chronic:EYE CONTACT: PRACTICALLY

NON-IRRITATING TO THE EYE. SKIN CONTACT: MAY CAUSE LIGHT SKIN  
IRRITATION. INHALATION: NOT EXPECTED TO PRESENT AN INHALATION  
HAZARD. INGESTION: RELATIVELY NON-TOXIC. PRODUCT DOES HAVE  
LAXATIVE PROPERTIES.

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:PROLONGED AND REPEATED EXPOSURE TO OIL MIST MAY  
CAUSE PULMONA

RY DISEASE SUCH AS CHRONIC LUNG INFLAMMATION.

SHORTNESS OF BREATH AND COUGH ARE THE MOST COMMON SYMPTOMS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
First Aid Measures  
=====

First Aid:EYE CONTACT: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF  
WATER. IF MATERIAL IS HOT, TREAT FOR THERMAL BURNS AND TAKE VICTIM  
TO HOSPITAL IMMEDIATELY. SKIN CONTACT: WASH CONTAMINATED AREA WITH  
SOAP AND WATER. IF IRRITATION OCCURS  
, SEEK MEDICAL ATTENTION.

INHALATION: NOT EXPECTED TO PRESENT AN INHALATION PROBLEM AT  
AMBIENT CONDITIONS. INGESTION: DO NOT INDUCE VOMITING. SEEK MEDICAL  
ATTENTION.

=====  
Fire Fighting Measures  
=====

Flash Point Method:COC

Flash Point:260C

Spec Gravity:0.93

Appearance and Odor:MEDIUM AMBER LIQUID

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condi

tion to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:COMBUSTION PRODUCTS INCLUDES CARBON DIOXIDE, CARBON MONOXIDE AND OTHER OXIDES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The Un

ited States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.