View NSN Online: https://aerobasegroup.com/nsn/9150-01-079-8310

DRYDEN OIL COMPANY, INC -- DRYDENE NON-DETERGENT MOTOR OILS, SAE 10, 20,

MSDS Safety Information

_____ FSC: 9150 NIIN: 01-079-8310 MSDS Date: 01/14/1994 MSDS Num: BTRKR Product ID: DRYDENE NON-DETERGENT MOTOR OILS, SAE 10, 20, 30, 40, 50. MFN: 01 **Responsible Party** Cage: 40310 Name: DRYDEN OIL COMPANY, INC Address: 9300 PULASKI HIGHWAY City: BALTIMORE MD 21220 Info Phone Number: 410-574-500 Emergency Phone Number: 410-574-500/800-777-1466 Proprietary Ind: Y Published: Y ______ Contractor Summary _____ Cage: 40310 Name: DRYDEN OIL CO INC Address: 9300 PULASKI HWY City: BALTIMORE MD 21220 Phone: 301-574-5000 ______ Item Description Information _____ _____ Item Manager: S9G Item Name: LUBRICATING OIL, ENGINE Specification Number: NONE Type/Grade/Class: NONE Unit of Issue: QT UI Container Qty: 1 Type of Container: CAN _____ Ingredients ______ Name: *** PROPRIETARY *** _____ ______ Health Hazards Data _______

=========== LD50 LC50 Mixture: NOT KNOWN. Route Of Entry Inds - Inhalation: YES Skin: YES Ingestion: NO Carcinogenicity Inds - NTP: NO IARC: NO OSHA: NO Effects of Exposure: EYE:MAY CAUSE IRRIT. SKIN:PROLONGED OR REPEATED CONTACT MAY CAUSE IRRIT. INGEST: RELATIVELY NON-TOXIC. INHAL: VAPOR PRESSURE IS VERY LOW. VAPOR INHAL UNDER AMBIENT TEMP CONDITONS IS NOT NORMALLY A PROBLEM. Signs And Symptions Of Overexposure: EYE & amp; SKIN IRRITATION. Medical Cond Aggravated By Exposure: NONE STATED. Fir st Aid: EYE:FLUSH W/CLEAR WATER FOR 15MINS OR TIL IRRIT SUBSIDES. IF PERSISTS CALL DR. SKIN: REMOVE CONTAMINATED CLOTH. WASH AREA THOROUGHLY W/SOAP & WATER. INGEST: DO NOT INDUCE VOMIT. CALL DR IMMED. INHAL:NO T NORMALLY A PROBLEM. OVERCOME BY VAPORFROM HOT PRODUCT REMOVE FROM EXPOSURE. CALL DR. GIVE OXY. IF OVER EXPOSED TO OIL MIST REMOVE FROM EXPOSURE TIL EXCESSIVE MIST **OIL CONDITION SUBSIDES.** ______ Handling and Disposal _____ Spill Release Procedures: REPORT SPILLS TO PROPER AUTHORITIES. IF REACH WATERWAY CALL COAST GUARD:800-424-8802.RECOVER FREE PRODUCT.ADD SUITABLE ABSORBENT MATL(SAND, EARTH, OTHER) TO SPILL. MINIMIZE BREATHING VAPORS & amp; SKIN CONTACT. KEEP OUT OF SEWERS/WATERCOURSE W/DIKE/IMPOUND. Waste Disposal Methods: DISPOSE OF IN AN ENVRIONMENTALLY SAFE MANNER AND IN ACCORDANCE WITH ALL GOVERNMENT REGULATIONS TO INCLUDE LOCAL, STATE AND FEDERAL REQUIREMENT S. Handling And Storage Precautions: USE PRODUCT W/CAUTION AROUND HEAT, SPARKS, PILOT LIGHTS, STATIC ELECTRICITY AND OPEN FLAME.EMPTY CONTAINERS RETAIN RESIDUE.DO NOT ATTEMPT TO CLEAN. Other Precautions: EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED & PROMPTLY RETUREND TO DRUM RECONDITIONER.ALL OTHER CONTAINER SHOULD BE DISPOSED OF IN ENVIRONMENTALLY SAFE MANNER & amp; IAW GOVT REGS.DON'T PRESS/ CUT/WELD/BRAZE/ETC CONTAINERS NEAR FLAME

Fire and Explosion Hazard Information

Flash Point Method: COC

Flash Point: =215.C, 419.F

Extinguishing Media: FOAM, WATER SPRAY (FOG), DRY CHEMICAL, CARBON DIOXIDE AND VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS.

Fire Fighting Procedures: USE SUPPLIED AIR BREATH EQMPT AS NEEDED.H2O/FOAM MAY CAUSE FROTHING.USE H2O FOR COOLING PURPOSES.USE H2O SPRAY TO FLUSH SPILLS AWAY FROM EXPOSURES.

Unusual Fire/Explosion Hazard:

MINIMIZE BREATHING OF

GASES/VAPOR/FUMES/DECOMPOSITION PRODUCTS.DECOMP PROD UNDER FIRE CONDITIONS:FUMES,SMOKE,CARBON MONOXIDE, SULFUR OXIDES,OTHER PRODUCTS.

Control Measures

Ventilation: LOC EXHAUST TO CAPTURE VAPOR/MISTS/FUMES IF NECESSARY.PROVIDE VENT SUFFICIEN TO PREVE

NT EXCEEDING EXPOSURE LIMIT/BUILDUP

Protective Gloves: CHEM RESISTANT FOR PROLONGED EXPOSURE.

Eye Protection: SPLASH GOGGLES OR FACE SHIELD.

Other Protective Equipment: CHEM RESISTANT APRON OR OTHER IMPERVIOUS CLOTH IF NEEDED.

Work Hygienic Practices: KEEP CONTAINERS CLOSED WHEN NOT IN USE.DON'T STORE NEAR HEAT/SPARKS/ETC. USE APPROPRIATE EQUPMT. WASH HANDS AFT HANDLING

Supplemental Safety and Health: PRECISE COMPOSITION OF THIS MIXTURE IS

PROPRIETARY INFO. A MORE COMPLETE DISCLOSURE WILL

BE PROVIDED TO A PHYSICIAN

OR NURSE IN THE EVENT OF A MED EMERGENCY.

Physical/Chemical Properties

HCC: V6 Vapor Pres: NEGLIGIBLE Vapor Density: >AIR Spec Gravity: .8708/.8866 Viscosity: 6.5CST @100C Evaporation Rate & Reference: NEGLIGIBLE Solubility in Water: NEGLIGIBEL (Appearance and Odor: CLEAR LIQUID, YELLOW COLOR, MILD BLAND PETROLEUM ODOR. Percent Volatiles by Volume: NEGLI

Reactivity Data _____ Stability Indicator: YES Stability Condition To Avoid: AVOID HEAT, OPEN FLAMES. Materials To Avoid: OXIDIZING AGENTS. Hazardous Decomposition Products: HIGHLY DEPENDENT ON COMBUSTION CONDITIONS.MIX OF AIRBONRE SOLID, LIQ, PARTI, GAS; CO; FUMES; SMOKE; SULFUR OXIDES; UNID ORG CMPD Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: NOT RELEVANT. _____ **Toxicological Information** ______ _____ **Ecological Information** _____ _____ MSDS Transport Information _____ ______ **Regulatory Information** ===== ______ ______ Other Information _____ Transportation Information _____ Responsible Party Cage: 40310 Trans ID NO: 105724 Product ID: DRYDENE NON-DETERGENT MOTOR OILS, SAE 10, 20, 30, 40, 50. MSDS Prepared Date: 01/14/1994 Review Date: 03/15/2001 MFN :1 Net Unit Weight: 1.8 LBS Multiple KIT Number: 0 **Review IND: Y** Unit Of Issue: QT Container QTY: 1 Type Of Container: CAN Additional Data: PER MFG'S MSDS: DOT IDENTIFICATION NUMBER NOT APPLICABLE. _____ **Detail DOT Information** _____ ______ DOT PSN Code: ZZZ DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION _____

Detail IMO Informati

on

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

Detail IATA Information

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Information

=============

AFI PSN Code: ZZZ AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

_____ Product ID: DRYDENE NON-DETERGENT MOTOR OILS, SAE 10, 20, 30, 40, 50. Cage: 40310 Company Name: DRYDEN OIL CO INC Street: 9300 PULASKI HWY City: BALTIMORE MD Zipcode: 21220 Health Emergency Phone: 410-574-500/800-777-1466 Label Required IND: Y Date Of Label Review: 07/07 /1994 Status Code: C Label Date: 07/07/1994 Origination Code: F Eye Protection IND: YES Skin Protection IND: YES Signal Word: CAUTION **Respiratory Protection IND: YES** Health Hazard: Slight Contact Hazard: Slight Fire Hazard: None Reactivity Hazard: None Hazard And Precautions: EYE:MAY CAUSE IRRIT. SKIN:PROLONGED OR REPEATED CONTACT MAY CAUSE IRRIT. INGEST: RELATIVELY NON-TOXIC. INHAL: VAPOR PRESSURE IS VERY LOW. VAPOR INHAL UNDER AMBIENT TEMP CONDITONS IS NOT NORMALLY A PROBLEM. TARGET ORGAN

S:EYE/SKIN. FIRST AID: EYE:FLUSH W/CLEAR WATER FOR 15MINS OR TIL IRRIT SUBSIDES. IF PERSISTS CALL DR. SKIN:REMOVE CONTAMINATED CLOTH. WASH AREA THOROUGHLY W/SOAP & amp; WATER. INGEST: DO NO T INDUCE VOMIT. CALL DR IMMED. INHAL:NOT NORMALLY A PROBLEM. OVERCOME BY VAPOR FROM HOT PRODUCT REMOVE FROM EXPOSURE. CALL DR. GIVE OXY. IF OVER EXPOSED TO OIL MIST REMOVE FROM EXPOSURE TIL EXCESSIVE MIST OIL CONDITION SUBSIDES.

Disclaimer (pro

vided with this information by the compiling agencies): This

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability f

or such use. Any person

utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.