View NSN Online: https://aerobasegroup.kr/nsn/6850-00-297-3885 XEROX ENGINEERING SYSTEMS -- 8836 FUSER OIL, PARTNO:8R79 -- 6850-00-297-3885 ============= Product Identification =============== Product ID:8836 FUSER OIL, PARTNO:8R79 MSDS Date:03/10/1993 FSC:6850 NIIN:00-297-3885 MSDS Number: BTSFV === Responsible Party === Company Name: XEROX ENGINEERING SYSTEMS Address:5853 RUE FERRARI AVENUE City:SAN JOSE State:CA ZIP:95138 Country:US Info Phone Num:800-828-3571/716-422-2177 mergency Phone Num:716-422-2177/800-828-6571 CAGE:3T895 === Contractor Identification === Company Name: XEROX ENGINEERING SYSTEMS Address:5853 RUE FERRARI AVENUE Box:City:SAN JOSE State:CA ZIP:95138 Country:US Phone:800-828-3571/716-422-2177 CAGE:3T895 ======= Composition/Information on Ingredients ======== Ingred Name: POLYDIMETHYL SILOXANE

CAS:9016-00-6

RTECS #:TQ2690000 Fraction by Wt: 100%

Other REC Limits: NONE RECOMMENDED

====== Hazards Identification =======

========== LD50 LC50 Mixture:LD50(ORAL,RATS)=35G/KG,PRACTICA NONTOXIC Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: MAY CAUSE MINIMAL IRRITATION OF RESPIRATORY PASSAGES ON CONTINUOUS EXPOSURE TO HIGH CONCENTRATIONS. Explanation of Carcinogenicity: PER MSDS NONE PRESENT. Effects of Overexposure: MAY CASUE MINIMAL IRRITATION OF RESPIRATORY PASSAGES ON CONTINUOUS EXPOSURE TO HIGH CONCENTRATIONS. Medical Cond Aggravated by Exposure: NONE WHEN USED AS DESCRIBED BY PRODUCT LITERATURE. First Aid:EYE:FLUSH THOROUGHLY W/WATER. SKIN:WASH W/SOAP & WATER. INHAL:REMOVE FROM EXPOSURE. INGEST:DILUTE STOMACH CONTENTS W/SEVERAL GLASSES OF WATER. ============ Fire Fighting Measures ========================= Flash Point Method:COC Flash Point:>500F,>260C Extinguishing Media: FOAM, CARBON DIOXIDE, WATER SPRAY. Fir e Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard: NONE.

========= Accidental Release Measures ==============

COMPLETELY AS RESIDUE IS SLIPPERY.

Handling and

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Spill Release Procedures:SOAK UP WITH AN ASBSORBENT MATERIAL SUCH AS VERMICULITE OR OTHER ABSORBENT MATERIAL. CLEAN UYP SPILLS

============ Handling and Storage ===========================

Storage Precautions: USE REASONABLE CARE AND CAUTION. Other Precautions:NONE. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: NONE REQUIRED WHEN USED AS INTENDED IN XEROX PRODUCTS. Ventilation: NONE REQUIRED WHEN USED AS INTENDED IN XEROX PRODUCTS. Protective Gloves: PVC OR PLASTIC GLOVES RECOMMENDED. Eye Protection: NONE REQUIRED WHEN USED AS INTENDED Other Protective Equipment: NONE REQUIRED WHEN USED AS INTENDED IN XEROX PRODUCTS. Work Hygienic Practices: WASH HANDS AFTER HANDLING. Supplemental Safety and Health ======== Physical/Chemical Properties =========== HCC:N1 Boiling Pt:B.P. Text:300F,149C

Vapor Pres: