

FARWEST PAINT MFG CO -- TYPE I MASONRY WHITE BASE PAINT -- 8010-00-297-2136

===== Product Identification =====

Product ID:TYPE I MASONRY WHITE BASE PAINT

MSDS Date:03/01/1993

FSC:8010

NIIN:00-297-2136

MSDS Number: BTSWJ

==== Responsible Party ====

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:206-941

-1619

CAGE:6F266

==== Contractor Identification ====

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA, HEAVY ALKYLATED/ODORLESS MINERAL SPIRITS

CAS:64741-65-7

Fraction by Wt: 7.54%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MISTS

ACGIH TLV:5 MG/M3 AS OIL MISTS

Ingred Name:HYDROTREATED LIGHT PETR

OLEUM DISTILLATE

CAS:64742-47-8

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MISTS

ACGIH TLV:5 MG/M3 AS OIL MISTS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 1.07%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 0.24%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

A

CGIH TLV:100 PPM/125STEL;9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS UNKNOWN.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, CNS,
RESPIRATORY TRACT. ACUTE- IRRITATION OF EYES, SKIN & RESPIRATORY
SYSTEM. MAY CAUSE SENSITIZATION OF SKIN. EXCESSIVE OVEREXPOSURE M
AY

CAUSE UNCONSCIOUSNESS. HARMFUL IF INGESTED. CHRONIC- MAY CAUSE
PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, LOSS OF
CONSCIOUSNESS, IRRITATION OF EYES, SKIN, RESPIRATORY TRACT, SKIN
DEFATTING & SENSITIZATION

Medical Cond Aggravated by Exposure:NONE WHEN USED IN ACCORDANCE WITH
SAFE HANDLING INSTRUCTIONS.

===== First Aid Measures =====

First Aid:GET M

EDICAL HELP IF SYMPTOMS PERSIST. INHALATION: REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES: FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN: WASH WITH SOAP & WATER. INGESTION: DO NOT INDUCE VOMITING. KEEP PERSON WARM & QUIET. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:103F,39C

Lower Limits:0.7

Upper Limits:8.9

Extinguishing Media: USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON

DIOXIDE. WATER MAY BE UNSUITABLE.

Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard: VAPORS MAY FORM AN EXPLOSIVE MIXTURE WITH AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS ETC.. CLOSED CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures: WEAR

PROTECTIVE EQUIPMENT. ELIMINATE SOURCES

OF IGNITION. VENTILATE AREA. CONTAIN SPILL. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND/USE PUMP (EXPLOSION PROOF). PREVENT LIQUID FROM ENTERING SEWERS, WATERWAYS OR LOW AREAS.

Neutralizing Agent: NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL, VENTILATED AREA, AWAY FROM HEAT, FLAMES, SPARKS AND INCOMPATIBLE MATERIALS. USE APPROVED BONDING AND GROUNDING PROCEDURES.

Other Precautions: USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. DO NOT BREATHE VAPOR AND SPRAY MIST. KEEP OUT OF REACH OF CHILDREN. DO NOT WELD ON FULL/EMPTY CONTAINER

===== Exposure Controls/Personal Protection =====

Respiratory Protection: IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH APPROVED RESPIRATORS. RE

SPIRATORS SHOULD BE SELECTED BASED ON THE FORM AND CONCENTRATION OF CONTAMINANT IN AIR & IN ACCORDANCE WITH OSHA (29 CFR 1910.134).

Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE.

LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED.

Protective Gloves:NEOPRENE, NITRILE, VPC OR NATURAL RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION, SAFETY SHOWER,

INDUSTRIAL-TYPE WORK CLOTHING, APRON AND BARRIER CREA

M FOR EXPOSED

SKIN

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:282F - 390F

Vapor Pres:6.0 @ 68F

Vapor Density:>1

Spec Gravity:1.384

Evaporation Rate & Reference: