View NSN Online: https://aerobasegroup.kr/nsn/8010-00-550-4261

Product ID:TENNANT STS (420) STD. TRAFFIC TWO-COAT #08511 MSDS Date:01/01/1992 FSC:8010 NIIN:00-550-4261 MSDS Number: BTSXF === Responsible Party === Company Name: TENNANT CO Address:701 N LILAC DR Box:1452 City:MINNEAPOLIS State:MN ZIP:55440-1452 Country:US Info Phone Num:612-540-138 1 Emergency Phone Num:612-544-5163 Preparer's Name:NORM GILL CAGE:59500 === Contractor Identification === Company Name: TENNANT CO Address:701 N LILAC DR Box:1452 **City:MINNEAPOLIS** State:MN ZIP:55440-1452 Country:US Phone:612-540-1556/800-553-8033 CAGE:59500

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 50-60% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:100 PP M/150STEL;9394 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:URETHANE PREPOLYMER CAS:9040-80-6 Fraction by Wt: 40-50% % Other REC Limits:NONE RECOMMENDED

Ingred Name:TOLUENEDIISOCYANATE (MIXED ISOMERS) (SARA III) (HZD) CAS:26471-62-5 RTECS #:NQ9490000 Fraction by Wt: < 1% Other REC Limits:NONE RECOMMENDED ACGIH TLV:0.005PPM/0.02STEL;94 EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

LD50 LC50 Mixture:NOT GIVEN FOR PRODUCT AS A WHOLE Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic: CONTAINS MATERIALS WHICH MAY CAUSE SKIN IRRITATION. CONTAINS MATERIALS WHICH MAY CAUSE EYE IRRITATION AND EYE INJURY. CONTAINS MATERIAL WHICH CAN CAUSE A BURNING SENSATION, VOMITING, DIARRHEA, DROWSIN ESS AND TISSUE DAMAGE. ASPIRATION CAN CAAUSE CHEMICAL PNEUMONIA. INHALATION MAY CAUSE ANESTHETIC EFFECTS. Explanation of Carcinogenicity: TOLUENE 2,4/2,6-DIISOCYANATE (TDI) IS LISTED AS A CARCINOGEN BY NTP AND IARC. Effects of Overexposure: EYE IRRITATION, EYE INJURY, SKIN IRRITATION, NAUSEA, VOMITING, DIARRHEA, BURNING SENSATION IN GI TRACT, TISSUE DAMAGE IN GI TRACT, CHEMICAL PNEUMONIA, RESPIRATORY TRACT

IRRITATION, ACUTE NERVOUS SYSTEM DEPRESSION, HEADACHE, DIZZINESS, STAGGERING GAAIT, CONFUSION AND UNCONSCIOUSNESS. CHRONIC: PERMANENT BRAIN, CNS INJURY.

Medical Cond Aggravated by Exposure:

NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. IN HALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

Flash Point Method:SCC Flash Point:80.0F,26.7C Lower Limits:1.0 % Upper Limits:7.6 % Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND FLAME. CLOSED

CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Spill Release Procedures: ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. WEAR PROPER PERSONAL PROTECTIVE EQUIPMENT. CONTAIN SPILL. REMOVE WITH INERT ABSORBENT. SCRUB WITH SOAP AND WATER. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:STORE IN A COOL, DRY PLA CE WITH

ADEQUATE VENTILATION. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS 1C FLAMMABL

Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED CONTACT WITH SKIN. CONTAMINATED CLOTHING SHOULD BE REMOVED IMMEDIATELY. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO NOT SPRAY APPLY THIS PRODUCT.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:WEAR A CHEMICAL RESPIRATOR APPROVED FOR ORGA

NIC

VAPORS (NIOSH 23C OR EQUIVALENT) DURING THE APPLICATION AND UNTIL WORK AREA HAS BEEN EXHAUSTED OF ALL VAPORS. Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL) VENTILATION TO MAINTAIN EXPOSURE LEVELS. Protective Gloves: IMPERVIOUS Eye Protection: SAFETY GLASSES OR GOGGLES Other Protective Equipment: PROTECTIVE CLOTHING AS REQUIRED TO AVOID SKIN CONTACT. AN EMERGENCY EYE WASH STATION AND SHOWER SHOULD BE AVAILABLE. Work Hygienic Practices: WASH WITH SOAP AND WATER AFTER HANDL ING PRODUCT AND BEFORE EATING DRINKING OR SMOKING. Supplemental Safety and Health INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. HCC:F3 Boiling Pt:B.P. Text:295F,146C Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:6 MM HG Vapor Density:> 1 Spec Gravity:0.98 Evaporation Rate & amp; Reference: < 1 (N-BUTYL ACETATE = 1) S olubility in Water:NOT SOLUBLE Appearance and Odor: CLEAR LIQUID, AROMATIC ODOR Percent Volatiles by Volume:55 % Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid: HEAT, OPEN FLAME. DO NOT APPLY TO HOT SURFACES. Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE AND NITROGEN OXIDES IN VARYING QUANTITIES.

======== Disposal Considerations =========

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.