

FLAMEMASTER CORP THE CHEM SEAL DIV -- CS 3100 TYPE II CLASS 1 (PART A) --
8030-00-881-2618

===== Product Identification =====

Product ID:CS 3100 TYPE II CLASS 1 (PART A)

MSDS Date:07/19/1991

FSC:8030

NIIN:00-881-2618

Kit Part:Y

MSDS Number: BTTJC

=== Responsible Party ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

In

fo Phone Num:818-982-1650 FAX 818-765-5603

Emergency Phone Num:818-982-1650 800-424-9300(CHEMTREC]

Preparer's Name:HERBERT MOORE

CAGE:14439

=== Contractor Identification ===

Company Name:FLAMEMASTER CORP THE CHEM SEAL DIV

Address:11120 SHERMAN WAY

Box:City:SUN VALLEY

State:CA

ZIP:91352-4949

Country:US

Phone:818-982-1650

CAGE:14439

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 2%

Other REC Limi

ts:NONE RECOMMENDED
OSHA PEL:200 PPM; Z-2
ACGIH TLV:S, 50 PPM; 9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:MAY
CAUSE IRRITATION.INGEST:MAY CAUSE GI TRACT IRRITATION.INHAL:MAY
CAUSE RESPIRATORY IRRITATION.CHRONIC:DERMATITIS,LIVER AND KIDNEY
D
AMAGE.
Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%
WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.
Effects of Overexposure:INHAL/INGEST:MUSCLE
WEAKNESS,HEADACHE,NAUSEA,IMPAIRED COORDINATION.
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING
SKIN,LIVER,KIDNEY OR RESPIRATORY AILMENTS MAY BE AT INCREASED RISK
FROM EXPOSURE.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WA
SH WITH WATER.EYES:FLUSH
WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR
ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE VOMITING.GET
PROMP T QUALIFIED MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:130F,54C
Lower Limits:1.3
Upper Limits:7.1
Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE,FOAM.
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND
FULL

PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER
FOG.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR,CAN TRAVEL
DISTANCES ALONG THE GROUND,AND FLASHBACK AT THE SOURCE.HAZARDOUS
FUMES MAY BE EVOLVED FROM FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION.USE PROPER
RESPIRATORY AND PROTECTIVE EQUIPMENT.SHUT OFF LEAK IF
SAFE.DIKE.SOAK UP WITH A NON-COMBUSTIBLE INERT
ABSORBA

NT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSAL.WASH
SPILL AREA TO REMOVE SLIPPINESS.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED
PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:WASH AFTER AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN
ENC

LOSED SPACES WHERE VAPORS ARE ABOVE 200PPM,USE A SELF-CONTAINED
BREATHING APPARATUS.

Ventilation:LOCAL VENTILATION AT THE WORKSITE;MECHANICAL(GENERAL)
VENTILATION TO MAINTAIN TLV/PEL.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES WITH FACE SHIELD

Other Protective Equipment:PROTECTIVE CLOTHING,AS NEEDED.PROVIDE A
LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET
CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK
AREA.

Supplemental Safety and Health

KEY1;F4.THIS ITEM IS A MARINE POLLUTANT.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:231F,111C

Vapor Pres:22

Vapor Density:3.2

Spec Gravity:1.68

pH:7.2

Viscosity:500 POISES

Evaporation Rate & Reference:2.0 (N-BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:PASTE;WHITE;POLYSULFIDE ODOR

Percent Volatiles by Volume:5

===== Stability and Reactivity D

ata =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: HIGH HEAT, SOURCES OF IGNITION.

Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE, HYDROGEN SULFIDE, SULFUR DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This info

mation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.