

EASTMAN KODAK COMPANY -- KODAK RAPID FIXER CAT#: 186 6342, WORKING SOLUTION (PAPER) -- 6750-01-360-5173

===== Product Identification =====

Product ID:KODAK RAPID FIXER CAT#: 186 6342, WORKING SOLUTION (PAPER)

MSDS Date:11/08/1995

FSC:6750

NIIN:01-360-5173

Kit Part:Y

MSDS Number: BTTWH

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:

14650

Country:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====

==== Composition/Information on Ingredients =====

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 90-95% %  
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM THIOSULFATE  
CAS:7783-18-8  
RTECS #:XN6465000  
Fraction by Wt: 5-10% %  
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM ACETATE  
CAS:126-96-5  
RTECS #:AJ4375000  
Fraction by Wt: 1-5% %  
Other REC Limits:NONE RECOMMENDED

Ingred Name:BORIC ACID  
CAS:10043-35-3  
RTECS #:ED4550000  
Fraction by Wt: < 1%  
Other REC  
Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM SULFITE (SARA III)  
CAS:10196-04-0  
Fraction by Wt: < 1%  
Other REC Limits:NONE RECOMMENDED  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ACETIC ACID (SARA III)  
CAS:64-19-7  
RTECS #:AF1225000  
Fraction by Wt: < 1%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:10 PPM  
ACGIH TLV:10 PPM/15 STEL; 9394  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

==== Hazards Identification =====

LD50 LC50 Mixture:NOT GIVEN FOR WORKING

## SOLUTION

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EXPECTED TO BE A LOW INHALATION HAZARD FOR RECOMMENDED HANDLING. MAY CAUSE TRANSIENT EYE IRRITATION. LOW SKIN CONTACT HAZARD FOR RECOMMENDED HANDLING. EXPECTED TO BE A LOW INGESTION HAZARD.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:EYE IRRITATION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

### ===== First Aid Measures =====

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: WASH OUT IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN: WASH WITH SOAP AND WATER . GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

### ===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE

Lower Limits:NOT GIVEN

Upper Limits:NOT GIVEN

Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

### ===== Accidental Release Measures =====

Spill Release Procedures:MAY REQUIRE NEUTRALIZATION. FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNTS OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE TO REMOVE RESIDUAL CONTAMINATION. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

### ===== Handling and Storage =====

Handling and Storage Precautions:USE WITH ADEQ

UATE VENTILATION. WASH  
THOROUGHLY AFTER HANDLING. KEEP FROM CONTACT WITH OXIDIZING  
MATERIALS. KEEP CONTAINER TIGHTLY CLOSED.  
Other Precautions:KEEP AWAY FROM INCOMPATIBLE MATERIALS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.  
Ventilation:GOOD GENERAL VENTILATION, TYPICALLY 10 AIR CHANGES PER  
HOUR, SHOULD BE USED. RATES SHOULD MATCH CONDITIONS.  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES W/SIDE SHIE  
LDS OR GOGGLES  
Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO  
PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE  
AVAILABLE.  
Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER  
BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.  
Supplemental Safety and Health  
REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

===== Physical/Chemical Properties =====

HCC:C3  
Boiling Pt:B.P. Text:>212F,>100C  
Melt/F  
reeze Pt:M.P/F.P Text:NOT GIVEN  
Vapor Pres:18  
Vapor Density:0.6  
Spec Gravity:1.04  
pH:4.4  
Evaporation Rate & Reference:NOT GIVEN  
Solubility in Water:COMPLETE  
Appearance and Odor:COLORLESS LIQUID, SLIGHT SULFUR DIOXIDE ODOR  
Percent Volatiles by Volume:90-95%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
BASES, SODIUM HYPOCHLORITE (BLEACH), STRONG OXIDIZING AGENTS, STRONG  
ACIDS.  
Stability Condition to Avoid:NONE SPECIFIED BY

MANUFACTURER.

Hazardous Decomposition Products:AMMONIA, NITROGEN OXIDES, SULFUR DIOXIDE, CHLORAMINE.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS. MAY REQUIRE NEUTRALIZATION IF PH < 2.0 OR PH > 12.5. DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND L OCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies ):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.