

QCM COMPANY -- A-1104 PRIMER FOR PLASTISOL COATINGS -- 8030-01-041-1599

=====
Product Identification
=====

Product ID:A-1104 PRIMER FOR PLASTISOL COATINGS

MSDS Date:05/20/1994

FSC:8030

NIIN:01-041-1599

Kit Part:Y

MSDS Number: BTWCS

=== Responsible Party ===

Company Name:QCM COMPANY

Address:930 SOUTH CENTRAL AVENUE

City:KENT

State:WA

ZIP:98032

Country:US

Info Phone Num:206-859-0933

Emergency Phone

Num:206-859-0933/800-424-9300 CHEMTREC

Preparer's Name:ROY WHEELDON

CAGE:8L872

=== Contractor Identification ===

Company Name:Q C M CO

Address:930 CENTRAL AVE S

Box:City:KENT

State:WA

ZIP:98032-6105

Country:US

Phone:253-859-0933, FAX 253-859-0935

CAGE:8L872

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ETHYL KETONE (SARA III) (SEC 304: FINAL RQ 5000 LBS)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 61.8%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200

PPM
ACGIH TLV:200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHANOL (SEC 304: FINAL RQ 100 LBS)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM

Ingred Name:VOC PER LITER: 5.78 LBS/GAL (692 GRAMS/LITER); VOC PER
LITER MINUS EXEMPT SOLVENTS & WATER: 5.78 LBS/GAL
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inh
Absorption: YES Skin: YES Ingestion: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: SKIN, EYE, RESPIRATORY AND
GASTROINTESTINAL IRRITATION, POSSIBLY SEVERE. EXCESSIVE INHALATION
MAY PRODUCE CENTRAL NERVOUS SYSTEM DEPRESSION.
Explanation of Carcinogenicity: NONE KNOWN

===== First Aid Measures =====

First Aid: EYE CONTACT: IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER
FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.
SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING. WASH THOROUGHLY WITH SOAP AND WATER.
INHALATION: SEEK IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE
VOMITING.

===== Fire Fighting Measures =====

Flash Point Method: TCC
Flash Point: 16.0F, -8.9C
Lower Limits: 1.8
Upper Limits: 19.0
Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL
Fire Fighting Procedures: USE SELF-CONTAINED BREATHING APPARATUS WITH
FULL FACEPIECE. COOL CONTAINERS IN VICINITY WITH WATER

SPRAY.

Unusual Fire/Explosion Hazard:KEEP ALL IGNITION SOURCES AWAY. GROUND ALL CONTAINERS. VAPORS MAY TRAVEL TO SOURCE OF IGNITION AND CAUSE FLASHBACK. FIRE CAUSES ACID SMOKE AND/OR FUMES.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. SMALL SPILLS: TAKE UP WITH ABSORBENT MATERIAL. LARGE SPILLS: DAM AND RECOVER.

===== Handling and Storage =====

Handling and Storage Prec

autions:AVOID HIGH TEMPERATURE AREA AND IGNITION SOURCES. ALL HANDLING EQUIPMENT SHOULD BE GROUNDED AND EXPLOSION PROOF. AVOID ALL PERSONAL CONTACT.

Other Precautions:WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE APPROVED SELF-CONTAINED BREATHING APPARATUS IF NECESSARY.

Ventilation:LOCAL EXHAUST: NECESSARY. MECHANICAL (GENERAL): NECESSARY.

Protective Gloves:RUBBER OR NEOPRENE

Eye Protection:CHEMICAL SP

ALSH GOGGLES

Other Protective Equipment:SAFETY SHOWER. EYE WASH STATION.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:165F,74C

Vapor Pres:85 @ 20C

Vapor Density:2.4

Spec Gravity:0.86 (WATER=1)

Evaporation Rate & Reference:4.6 (BU AC=1)

Solubility in Water:APPRECIABLE

Appearance and Odor:CLEAR TO AMBER LIQUID, KETONE ODOR

Percent Volatiles by Volume:86

===== Stability and Reactivity Data =====

====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: STRONG ACIDS OR OXIDIZERS, HIGH TEMPERATURES

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, MISCELLANEOUS HYDROCARBON

Conditions to Avoid Polymerization: STRONG OXIDIZERS, ALL IGNITION SOURCES.

===== Disposal Considerations =====

Waste Disposal Methods: ACCORDING TO STATE, FEDERAL, AND LOCAL REGULATIONS. HAZARDOUS WASTE CODE: F005, D001, U159, FLAMMABLE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.