

PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV -- ENAMEL ALKYD, SEMI-GLOSS LO VOC
CNT GRAY 26555, ID 775662 -- 8010-00-298-3857

=====
Product Identification
=====

Product ID:ENAMEL ALKYD, SEMI-GLOSS LO VOC CNT GRAY 26555, ID 775662

MSDS Date:01/06/1994

FSC:8010

NIIN:00-298-3857

MSDS Number: BTZYR

==== Responsible Party ====

Company Name:PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV

Box:2153

City:

WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLISON

CAGE:61196

==== Contractor Identification ====

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ACETATE (SOLVENT) (VAPOR PRESSURE 10 MM HG @ 20C)
(LFL 1.7; UFL 7.6)

CAS:123-86-4

RTECS #:A

F7350000

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:150 PPM;STEL 200 PPM

ACGIH TLV:150 PPM;STEL 200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SOLVENT) (SARA III) (VAPOR PRESSURE 5 MM HG @ 20C)
(LFL 1.0; UFL 7.0)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE (PIGMENT)

7-7
RTECS #:XR2275000
Fraction by Wt: 15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:SILICA, AMORPHOUS HYDRATED (PIGMENT)
CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:TALC (PIGMENT)
CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: 20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3; 20 MPPCF
ACGIH TLV:2 MG/M3; 15 MPPCF

Ingred Name:SILICA, CRYSTALLINE
CAS:14808-6
0-7

RTECS #:VV7330000
Fraction by Wt: 115F) AND SOURCES
OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY
WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE & CARBON
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, &
LOCAL LAWS OR REGULATIONS. THIS PRODUCT, IF DISCARDED DIRECTLY,
WOULD BE CLASSIFIED A HAZARDOUS WASTE BASED ON ITS IGNITABILITY

CHARACTERISTIC (FLASH POINT 140F OR LESS). PROPER RCRA
CLASSIFICATION: D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume

responsibility for the suitability of this information to their particular situation.