

BAKER SEALANTS AND COATINGS CO -- CEMENT, EPOXY, METAL REPAIR AND HULL SMOOTHING
P/N X-949R -- 8030-00-670-8553

===== Product Identification =====

Product ID:CEMENT, EPOXY, METAL REPAIR AND HULL SMOOTHING P/N X-949R

MSDS Date:02/12/1990

FSC:8030

NIIN:00-670-8553

Kit Part:Y

MSDS Number: BVBFM

=== Responsible Party ===

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:B

City:JER

SEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone Num:201-333-6986

Emergency Phone Num:201-333-6986/800-424-9300 CHEMTREC

Preparer's Name:MARIO NAVARRO

CAGE:34094

=== Contractor Identification ===

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

=====

Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS MATERIAL (NON-HAZARDOUS AS DEFINED PER PED-STD 313C, PAR 3.3)

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:EYES: CAN CAUSE IRRITATION. SKIN: CAN CAUSE REDDENING, IRRITATION, DERMATITIS, POSSIBLE SENSITIZATION.

INHALATION: EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL AND RESPIRATORY IRRITATION. INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION,NAUSEA, VOMITING, AND DIARRHEA.

Medical Cond Aggravated by Exposure:SKIN SENSITIZATION

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER, GET MEDICAL ATTENTION. SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. IF IRRITATION OR RASH DEVELOPS, GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:>150F,>66C
Autoignition Temp:Autoignition Temp Text:150 F
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER SPRAY
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH VERMICULITE, FLOOR ABSORBENT. PUT INTO CONTAINERS FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT ROOM TEMPERATURE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF NEEDED--ORGANIC CHEMICAL CARTRIDGE RESPIRATOR.
Ventilation:GOOD MECHANICAL VENTILATION AND LOCAL EXHAUST.
Protective Gloves:NATURAL RUBBER GLOVES
Eye Protection:CHEM SPLASH GOGGLES
Supplemental Safety

and Health
KEY1:F8.

===== Physical/Chemical Properties =====

HCC:V4
Spec Gravity:1.60
Solubility in Water:NEGLIBIBLE
Appearance and Odor:WHITE PASTE; ODOR CHARACTERISTIC

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, STRONG ALKALIES AND
AMINES
Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE AND
VARIOUS HYDROCARBONS, ETC

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE WITH ALL LOCAL STATE AND FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document
should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.