

EASTMAN KODAK COMPANY -- 156 4632 FIRST DEVELOPER,PROCESS E-6,WORKING SOLUTION --  
6750-01-042-6480

===== Product Identification =====

Product ID:156 4632 FIRST DEVELOPER,PROCESS E-6,WORKING SOLUTION

MSDS Date:01/14/1998

FSC:6750

NIIN:01-042-6480

MSDS Number: BVBJY

==== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info

Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

==== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/I

information on Ingredients =====

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 85 - 90%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

Ingred Name:POTASSIUM SULFITE  
CAS:10117-38-1  
RTECS #:WT3530000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM CARBONATE  
CAS:584-08-7  
RTECS #:TS7750000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM HYDROQUINONE MONOSULFONATE  
CAS:21799-87  
-1  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:DIETHYLENE GLYCOL  
CAS:111-46-6  
RTECS #:ID5950000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM CARBONATE  
CAS:497-19-8  
RTECS #:VZ4050000  
Fraction by Wt: 212F,>100C  
Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN  
Decomp Temp:Decomp Text:NOT GIVEN  
Vapor Pres:18  
Vapor Density:0.6  
Spec Gravity:1.03 - 1.09  
pH:9.7  
Evaporation Rate & Reference:NOT GIVEN  
Solubility in Water:COMPLETE  
Appearance and Odor:LIGHT

BROWN LIQUID, ODORLESS  
Percent Volatiles by Volume:85- 90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

NONE WITH COMMON MATERIALS AND CONTAMINANTS WITH WHICH THE MATERIAL MAY  
REASONABLY COME INTO CONTACT.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: SULFUR DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: DISCHARGE, TREATMENT

OR DISPOSAL MAY BE SUBJECT

TO FEDERAL, STATE OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNT  
OF WATER, IF ALLOWED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent  
professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.