View NSN Online: https://aerobasegroup.kr/nsn/5970-00-835-1012

VARFLEX CORPORATION -- VARGLAS SILICONE RESIN 500 -- 5970-00-835-1012

Product ID:VARGLAS SILICONE RESIN 500 MSDS Date:02/14/1992 FSC:5970 NIIN:00-835-1012 MSDS Number: BVFSB === Responsible Party === Company Name: VARFLEX CORPORATION Address:512 WEST COURT STREET City:ROME State:NY ZIP:13440 Country:US Info Phone Num:315-336-4400 Emergency Phone Num:315-336-4400 Ρ reparer's Name:UNREADABLE CAGE:79074 === Contractor Identification === Company Name: VARFLEX CORPORATION Address:512 WEST COURT STREET Box:City:ROME State:NY ZIP:13440 Country:US Phone:315-336-4400 CAGE:79074

Ingred Name: FIBROUS GLASS Other REC Limits: NONE RECOMMENDED OSHA PEL:5 MG/M3 RDUST ACGIH TLV:10 MG/M3 TDUST 9394

Ingred Name:SILICONE COATING-METHYL, PHENYL Other REC Limits:NONE RECOMMENDED

======= Hazar

LD50 LC50 Mixture: ORAL LD50 (RAT) IS UNKNOWN. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: EYES: MAY PRODUCE TEMPORARY MECHANICAL IRRITATION. SKIN: MAY PRODUCE ITCHING AND TEMPORARY MECHANICAL IRRITATION. INHALATION: MAY CAUSE IRRITATION OF MOUTH, NOSE, AND THROAT, INGESTION: NONE SP ECIFIED, CHRONIC: NONE SPECIFIED. Explanation of Car cinogenicity:NONE. Effects of Overexposure: EYES: IRRITATION. SKIN: ITCHING, IRRITATION. INHALATION: IRRITATION OF MOUTH, NOSE, THROAT. Medical Cond Aggravated by Exposure: PERSON WITH A HISTORY OF CHRONIC RESPIRATORY OR SKIN CONDITIONS THAT ARE AGGRAVATED BY MECHANICAL IRRITANTS MAY BE AT INCREASED RISK FROM EXPOSURE. First Aid: EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTI ON. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN AREA WITH SOAP AND WATER. DO NOT RUB OR SCRATCH IRRITATED AREAS. I NHALATION: MOVE TO FRESH AIR. IF ADVERSE SYMPTOMS DEVELOP OR PERSIST, GET MEDICAL ATTENTION. Extinguishing Media:WATER, FOAM, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. **Unusual Fire/Explosion Hazard:NONE** ======== Spill Release Procedures: FOR DUST AND FIBERS GENERATED DURING FABRICATION, VACUUM AND CONTAINERIZE FOR LATER DISPOSAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: STORE IN THE ABSENCE OF DIRECT

SUNLIGHT AND AT A RELATIVE HUMIDITY OF 30-60%. USE PROTECTIVE GLOVES IF YOU HAVE SENSITIVE SKIN. Other Precautions:NONE SPE CIFIED BY MANUFACTURER.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: NONE NORMALLY REQUIRED. Ventilation: USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW REGULATORY LIMITS. Protective Gloves: WORK GLOVES WHEN HANDLING. Eye Protection: WEAR SAFETY GLASSES. Other Protective Equipment:NONE Work Hygienic Practices: WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health NONE HCC:N1 Spec Gravity:1.2 Appearance and Odor: SILICONE RESIN COATED FIBERGLASS, COLOR BLACK. NO ODOR. 2.5 WIDE X 3.5 FEET LON Stability Indicator/Materials to Avoid:YES NONE KNOWN. Stability Condition to Avoid:NONE KNOWN. Hazardous Decomposition Products: SIZINGS AND BINDERS MAY DECOMPOSE IN FIRE PRIMARILY TO CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER HYDROCARBONS. Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:DISPOSE OF WASTE IN MUNICIPAL OR INDUSTRIAL LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America i

n no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.