

ALPHA METALS -- 711-35 FLUX -- 3439-00-602-5965

===== Product Identification =====

Product ID:711-35 FLUX

MSDS Date:06/03/1986

FSC:3439

NIIN:00-602-5965

MSDS Number: BVFXQ

=== Responsible Party ===

Company Name:ALPHA METALS

Address:600 ROUTE 440

City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone Num:201-434-6778

Emergency Phone Num:201-434-6778/800-424-9300(CHEMTREC)

CAGE:96613

=== Contract

or Identification ===

Company Name:FRYS METALS INC (FORMER ALPHA METALS)

Address:600 ROUTE 440

Box:City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Phone:201-434-6778

CAGE:96613

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 25-50%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:400 PPM/500STEL;9394

Ingred Name:SEC-BUTYL ALCOHOL (SARA III)

CAS:78-92-2

RTECS #:EO1750000

Fra

ction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:150 PPM
ACGIH TLV:100 PPM; 9394

Ingred Name:ETHYL ALCOHOL (ETHANOL)
CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9394

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION- CAN CAUSE NASA
L

IRRITATION. INGESTION- CAN CAUSE GASTROINTSTINAL IRRITATION.
SKIN- PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS. EYES-
CAN CAUSE SEVERE IRRITATION.

Effects of Overexposure:INHALATION- DIZZINESS, NAUSEA, HEADACHE.
INGESTION- NAUSEA, VOMITING AND DIARRHEA. SKIN- DEFATTING. EYES-
TEARING, BLURRED VISION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION- RE
MOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS
DIFFICULT, ADMINISTER OXYGEN. INGESTION- CALL PHYSICIAN OR POISON
CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN
UNCONSCIOUS PERSON. SKIN- WASH EXPOSED AREA WITH SOAP AND WATER.
REMOVE CONTAMINATED CLOTHING. EYES- FLUSH WITH LARGE AMOUNTS OF
WATER LIFTING UPPER AND LOWER LIDS OCCASIONALLY. GET MEDICAL
ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Fla

sh Point:64.0F,17.8C

Lower Limits:2.0

Upper Limits:12.0

Extinguishing Media:CARBON DIOXIDE OR DRY CHEMICAL.

Fire Fighting Procedures:USE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS IN ENCLOSED AREA.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:SMALL: VENTILATE AREA. ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD. LARGE: VENTILATE AREA. EL

IMINATE IGNITION

SOURCES. WEAR PROTECTIVE EQUIP MENT. DIKE AREA. PUMP LIQUID TO SALVAGETANK.

===== Handling and Storage =====

Handling and Storage Precautions:OBSERVE PRECAUTIONS FOR A FLAMMABLE LIQUID. KEEP CONTAINER CLOSED WHEN NOT IN USE. STORE AWAY FROM IGNITION SOURCES. STORE IN COOL, DRY AREA.

Other Precautions:USE ADEQUATE VENTILATION. READ ALL CONTAINER LABELING. AVOID THE USE OF BRASS DRUM SPIGOTS. USE POLYETHYLENE, POLYPROPY

LENE, TEFLON OR STAINLESS STEEL. EMPTY CONTAINERS MAY RETAIN PRODUCT RESIDUES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF THRESHOLD LIMIT VALUE IS EXCEEDED, USE NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV'S.

Protective Gloves:WEAR RESISTANT GLOVES.

Eye Protection:CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:

PROVIDE EEYE BATH NEAR WORK SITE.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:180F,82C

Vapor Pres:33 MMHG

Vapor Density:2.1

Spec Gravity:0.875

Evaporation Rate & Reference:2.8 (N-BUTYL ACETATE=1)

Solubility in Water:SLIGHT

Appearance and Odor:CLEAR, AMBER LIQUID, NONRESIDUAL ODOR.

Percent Volatiles by Volume:65

===== Stability and Reactiv

ity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: HEAT, SPARKS AND OPEN FLAMES.

Hazardous Decomposition Products: CARBON DIOXIDE AND CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DESTROY BY APPROVED INCINERATION OR DEPOSIT IN
APPROVED LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use

by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.