View NSN Online: https://aerobasegroup.kr/nsn/6750-01-353-4889

EASTMAN KODAK CO. -- 139 7215 KODAK INDUSTREX DEVELOPER REPLRNISHER, PART C --

6750-01-353-4889

Product ID:139 7215 KODAK INDUSTREX DEVELOPER REPLRNISHER, PART C

MSDS Date:04/08/1998

FSC:6750

NIIN:01-353-4889

Kit Part:Y

MSDS Number: BVFZQ === Responsible Party ===

Company Name: EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD Box:City:ROCHESTER

State:NY

ZIP:14650-3129 Country:US

Phone:800-828-6203

CAGE:5K871

====== Composition/Information on I

ngredients =======

Ingred Name:WATER

CAS:7732-18-5 RTECS #:ZC0110000

RTECS #:ZC0110000 Fraction by Wt: 65-70%

Other REC Limits: NONE RECOMMENDED

Ingred Name:GLUTARALDEHYDE-BIS-SODIUM BISULFITE,

CAS:7420-89-5

Fraction by Wt: 20-25%

Other REC Limits: NONE RECOMMENDED

Ingred Name: GLUTARALDEHYDE

CAS:111-30-8

RTECS #:MA2450000 Fraction by Wt: 10-15%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:C 0.2 PPM

ACGIH TLV:C 0.2 PPM; 9495

Ingred Name: ACETIC ACID (CERCLA)

CAS:64-19-7

RTECS #:AF1225000 Fraction by Wt: 212F

,>100C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Decomp Temp:Decomp Text:NOT GIVEN

Vapor Pres:18 MMHG Vapor Density:0.6 Spec Gravity:1.155

pH:3.0

Evaporation Rate & Dr. Reference: NOT GIVEN

Solubility in Water: COMPLETE

Appearance and Odor:LIQUID, CLEAR-BROWN, ALDEHYDE ODOR.

Percent Volatiles by Volume:75-80

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURE

R. Hazardous Decomposition Products: SULFUR DIOXIDE. CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF SULFUR. Conditions to Avoid Polymerization: HAZARDOUS POLYMERIZATION MAY OCCUR.

======= Disposal Considerations ===========

Waste Disposal Methods: DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE, OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EV EN AFTER CONTAIN ER IS EMPTIED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever. expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their pa

rticular situation.