View NSN Online: https://aerobasegroup.kr/nsn/5960-01-316-8100 VARIAN ASSOCIATE INC; CROSSED FIELD & RECEIVER PROT -- VDU-1120 -- 5985-01-316-8100 Product ID:VDU-1120 MSDS Date: 08/26/1994 FSC:5985 NIIN:01-316-8100 MSDS Number: BVHLX === Responsible Party === Company Name: VARIAN ASSOCIATE INC; CROSSED FIELD & RECEIVER PROT Address:150 SOHIER RD City:BEVERLY State:MA ZIP:01915-1018 Country:US Info Phone Num:508-922-6000 EXT.28 Emergency Phone Num:508-922-6000 EXT.285 Preparer's Name: FRANK E. TROJAN CAGE:88236 === Contractor Identification === Company Name: COMMUNICATIONS AND POWER INDUSTRIES INC Address:150 SOHIER RD City:BEVERLY State:MA ZIP:01915-5595

Country:US

Phone:978-922-6000 EXT.285

CAGE:88236

======= Composition/Information on Ingredients ========

Ingred Name:TRITIUM

CAS:10028-17-8

Other REC Limits: NONE RECOMMENDED

========== Hazards Identification ===============

Routes

of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:OVEREXPOSURE: SIGNIFICANT EXPOSURE TO A RADIONUCLIDE MAY CAUSE CANCER. Explanation of Carcinogenicity:NOT LISTED IN NTP, IARC, OR SOHA. Effects of Overexposure:TRITIUM IS A BETA EMITTER. IF EXPOSURE IS SUSPECTED, SEEK MEDICAL ATTENTION, URINE ASSAY FOR TRITIUM IS THE ONLY MEANS OF MEASURING THE DEGREE OF EXPOSURE. Medical Cond Aggravated by Exposure :HEALING OF DAMAGED TISSUE MAY BE PROLONGED.
======================================
First Aid:SKIN CONTACT: FLUSH WITH WATER FOR 15 MINUTES. EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES. INHALATION: REMOVE TO FRESH AIR. INGESTION: A HIGH ORAL FLUID INTAKE SHOULD BE ADMINISTERED FOLLOWING TRITI UM EXPOSURE.
======== Accidental Release Measures =========
Spill Release Procedures:NONE SPECIFIED BY MANUFACTURER.
====== Handling and Storage ===============
Handling and Storage Precautions: NONE SPECIFIED BY MANUFACTURER. Other Precautions: NONE SPECIFIED BY MANUFACTURER.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF SPILLED, WAER RADIONUCLIDE CARTRIDGE RESPIRATOR. Ventilation:PLACE AFFECTED COMPONENT IN LOCAL EXHAUST. Protective Gloves:DISPOSABLE GLOVES. Eye Protection:GOGGLES. Work Hygienic Practices:WASH HANDS. Supplemental Safety and Health RADIOACTIVE MATERIAL, EXCEPTED PACKAGES, ARTICLES.
======== Physical/Chemical Properties =========
HCC:A2 NRC/State Lic Num:20-02237-04 Boiling Pt:B.P. Text:-414F,-248C Melt/Freeze Pt:M.P/F.P Text:-425F,-254C Vapor Pres:18.317 Spec Gravity:6.0 Solubility in Water:100% Appearance and Odor:GAS, NO ODOR.
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES OXIDIZERS. Stability Condition to Avoid:TEMPERATURES IN EXCES

S OF 400C WILL CAUSE
DECOMPOSITION OF TIT2 WITH RELEASE OF TRITIUM GAS.
Hazardous Decomposition Products:UNBOUND TRITIUM.

====== Disposal Considerations ==========

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner what soever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.