

MINNESOTA MINING AND MFG CO -- SCOTCH-SEAL 800 INDUSTRIAL SEALANT -- 8030-00-080-2171

=====  
Product Identification  
=====

Product ID:SCOTCH-SEAL 800 INDUSTRIAL SEALANT

MSDS Date:04/12/1990

FSC:8030

NIIN:00-080-2171

MSDS Number: BVPXR

=== Responsible Party ===

Company Name:MINNESOTA MINING AND MFG CO

Address:3M CTR

City:SAINT PAUL (FORMALLY IN DETROITT, MI)

State:MN

ZIP:55144-1000

Country:US

Info

Phone Num:612-733-1341/612-733-1110

Emergency Phone Num:612-733-1341

CAGE:76381

=== Contractor Identification ===

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

=====  
Composition/Information on Ingredients  
=====

Ingred Name:2-BUTANONE; (METHYL ETHYL KETONE) (MEK). BP:175F,79C.

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 40-50%

OSHA PEL:200

PPM;300 STEL

ACGIH TLV:200 PPM;300 STEL

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ACRYLONITRILE-BUTADIENE POLYMER

CAS:9003-18-3

Fraction by Wt: 10-20%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:GLYCEROL ESTERS OF ROSIN ACIDS

CAS:8050-31-5

Fraction by Wt: 10-20%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:CARBONIC ACID, CALCIUM SALT (1:1); (CALCIUM CARBONATE)

CAS:471-34-1

RTECS #:FF9335000

Fraction by Wt: 1-10%

YL-; (METHYL ISOBUTYL KETONE)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 1-10%

OSHA PEL:100 PPM;75 STEL

ACGIH TLV:50 PPM;75 STEL

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHANOL, 2-BUTOXY-, PHOSPHATE(3:1);  
(TRI(BUTOXYETHYL)PHOSPHATE)

CAS:78-51-3

RTECS #:KJ9800000

Fraction by Wt: 1-10%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:CALCIUM ALUMINUM SILICATE

CAS:1327-39-5

Fraction by Wt: 1-10%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:TITANIUM OXIDE; (TITANIUM DIOXIDE)

CAS:13463-6

7-7

RTECS #:XR2275000

Fraction by Wt: 1-10%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST

Ingred Name:IRON (III) OXIDE; (IRON OXIDE)

CAS:1309-37-1

RTECS #:NO7400000

Fraction by Wt: 1-10%

OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5 MG/M3 (FE)

Ingred Name:ZINC OXIDE

CAS:1314-13-2

RTECS #:ZH4810000

Fraction by Wt: 1-10%

OSHA PEL:15MG/M3 TDUST;5 FUME

ACGIH TLV:10MG/M3 TDUST

Ingred Name:SALICYLIC ACID

CAS:69-72-7

RTECS #:VO0525000

Fraction by Wt: 1-10%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:VOLATILE

ORGANIC COMPOUNDS

RTECS #:9999999VO

Fraction by Wt: 604% G/L

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:CONT W/LIQ IS IRRIT. OVEREXP TO VAPS MAY ALSO CAUSE IRRIT. SYMPS OF OVEREXP INCL REDNESS, SMARTING, TEARING & SWELL. SKIN:PRLNG/RPTD CONT WILL DEFAT SKIN & CAUSE IRRIT

& POSS DERM. SYMPS ARE DRYNE SS, INCL CRACKING. INHAL:VAP OVEREXP MAY CAUSE RESP SYS IRRIT & TEMPORARY NERV SYS IMPAIRMENT(LT HEAD).(EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ:RPTD OVEREXP TO METHYL ISOBUTYL KETONE MAY CAUSE LIVER & KIDNEY DMG. SYMPS OF OVEREXP INCL DIZZ, HDCH, NAUS & FATG. EXTREME OVEREXP, SUCH AS WOULD OCCUR W/INTENTIONAL INHAL OF CONCENTRATED VA PS, COULD RSLT IN MORE SERIOUS INJURY, INCL ASPH

Y. INGEST:MAY CAUSE DIGEST SYS IRRIT.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:IMMEDIATELY FLUSH W/LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CALL MD. SKIN:WASH AFFECTED AREA W/SOAP & WATER. INHAL:REMOVE PERSON TO UNCONTAMINATED AIR. CALL MD. INGEST:DO NOT INDUCE VOMITING; IMMEDIATELY CALL MD OR POISON CONTROL CENTER.

===== Fire Fighting Measures ==

Flash Point:20.0F,-6.7C

Lower Limits:1.4%

Upper Limits:11.5%

Extinguishing Media:CO\*2, FOAM, DRY CHEMICALS, WATER.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE. OVERHEATED, CLOSED CONTAINERS ADJACENT TO FIRE COULD EXPLODE DUE TO INTERNAL PRESSURE BUILDUP.

===== Accidental Release Measures =====

Spill Release Procedures:EXTING ALL IGNIT SOURCES. V

ENTILATE AREA.

OBSERVE PRECS FROM OTHER SECTIONS. CONTAIN SPILL. COVER W/ABSORB MATLS AS NEEDED. COLLECT SPILLED MATL USING NON-SPARKING TOOLS.

PLACE IN U.S. DOT APPRVD META L CNTNR & SEAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:FOR INDUSTRIAL/PROFESSIONAL USE ONLY.  
KEEP AWAY FROM HEAT, SPARKS, FLAME & OTHER SOURCES OF IGNIT. VAPS  
RELEASED BY THIS PROD CAN BE IGN  
ITED EASILY.

Other Precautions:GROUND CONTAINERS WHEN TRANSFERRING CONTENTS. AVOID  
PROLONGED BREATHING OF VAPORS. AVOID EYE & SKIN CONTACT. KEEP  
CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF  
CHILDREN.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR  
EXPOSURE OF CONCERN .

Ventilation:USE ONLY IN AREAS W/SUFFICIENT VENTILATION TO MAINTAIN  
VAPOR CONCENTRATIONS BELOW RECOMMENDE  
D EXPOSURE LIMITS.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

THIS IS A REFORMATION:PART NUMBER INDICATOR "B" DENOTES NEWER PRODUCT  
THAN "A", 8030-00-080-2171. INGREDIENTS & OTHER CHANGES MAY APPLY .

=====  
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:SEE ING

1

Vapor Pres:80 @ 68F

Vapor Density:2.5

Spec Gravity:1.04

Evaporation Rate & Reference:2.7

Solubility in Water:SLIGHT

Appearance and Odor:REDDISH-BROWN, HEAVY SYRUP; KETONE ODOR.

Percent Volatiles by Volume:48

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CO, CO\*2 & SMOKE PARTICLES WHEN  
SUBJECTED TO EXCESSIVE HEAT OR FLAME.

===

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE ABSORBED & BULK PRODUCT AFTER MIXING W/FLAMMABLE MATL IN LICENSED HAZ WASTE FACILITY. DISPOSAL SHOULD BE I/A/W APPLICABLE LOCAL, STATE & FEDERAL REGULATIONS. U.S. HAZ WASTE NO:D001 (IGNITABLE).

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.