View NSN Online: https://aerobasegroup.kr/nsn/8010-01-330-0614

Product ID:CAT,MIL-C-85285B,24052,TYPE II;04GN003CAT MSDS Date:07/13/1992 FSC:8010 NIIN:01-330-0614 Kit Part:Y MSDS Number: BVQFW === Responsible Party === Company Name: DEFT INC CHEMICAL COATING DIV Address:17451 VON KARMAN AVE City:IRVINE State:CA ZIP:92714-6205 Countr v:US Info Phone Num:714-474-0400 Emergency Phone Num:714-474-0400 800-424-9300(CHEMTREC) Preparer's Name:NORM GAUL CAGE:33461 === Contractor Identification === Company Name: DEFT, INC. Address:17451 VON KARMAN AVE City:IRVINE State:CA ZIP:92614 Country:US Phone:949-474-0400 CAGE:33461

Ingred Name:HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE (HDI) CAS:28182-81-2 RTECS #:NQ9170000 Fraction by Wt: 90% Other REC Limits:NONE RECOMMEN

## DED

Ingred Name:1,6-DIISOCYANATOHEXANE (HEXAMETHYLENE DIISOCYANATE) CAS:822-06-0 RTECS #:MO1740000 Fraction by Wt: 0.5-1.6% Other REC Limits:NONE RECOMMENDED ACGIH TLV:0.005 PPM; 9394 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name:NAPHTHA, LIGHT AROMATIC (SOLVENT NAPHTHA) CAS:64742-95-6 RTECS #:WF3400000 Fraction by Wt: 5% Other REC Limits:NONE RECOMMENDED Ingred Name:N-BUTYL ACETATE (SARA III) CAS:123-86-4 RTECS #:AF7350000 Fraction by Wt: 5% Other REC Limits:NONE RECOMMENDED OSHA PEL:150 P ΡM ACGIH TLV:150 PPM/200STEL;9394 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS LD50 LC50 Mixture: ORAL LD50 (RAT) IS 738MG/KG FOR HDI Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYES/SKIN: ISOCYANATES REACT WITH SKIN PROTEINS AND MOISTURE TO CAUSE IRRITATION.SKIN ABSORPTION MAY CAUSE DEFATTING.INHAL:MAY CAUSE RESPIRATORY IRRIT ATION AND NERVIOUS SYSTEM DEPRESSION.INGEST:CORROSI VE TO MUCOSAL TISSUE.MAY CAUSE LUNG DAMAGE IF VOMITED AFTER INGESTING.CHRONIC: ISOCYANATE SENSITIZATION. Explanation of Carcinogenicity: THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP, IARC OR OSHA. Effects of Overexposure: INHAL: DIFFICULT BREATHING, HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, LEADING TO UNCONSCIOUSNESS OR COMA.SKIN/EYES:SWEELING REDNESS, RASH, DRYNESS, CRACKING, CHRONIC OVERE

XPOSURE WILL RESULT IN REACTION TO PROGRESSIVELY SMALLER DOSES OF ISOCYANTES. Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING RESPIRATORY,SKIN AILMENTS OR ISOCYANATE SENSITIZATION MAY BE AT INCREASED RISK FROM EXPOSURE.

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND WATER.EYES:FLUSH WITH LUKEWARM WATER FOR 15 MINUTES.INHAL:NOTE-ASTHMATIC RESPONSE MAY BE DELAYED.REMOVE TO

FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESP IRATION IF NEEDED.INGEST:DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.

Spill Release Procedures:ELIMINATE SOURCES OF IGNITION.USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT.SHUT OFF LEAK IF SAFE.DIKE.SOAK UP WITH A NON-COMBUSTIBLE INERT ABSORBANT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSA L.USE NON-SPARKING TOOLS. Neutralizing Agent:NONE

====

Handling and Storage Precautions: STORE IN A COOL, DRY, WELL-VENTILATED PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.AVOID HEAT, SOURCES OF IGNITION, MOISTURE AND INCOMPATIBLE MATERIALS. Other Precautions: EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUE; DISPOSE OF PROPERLY. AVOID SKIN AND EYE CONTACT. DO NOT BREATHE VAPORS. Respiratory Protection:WHERE ENVI RONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE EITHER A SELF-CONTAINED BREATHING APPARATUS OR A NOISH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPOR PARTICULATES(TC23C), DEPENDING ON THE AIRBORN CONCENTRATION. Ventilation:LOCAL VENTILATION AT THE WORKSITE;MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TLV/PEL.USE NON-SPARKING EQUIPMENT. Protective Gloves:COTTON, NEOPRENE, RUBBER, POLYETHYLENE Eye Protection: CHEMICAL SPLASH GOGGLES. Other Protective Equipment: PROTECTIVE CLOTHING, A S NEEDED.PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER. Work Hygienic Practices: WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA. Supplemental Safety and Health KEY1;F4.CONCENTRATION OF FREE HDI MONOMER INCREASES AFTER 3-6 MONTHS OF STORAGE-USE CAUTION FOR PRESSURE BUILDUP IN CONTAINERS REMOVED FROM STORAGE. HCC:F3 Boiling Pt:B.P. Te xt:260F-335F Vapor Density:>1 Spec Gravity:1.128 Evaporation Rate & amp; Reference: 0.44 (N-BUTYL ACETATE=1) Appearance and Odor:LIQUID;AMBER;SOLVENT ODOR Percent Volatiles by Volume:12.9 Stability Indicator/Materials to Avoid:YES WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS, SURFACE ACTIVE MATERIALS. Stability Condition to Avoid:MOISTURE,HIGH HEAT. Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE, OXIDES

## OF NITROGEN, TRACES OF HCN AND HEXAMETHYLENEDIISOCYANATE.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.EPA CODES:D001,F003,F005;WASTE CHARACTERISTICS:IGNITABILITY,REACTIVITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner w hatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.