

CIA. PETROLERA CARIBE, INC. -- DIESEL FUEL -- 9140-00-286-5295

===== Product Identification =====

Product ID:DIESEL FUEL

MSDS Date:10/01/1985

FSC:9140

NIIN:00-286-5295

MSDS Number: BVTWS

=== Responsible Party ===

Company Name:CIA. PETROLERA CARIBE, INC.

Box:1650

City:SAN SEBASTIAN

State:PR

ZIP:00685

Country:US

Info Phone Num:809-896-2575

Emergency Phone Num:809-896-1610

CAGE:5W150

=== Contractor

Identification ===

Company Name:CIA. PETROLERA CARIBE, INC.

Box:City:SAN SEBASTIAN

State:PR

ZIP:00685

Country:US

Phone:809-896-2575

CAGE:5W150

===== Composition/Information on Ingredients =====

Ingred Name:DIESEL FUEL [PETROLEUM MID-DISTILLATE]

CAS:68476-34-6

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO

IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHALATION MAY CAUSE RESPIRATORY IRRITATION. CONTACT MAY CAUSE SLIGHT EYE IRRITATION & MODERATE TO SEVERE SKIN IRRITATION. INGESTION MAY CAUSE IRRITATION TO INESTINES. MAY BE ASPIRATED INTO LUN GS. REPEATED EXPOSURE MAY CAUSE SEVERE SKIN IRRITATION REACTIONS. CHRONIC: NO KNOWN APPLICABLE INFORMATION.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:INHALATION: HEADACHE, NAUSEA, DIZZINESS, DROWSINESS, UNCONSCIOUSNESS. EYES: BURNING SENSATION, REDNESS. SKIN: BURNS, RASH, BLISTERS. INGESTION: BURNING OF MOUTH AND ESOPHAGUS. NAUSEA, VOMITING, STOMAC H PAIN, HEADACHE, UNCONSCIOUSNESS.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE AGGAVATED BY EXPOSURE.

===== First Aid Measures =====

First Aid:INHALATION-REMOVE TO FRESH AIR.SEEK MEDICAL ATTENTION IF SYMPTOMS DEVELOP.EYES-FLUSH WITH PLENTY OF WATER FOR 15 MINUTES.SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.SKIN-WASH WITH SOAP & WATER.SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.INGESTION-DO NOT INDUCE VOMITING!SEEK IMMEDIATE MEDICAL ATTENTION.A PHYSICIAN,AT HIS DISCRETION,MAY PERFORM GASTRIC LAVAGE WITH A CUFFED ENDOTRACHEAL TUBE.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:1
40F,60C

Extinguishing Media:DRY CHEMICAL, FOAM, OR CARBON DIOXIDE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. USE WATER FOG TO COOL FIRE EXPOSED CONTAINERS AND TO DISPERSE VAPORS.

Unusual Fire/Explosion Hazard:CARBON OXIDES AND VARIOUS HYDROCARBONS FORMED WHEN BURNED.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL UNECESSARY PERSONNEL. WEAR PROPER PROTECTIVE CLOTHING IF CO

CONDITIONS WARRANT. SHUT OFF SOURCE IF NO RISK. KEE OUT OF WATER SOURCES & SEWERS. ABSORB IN DRY, INERT MATERIAL (SAND, CLAY, SAWD UST, ETC.). TRANSFER TO DISPOSAL DRUMS. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL-VENTILATED PLACE AWAY FROM SOURCES OF IGNITION AND STRONG OXIDIZING AGENTS. KEEP CONTAINERS CLOSED.

Other Precautions:BOND & GROUND DURING LIQUID TRANSFER. PROVIDE MEANS OF CONTROLLING LEAKS AND SPILLS. USE NON-SPARKING TOOLS DURING LIQUID TRANSFER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION

Protective Gloves:NITRILE, PVA, NEOPRENE.

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:USE PROTECTIVE GARMENTS TO PREVENT EXCESSIVE SKIN CONTACT.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:>350F,>177C

Vapor Pres:1 MM HG

Spec Gravity:0.80

Evaporation Rate

Reference: