

DAVLIN PAINT CO -- B60011105D 600 INDUSTRIAL ENAMEL #11105 -- 8010-00-889-7345

=====  
Product Identification  
=====

Product ID:B60011105D 600 INDUSTRIAL ENAMEL #11105

MSDS Date:03/20/1992

FSC:8010

NIIN:00-889-7345

MSDS Number: BVVVG

=== Responsible Party ===

Company Name:DAVLIN PAINT CO

Address:1401 E 14TH

City:OAKLAND

State:CA

ZIP:94606-4401

Country:US

Info Phone Num:510-848-2863

Emergency Phone N

um:800-424-9300 (CHEMTREC)

CAGE:91007

=== Contractor Identification ===

Company Name:DAVLIN PAINT CO

Address:1401 E 14TH

Box:City:OAKLAND

State:CA

ZIP:94606-4401

Country:US

CAGE:91007

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HYDROCARBON MIXTURE [NAPHTHA, HEAVY STRAIGHT RUN]

CAS:64741-41-9

Fraction by Wt: 30%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

=====  
Hazards Identification  
=====

Routes o

f Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:INHALATION/INGESTION MAY CAUSE CENTRAL NEVOUS SYSTEM (CNS) DEPRESSION.INHALATION MAY CAUSE RESPIRATORY IRRITATION. INGESTION MAY CAUSE GI TRACT IRRITATION.CONTACT MAY CAUSE EYE IRRITATION.ASPIRATION MAY CAUSE LUNG DAMAGE.CHRONIC:PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN IRRITATION OR DERMATITIS;CNS DAMAGE.

Explanation of Carcinogeni

city:NO INGREDIENT OF A CONCENTRATION OF 0.1%

OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:CNS DEPRESSION: HEADACHE, NAUSEA, VOMITING, DIZZINESS, DROWSINESS, FATIGUE, WEAKNESS, UNCONSCIOUSNESS. INHALED: COUGHING, WHEEZING, SHORTNESS OF BREATH. EYES: REDNESS, TEARING, BLURRED VISION. SKIN: D RYING, DEFATTING, RASH, REDNESS, ITCHING, DISCOMFORT. INGESTED: NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:RESPIRATORY TRACT IRRITATION, DERMATITIS, NAUSEA.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION OR OXYGEN IF NEEDED. CONSULT A DOCTOR. EYE: FLUSH WITH LOTS OF WATER FOR 15 MINUTES, HOLD LIDS OPEN. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING! IF CONSCIOUS, GIVE WATER OR MILK TO DRINK. GET MEDICAL ATTENTION IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:104F,40C

Lower Limits:1.0

Upper Limits:6.1

Extinguishing Media:WATER FOG, CARBON DIXOIDE, DRY CHEMICAL, ALCOHOL FOAM. WATER MAY BE INEFFECTIVE; USE TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR FULL PROTECTIVE CLOTHING INCLUDING POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosi

on Hazard:VAPORS FORM AN EXPLOSIVE MIXTURE WITH AIR WHICH MAY BE IGNITED BY MANY SOURCES.CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.ISOLATE FROM IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. ELIMINATE ALL SOURCES OF IGNITION. VENTILATE THE AREA. PROVIDE ADEQUATE PROTECTIVE EQUIPMENT. DIKE AROUND THE AREA. COVER SPILL WITH INERT ABSORBANT AND TRANSFER WITH NON-SPARKING TOOLS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 80F IN A CLOSED CONTAINER.STORE IN ORIGINAL CONTAINER.AVOID FLAME & HIGH TEMPERATURES.DO NOT STORE NEAR STRONG OXIDIZING AGENTS/ACIDS.

Other Precautions:DO NOT TAKE INTERNALLY, AVOID PROLONGED OR REPEATED INHALATION OF HEATED VAPORS OR MISTS. KEEP AWAY FROM HEAT. GROUND ALL CONNECTIONS, CONTAINERS, ETC. WHEN POURING OR TRANSFERRING. USE NON-SPARKING TOOLS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation:USE ADEQUATE EXPOSURE-PROOF MECHANICAL VENTILATION TO MAINTAIN EXPOSURE BELOW AIRBORNE EXPOSURE LIMITS.

Protective Gloves:NITRILE, PVA.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:WEAR IMPERMEABLE APRONS & PROTECTIVE CLOTHING WHENEVER POSSIBLE TO PREVENT REPEATED OR PROLONGED CONTACT.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, USING THE TOILET OR SMOKING.LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

MSDS ENTERED BY DLA-HMIS UNDER PROJECT FOR GSA.

===== Physical/Chemical Properties =====

rties =====

HCC:F4

Boiling Pt:B.P. Text:315F,157C

Vapor Density:>1

Spec Gravity:1.1

Evaporation Rate & Reference: