

DOW CHEMICAL U.S.A. -- 29280 ETHAFOAM 220 PLANK BRAND POLYETHYLENE PLASTIC FOAM --
9330-01-186-0354

===== Product Identification =====

Product ID:29280 ETHAFOAM 220 PLANK BRAND POLYETHYLENE PLASTIC FOAM

MSDS Date:06/26/1992

FSC:9330

NIIN:01-186-0354

MSDS Number: BVXCW

=== Responsible Party ===

Company Name:DOW CHEMICAL U.S.A.

Address:CHEMICAL AND METALS DEPARTMENT

City:MIDLAND

State:MI

ZIP:48674

C

Country:US

Info Phone Num:517-636-4400

Emergency Phone Num:517-636-4400

CAGE:96717

=== Contractor Identification ===

Company Name:DOW CHEMICAL CO

Address:100 LARKIN CENTER

Box:City:MIDLAND

State:MI

ZIP:48674

Country:US

Phone:800-258-2436

CAGE:96717

===== Composition/Information on Ingredients =====

Ingred Name:POLYETHYLENE FOAM

CAS:9002-88-4

RTECS #:TQ3325000

Fraction by Wt: 75-100%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHANE, 1-CHLORO-1,1-DIFLUORO (HCFC-142B)

(C

HLORODIFLUOROETHANE)(BLOWING AGENTS ARE FUGITIVE & LEAVE PROD AFT
MANUFACTU)

CAS:75-68-3

RTECS #:KH7650000

Fraction by Wt: 0-18%

Other REC Limits:NONE RECOMMENDED

Ozone Depleting Chemical:2

Ingred Name:STEARYL STEARAMIDE

CAS:13276-08-9

Fraction by Wt: 0-2%

Other REC Limits:NONE RECOMMENDED

Ingred Name:COLOR CONCENTRATE IN POLYETHYLENE

Fraction by Wt: 0-2%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES

Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE:SOLID/DUST MAY CAUSE IRRIT OR
CORNEAL INJURY DUE TO MECHANICAL ACTION.VAP FROM THERM
OPERATIONS(HOT-WIRE CUTTING)MAY CAUSE EYE/RESP
IRRIT.SKIN:MECHANICAL INJURY ONLY, ESSENTIALLY NONIRRIT.INGEST:U
NLIKELY DUE TO PHY STATE.PHYSICAL INJURY ONLY.INHAL:RESP TRACT
IRRIT.

Explanation of Carcinogenicity:PER MSDS:CHLORODIFLUORETHANE DID NOT
CAUSE CANCER IN LONG-TERM A

NIMAL

STUDIES.NEG-MUTAGENICITY.TERATOLOGY-UNLIKELY.

Effects of Overexposure:INHAL:ANESTHETIC OR NARCOTIC EFFECTS. INCREASES
SENSITIVITY TO EPINEPHRINE & INCREASE MYOCARDIAL IRRIT(IRREG
HEARTBEATS).

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MFG.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/PLENTY OF WATER. MECHANICAL EFFECTS ONLY.

SKIN:WASH OFF IN FLOWING WATER OR SHOWER. INGEST:NO ADVERSE EFFECTS
ANTICIPATED BY THIS

ROUTE OF EXPOSURE. INHAL:NO ADVERSE EFFECTS
ANTICIPATED BY THIS ROUTE OF EXPOSURE INCIDENTAL TO PROPER
INDUSTRIAL HANDLING.

===== Fire Fighting Measures =====

Extinguishing Media:WATER FOG.
Fire Fighting Procedures:WEAR SELF-CONTAINED, POSTITIVE PRESSURE
BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:AVOID DENSE SMOKE.

===== Accidental Release Measures =====

Spill Release Procedures:PICK UP AND HANDLE AS ANY OTHER
INERT
MATERIAL.
Neutralizing Agent:NONE SPECIFIEID BY MFG.

===== Handling and Storage =====

Handling and Storage Precautions:PRAC REASONABLE CARE & CLEANLINESS AS
COMMON SENSE SAF PRECAUTION WHEN HANDLING MATL.POLYETHYLENE FOAM
COMBUST-DO NOT EXPO TO FLAME/IGN SOURCES.
Other Precautions:WHEN LG AMTS ARE STORED/FABRICATED SM QUANT OF
BLOSING AGENT RELEASED FROM FOAM MAY TEND TO ACCELERATE CORR OF
HEATERS/BOILERS.CORR CAN CREATE HOLES IN CO
MBUST CHAMBER LEADING TO
RELEASE OF COMBUST GA SES/CO.INSPECT HEATING EQIPMT REGUALARY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ATMOSPHERIC LEVELS SHOULD BE MAINTAINED BELOW
EPOS GUIDELINE.WHEN RESP PROTECTIVE IS REQUIRED FOR CERTAIN
OPERATIONS USE APPROVED AIR-PURIFYING RESP.IN DUSTY ATMOSPHERE USE
AN APPROVED DUST RESP.FULLF ACE RESP IF VAP EXPO CAUSES EYE
DISCOMFO
Ventilation:PROVIDE GENERAL &/OR LOCAL EXHAUST VENTILATIO
N TO CONTROL
AIRBORNE LEVELS BELOW THE EXPOSURE GUIDELINES.
Protective Gloves:CLEAN BODY-COVERING CLOTHING.
Eye Protection:SAFETY GLASSES, CHEM GOGGLES
Other Protective Equipment:SKIN PROT:NO PRECAUTIONS OTHER HTAN CLEAN
BODY-COVERING CLOTHING SHOULD BE NEEDED.
Work Hygienic Practices:WASH HANDS AFT HANDLING.
Supplemental Safety and Health
STORAGE OF LG AMTS OF FOAM IN UNVENTILATED SPACES SHOULD BE AVOIDED TO
PREVENT BUILDUP OF COMBUST VAP.USE OF FOAM IN APPLICATIONS
INVOLVING EX

PO TO CHILDREN SHOULD BE REVIEWED W/DOW'S PROD
STEWARDSHIP. CHOICE OF KING & OR SWALLOWING OF FOAM BY SMALL CHILDREN MAY
OCCUR.

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:0.02-0.16

Solubility in Water:INSOLUBLE

Appearance and Odor:CELLULAR SOLID PLASTIC FOAM, NO ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID FIRE & TEMPER

ATURES OVER 625F, 329C.

Hazardous Decomposition Products:CO GENERATED UNDER NORMAL COMBUSTION
CONDITIONS.ADDITIONAL TOXIC SUB MAY BE RELEASED UNDER LESS THAN
FULL COMBUST CONDIT

===== Disposal Considerations =====

Waste Disposal Methods:REUSE,RECYCLE, OR BURY IN AN APPROVED LANDFILL.
FOLLOW ALL LOCAL, STATE, AND FEDERAL REQUIREMENTS OF DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated f

or use by elements of the Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.