

HULS AMERICA INC -- MIL-H-6083E -- 9150-00-935-9810

=====
Product Identification
=====

Product ID:MIL-H-6083E
MSDS Date:01/16/1989
FSC:9150
NIIN:00-935-9810
MSDS Number: BVZHV
=== Responsible Party ===
Company Name:HULS AMERICA INC
Address:80 CENTENNIAL AVE
Box:456
City:PISCATAWAY
State:NJ
ZIP:08855-0456
Country:US
Info Phone Num:201-980-6800
Emergency Phone Num:201-980-6800
Preparer's Name:P.A.
PARKER
CAGE:63182
=== Contractor Identification ===
Company Name:HULS AMERICA INC
Address:TURNER PLACE
Box:365
City:PISCATAWAY
State:NJ
ZIP:08855
Country:US
Phone:201-763-7173
CAGE:63182

=====
Composition/Information on Ingredients
=====

Ingred Name:THE MANUFACTURER STATES THAT NO HAZARDOUS INGREDIENTS ARE
PRESENT IN THIS PRODUCT.
Fraction by Wt: 100%
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: In

halation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:LOW ORAL AND DERMAL TOXICITY. MISTS OR FUMES FROM EXCESSIVE HEATING AMY CAUSE EYE AND SKIN IRRITATION. MAY ALSO CAUSE RESPIRATORY TRACT IRRITATION.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:MIST OR FUMES FROM EXCESSIVE HEATING MAY CAUSE NAUSEA AND/OR VOMITING.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:CONTACT- WASH SKIN WITH SOAP AND EATER; FLUSH EYES WITH WATER FOR 25 MIN. CALL A PHYSICIAN IF IRRITATION DEVELOPS. INHALATION- REMOVE VICTIM TO FRESH AIR AND GIVE ARTIFICIAL RESPIRATION OR OXYGEN IF N EEEDED. INGESTION- DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:COC

Flash Point:200F,93C

Lower Limits:1

Upper Limits:6

Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM OR CARBON DIOXIDE.

Fire Fighting Procedures:BURNING WILL PRODUCE TOXIC FUMES. WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL TURN-OUT GEAR TO FIGHT FIRE. AVOID SPREADING LIQUIE AND FIRE WITH WATER.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS. COOL WITH WATER SPRAY.

=====
===== Accidental Release Measures =====

Spill Release Procedures:COVER WITH AN INERT ABSORBENT MATERIAL AND REMOVE TO DISPOSAL CONTAINER.

Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE OIL ABOVE THE MAXIMUM RECOMMENDED OPERATING TEMPERATURE OF 200F. MAY SOFTEN SOME PLASTIC AND PAINT SURFACES.

Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protect

ion:IF OVERHEATED, USE APPROPRIATE NIOSH-APPROVED
RESPIRATORY PROTECTIVE EQUIPMENT.

Ventilation:LOCAL EXHAUST AND MECHANICAL VENTILATION RECOMMENDED.

Protective Gloves:IMPERMEABLE GLOVES

Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment:EYEWASH FOUNTAIN, SAFETY SHOWER. WASH
CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

MSDS PRESENTED BY CAGE 63182 FOR CONTRACT NUMBER SP0451-95-C004

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:420F,216C

Vapor Pres:0.07 MM HG

Vapor Density:>1

Spec Gravity: