

CON-LUX COATINGS INC -- TT-P-19D,BLACK,37038,PAINT,LATEX,FS-730(ACRYLIC EMULSION) --
8010-00-823-7964

===== Product Identification =====

Product ID:TT-P-19D,BLACK,37038,PAINT,LATEX,FS-730(ACRYLIC EMULSION)

MSDS Date:03/02/1989

FSC:8010

NIIN:00-823-7964

MSDS Number: BWDYM

=== Responsible Party ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

City:EDISON

State:NJ

ZIP:08818-0847

Country

:US

Info Phone Num:908-287-4000

Emergency Phone Num:908-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

===== Composition/Information on Ingredients =====

Ingred Name:MAGNESIUM SILICATE

CAS:1480-96-6

Fraction by Wt: >1%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes

of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, RESPIRATORY TRACT. ACUTE- OVEREXPOSURE MAY CAUSE EYES AND SKIN IRRITATION. CONTINUED BREATHING OF VAPORS MAY CAUSE RESPIRATORY TRACT IRRITATION, HEADACHE, DIZZINESS & NAUSEA. CHRONIC- UNKNOWN.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:EYES, SKIN, RESPIRATORY TRACT IRRITATION; HEADACHE, DIZZINESS, NAUSEA

M
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

=====
First Aid Measures
=====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. IF CONSCIOUS, DRINK 1-2 GLASSES OF WATER. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW KNEE TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point:NONE
Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROUNDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.
Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NONE KNOWN

=====
Accidental Release Measures
=====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. VENTILATE AREA. CONTAIN SPILL. PICK UP SPILL WITH INERT ABSORBENT SUCH AS SAND. PREVENT LIQUID FROM ENTERING SEWERS.
Neutralizing Agent:NOT RELEVANT

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL PLACE, AWAY FROM INCOMPATIBLE MATERIALS

. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:USE WITH ADEQUATE VENTILATION. DO NOT BREATHE VAPORS.
AVOID EYES AND SKIN CONTACT. KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED.
WEAR NIOSH-APPROVED RESPIRATOR IF TLV EXCEEDED. IN CONFINED AREAS,
WEAR A NIOSH APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation:ADEQUATE

Protective Gloves:RUBBER, NEOPRENE FOR
REPEATED CONTACT

Eye Protection:SAFETY GOGGLES/FACE SHIELD IF SPLASHING

Other Protective Equipment:PROTECTIVE CLOTHING, SAFETY SHOWER AND
EYEWASH FACILITY

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:T6

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:212F MIN

Vapor Density: