

HAARTZ-MASON, INC. -- N-450-11 SOLVENT BLEND -- 6850-00-182-6467

===== Product Identification =====

Product ID:N-450-11 SOLVENT BLEND

MSDS Date:10/22/1993

FSC:6850

NIIN:00-182-6467

MSDS Number: BWGXN

=== Responsible Party ===

Company Name:HAARTZ-MASON, INC.

Address:270 PLEASANT STREET

City:WATERTOWN

State:MA

ZIP:02172

Country:US

Info Phone Num:617-926-2300

Emergency Phone Num:617-926-2300/800-424-9300(CHEMTREC)

CAGE:84697

=== Contractor Identification ===

Company Name:HAARTZ-MASON, INC.

Address:270 PLEASANT STREET

Box:322

City:WATERTOWN

State:MA

ZIP:02172

Country:US

Phone:617-926-2300

CAGE:84697

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA 313) (CERCLA)

CAS:108-88-3

RTECS #:XS5250000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2

ACGIH TLV:S, 50 PPM; 9495

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KE

ZONE (HEXONE) (SARA 313) (CERCLA)

CAS:108-10-1

RTECS #:SA9275000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM/75 STEL; 9495

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:VOLITILE ORGANIC CONTENT AS LISTED ON MSDS: 6.7 LBS/GAL.

RTECS #:9999999VC

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS UNKNOWN.

Routes of Entry: Inhalation

Eye: YES Skin: YES Ingestion: NO

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: TARGET ORGANS: EYES, LUNGS, SPLEEN, LIVER, KIDNEY, HEART. ACUTE- MAY CAUSE EYE & SKIN IRRITATION. MAY BE ABSORBED THROUGH SKIN. INHALATION MAY CAUSE NARCOSIS & NAUSEA. MAY BE HARMFUL IF SWALLOWED. ASPIRATION HAZARD. CHRONIC- MAY CAUSE LIVER & CARDIAC ABNORMALITIES, KIDNEY, LUNG, SPLEEN & EYE DAMAGE.

Explanation of Carcinogenicity: NONE

Effects of Overexposure: EYES, SKIN,

RESPIRATORY TRACT IRRITATION,

HEADACHE, DIZZINESS, NAUSEA, VOMITING, DIARRHEA, WEAKNESS, CONFUSION, IMPAIRED COORDINATION, DRYING SKIN, COUGHING, DIFFICULTY IN BREATHING AND DROWSINESS

Medical Conditions Aggravated by Exposure: PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED LIVER, KIDNEY, RESPIRATORY FUNCTIONS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

===== First Aid Measures =====

First Aid: GET MEDICAL ATTENTION

IF SYMPTOMS PERSIST. SKIN: WASH WITH

SOAP & WATER. EYE: FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. INHALED: REMOVE TO FRESH AIR & PROVIDE OXYGEN/CPR IF NEEDED.

ORAL: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method: SCC

Flash Point: 28.0F, -2.2C

Lower Limits: 0.9

Upper Limits: 8.9

Extinguishing Media: USE CARBON DIOXIDE, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE

IRE EXPOSED CONTAINERS COOL & DISPERSE VAPORS.

Fire Fighting Procedures:WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE, OPERATED IN POSITIVE PRESSURE MODE. WATER MAY BE INEFFECTIVE.

Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR, CAN TRAVEL A LONG DISTANCE TO A SOURCE OF IGNITION AND FLASHBACK. CONTAINERS MAY EXPLODE DUE TO HEAT OF FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND/NON-SPARKING PUMP. PLACE IN CONTAINER FOR DISPOSAL. PREVENT LIQUID FROM ENTERING SEWERS, WATERWAYS OR LOW AREAS.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, VENTILATED AREA, AWAY FROM HEAT, FLAMES & INCOMPATIBLES. OUTSIDE STORAGE PREFERRED. FOR INSIDE USE

USE STANDARD FLAMMABLE LIQUID STOREROOM.

Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS. DO NOT WELD, SOLDER OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS. THEY MAY EXPLODE AND CAUSE INJURY/DEATH. GROUND & BOUND SHIPPING CONTAINER . AVOID REPEATED/PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF WORKING IN A CONFINED AREA OR FIGHTING FIRE, USE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED AIR RESPIRATOR WITH FULL FACEPIECE, OPERATED IN POSITIVE PRESSURE MODE.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:PVA, NITRILE

Eye Protection:SPLASH-PROOF GOGGLES

Other Protective Equipment:IMPERVIOUS CLOTHING, COVERALLS OR LAB COAT, EMERGENCY SHOWER, EYE WASH STATION

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING VAPORS OR MISTS.

Suppl

===== Physical/Chemical Properties =====

HCC:F2

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:=93.3C, 200.F

Decomp Temp:Decomp Text:NOT KNOWN

Vapor Pres:20-30 @68F

Vapor Density:3.3

Spec Gravity:0.8

Solubility in Water:SLIGHT

Appearance and Odor:CLEAR LIQUID, CHARACTERISTIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to A

void:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES, HOT SURFACES,  
STATIC ELECTRICITY

Hazardous Decomposition Products:MAY FORM SMOKE, TOXIC LEVELS OF CARBON  
MONOXIDE, CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE  
AND FEDERAL REGULATIONS.

=====  
Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.