

VELSICOL CHEMICAL CORP -- MIL-H-46170B TYPE 2, PROD/MSDS#:0425599 -- 9150-01-119-8149

===== Product Identification =====

Product ID:MIL-H-46170B TYPE 2, PROD/MSDS#:0425599

MSDS Date:02/21/1991

FSC:9150

NIIN:01-119-8149

MSDS Number: BWPTK

=== Responsible Party ===

Company Name:VELSICOL CHEMICAL CORP

Address:10400 W. HIGGINS, SUITE 600

City:DES PLAINES

State:IL

ZIP:60018

Country:US

Info Phone Num:70

8-635-3471

Emergency Phone Num:708-298-9000

Preparer's Name:MANAGER, PRODUCT SAFETY

CAGE:VELSI

=== Contractor Identification ===

Company Name:HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08855

Country:US

Phone:201-763-7173

CAGE:63182

Company Name:VELSICOL CHEMICAL CORPORATION

Address:10400 W HIGGINS ROAD

Box:City:ROSEMONT

State:IL

ZIP:60018

Country:US

Phone:847-298-9000

CAGE:0Z6C4

Company Name:VELSICOL CHEMICAL CORPORATION

CAGE:VELSI

===== Composition/Info

Information on Ingredients =====

Ingredient Name:(PETROLEUM SULFONATE) BARIUM DINONYLNAPHTHALENE- SULFONATE
CAS:25619-56-1
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED

Ingredient Name:BARIUM COMPOUNDS
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE ESTABLISHED
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and
Chronic:LOW ORAL & DERMAL TOXICITY.
MISTS/FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE/SKIN IRRIT,
NAUSEA, VOMITING, RESPIRATORY TRACT IRRIT. BARIUM COMPOUNDS IS
MODERATE SKIN IRRITANT & IS CORROSIVE TO EYES.
Effects of Overexposure:EYE/SKIN/RESPIRATORY TRACT IRRIT. NAUSEA,
VOMITING.
Medical Condition Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:CONTACT:FLUSH EYES W/PLENTY OF WATER FOR 15MINS. WASH
SKIN
W/SOAP & WATER. CALL PHYSICIAN IF IRRIT PERSISTS. INHAL:REMOVE TO
FRESH AIR & GIVE CPR OR OXYGEN IF NEEDED. CALL PHYSICIAN. INGEST:DO
NOT INDUCE VOMITING. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:430F,221C
Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM, OR CARBON DIOXIDE.
Fire Fighting Procedures:BURNING WILL PRODUCE TOXIC FUMES. WEAR
SELF-CONTAINED BREATHING APPARATUS & FULL TURN-OUT GEAR

R TO FIGHT

FIRE. AVOID SPREADING LIQ & FIRE BY WATER FLOODING.

Unusual Fire/Explosion Hazard:EXPOUSRE TO HEAT BUILDS UP PRESSURE IN
CLOSED CONTAINERS. COOL WITH WATER SPRAY.

===== Accidental Release Measures =====

Spill Release Procedures:COVER W/AN INERT ABSORBENT MATERAIL & REMOVE
TO DISPOSAL CONTAINER. OBEY ALL RELEVANT LOCAL, STATE AND FEDERAL
LAWS. DO OT CONTAMINATED ANY LAKES, STREAMS, PONDS OR UNDERGROUND
WATER SUPPLY.

=====

=== Handling and Storage =====

Handling and Storage Precautions:CAUTION:DO NOT USE OIL ABOVE MAX
RECOMMENDED OPERATING TEMP OF 430F. MAY SOFTEN SOME PLASTIC & PAINT
SURFACES. WIPE UP SPILLS IMMED.

Other Precautions:AVOID EYE/SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF OVERHEATED USE APPROPRIATE NIOSH-APPROVED
RESPIRATORY PROTECTIVE EQUIPMENT.

Ventilation:LOCAL EXHAUST & MECHANICAL VENTILATION RECOMME
NDED.

Protective Gloves:IMPERMEABLE GLOVES

Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELDS

Other Protective Equipment:EYE WASH FOUNTAIN, SAFETY SHOWER. WASH
CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices:WASH HANDS AFTER HANDLING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.842

Solubility in Water:NEGLIGIBLE

Appearance and Odor:RED LIUQID.

Percent Volatiles by Volume:NOT VL

=====

Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG OXIDANTS.
Hazardous Decomposition Products: BURNING WILL PRODUCE TOXIC FUMES.

===== Disposal Considerations =====

Waste Disposal Methods: OBEY RELEVANT LOCAL, STATE AND FEDERAL LAWS. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS OR UNDERGROUND WATER SUPPLY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.