

FISKE BROS REFINING CO -- LUBRIPLATE FMO-350-AW -- 9150-01-237-7467

=====
Product Identification
=====

Product ID:LUBRIPLATE FMO-350-AW

MSDS Date:01/01/1994

FSC:9150

NIIN:01-237-7467

MSDS Number: BWPTZ

=== Responsible Party ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:419-691-2491

Emergency Phone Num:800-255-3924

Pre

parer's Name:JAMES R. KONTAK

CAGE:73219

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:TAYLOR PARKER CO.

CAGE:59349

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL, WHITE

CAS:8042-47-5

RTECS #:PY8047000

Fraction by Wt: MAJOR

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

=====

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5MG/M3

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:MAY CAUSE IRRITATION.HIGH PRESSURE INJECTION MAY RESULT IN NECROSIS.INGEST:THIS ITEM HAS A LOW ORDER OF ORAL TOXICITY.MAY CAUSE LUNG DAMAGE IF VOMITED AFTER INGESTING.IN HAL:MAY CAUSE RESPIRATORY IRRITATION.

Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%

WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.

Effects of Overexposure:EYE/SKIN:IRRITATION.A HIGH PRESSURE INJECTION MAY NOT APPEAR TO BE SERIOUS,BUT THIS IS A MEDICAL EMERGENCY.

Medical Cond Aggravated by Exposure:BECAUSE OF ITS DEFATTING PROPERTIES,PERSONS WITH PRE-EXISTING SKIN AILMENTS MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND

WATER.TREAT A HIGH PRESSURE INJECTION AS A MEDICAL EMERGENCY.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:335F-495F

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE,FOAM.

Fire

Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.

Unusual Fire/Explosion Hazard:FIRE CONDITIONS MAY EVOLVE TOXIC FUMES.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.AVOID RUNOFF INTO W

ATER WAYS.REPORT SPIL LS RESULTING
IN SHEEN UPON WATER TO 800-424-8802.

Neutralizing Agent:NOT APPLICABLE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED
PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY FROM
HEAT,SPARKS,FLAMES AND INCOMPATIBLE MATERIALS.

Other Precautions:EMPTY CONTAINERS MAY CONTAIN HAZARDOUS
RESIDUE;DISPOSE OF PROPERLY.

=====
===== Exposure Controls/Personal Pro
tection =====

Respiratory Protection:NOT NEEDED IN NORMAL SERVICE.

Ventilation:USE LOCAL EXHAUST TO CAPTURE FUMES AND VAPORS.

Protective Gloves:OIL RESISTANT.

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING,AS NEEDED.PROVIDE A
LOCAL EYE WASH STATION.

Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS
PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.

Supplemental Safety and Health

HMIS SPOKE TO TODD COLEMAN ON 20MAR95.HE INFORMED
US THAT THIS ITEM

CONTAINS PRIMARILY WHITE MINERAL OIL,CAS 8042-47-5.

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>55F,>13C

Vapor Pres:5

Spec Gravity:0.87-0.89

Evaporation Rate & Reference: