

EASTMAN KODAK COMPANY -- 140 8988 HC-110 DEVELOPER,CONCENTRATE -- 6750-00-837-7257
===== Product Identification =====

Product ID:140 8988 HC-110 DEVELOPER,CONCENTRATE

MSDS Date:12/17/1997

FSC:6750

NIIN:00-837-7257

MSDS Number: BWPZG

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194 MSDS :80

0- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Information on Ingredients =====

=====

Ingred Name:DIETHANOLAMINE-SULFUR DIOXIDE COMPLEX
CAS:63149-47-3
Fraction by Wt: 50 - 55%
Other REC Limits:NONE RECOMMENDED

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 10 - 20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

Ingred Name:HYDROQUINONE (SARA 302/313) (CERCLA)
CAS:123-31-9
RTECS #:MX3500000
Fraction by Wt: 9%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9495
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

I
Ingred Name:DIETHYLENE GLYCOL
CAS:111-46-6
RTECS #:ID5950000
Fraction by Wt: 8%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHANOLAMINE/2-AMINOETHANOL
CAS:141-43-5
RTECS #:KJ5775000
Fraction by Wt: 5 - 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:3 PPM
ACGIH TLV:3 PPM/6 STEL; 9495

Ingred Name:DIETHANOLAMINE (SARA 313) (CERCLA)
CAS:111-42-2
RTECS #:KL2975000
Fraction by Wt: 3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:3 PPM
ACGIH TLV:0.46 PPM; 9495
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred

Name:DIETHYLENETRIAMINEPENTAACITIC ACID/PENTETIC ACID

CAS:67-43-6

RTECS #:MB8205000

Fraction by Wt: 1 - 5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYLENE GLYCOL (SARA 313) (CERCLA)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 1%

Other REC Limits:NONE RECOMMENDED

ACGIH TLV:C 50 PPM,VAPOR; 9495

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====
===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >3200 MG/KG

Routes of Entry: Inhalation:YES Skin:YE

S Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: HARMFUL IF INHALED. MAY CAUSE IRRITATION TO THE MUCOUS MEMBRANES & UPPER RESPIRATORY TRACT. EYES: CUASES IRRITATION. SKIN: CAUSES IRRITATION. MAY CAUSE ALLERGIC SKIN REACTIONS. INGESTION: HARMFUL IF SWALLOWED. MAY CAUSE IRRITATION OF THE GASTROINTESTINAL TRACT.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:CONTAINS DIETHYLENE GLYCOL: CAN CAUSE KIDNEY DAMAGE. CAN CAUSE CNS EFFECTS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALATION-IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES-IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MIN. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN-IMMEDIATE LY

FLUSH WITH PLENTY OF WATER & WASH WITH A NON-ALKALINE SKIN CLEANER. GET MEDICAL ATTENTION. INGESTED-ONLY INDUCE VOMITING AT THE INSTRUCTION OF MEDICAL PERSONNEL. CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:WATER SPRAY, CARBON DIXOIDE, DRY CHEMICAL, ALCOHOL FOAM. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTH

ING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS
DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard:ELEVATED TEMPERATURES CAN CAUSE
DECOMPOSITION.

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER.
OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL,
THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE
THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION.

Neutralizing Agent
:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED. STORE IN A COOL
PLACE.
Other Precautions:AVOID PROLONGED OR REPEATED BREATHING OF MISTS OR
VAPOR. USE WITH ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE
CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS, AN APPRO
VED

RESPIRATOR MUST BE WORN. RESPIRATOR TYPE: ORGANIC VAPOR.

Ventilation:GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR)
SHOULD BE USED. VENTILATION RATES SHOULD MATCH CONDITIONS.

Protective Gloves:WEAR IMPERVIOUS GLOVES.

Eye Protection:WEAR SAFETY GLASSES WITH SIDE SHIELDS.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING APPROPRIATE FOR THE
RISK OF EXPOSURE. EYE BATH, SAFETY SHOWER, WASHING FACILITIES.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Sa

fety and Health

WARNING! HEAT SENSITIVE-CAN CAUSE DECOMPOSITION.

===== Physical/Chemical Properties =====

HCC:B3

Boiling Pt:B.P. Text:>212F,>100C

Decomp Temp:Decomp Text:293F,145C

Vapor Pres:11 @ 68F

Vapor Density:2.1

Spec Gravity:1.24

pH:9.0

Solubility in Water:COMPLETE

Appearance and Odor:BROWN LIQUID - AMINE ODOR

Percent Volatiles by Volume:65- 70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRO

NG OXIDIZING AGNETS.

Stability Condition to Avoid:STABLE; HOWEVER, MATERIAL CAN DECOMPOSE ABOVE 145C. AVOID TEMPERATURES ABOVE 45C.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN, OXIDES OF SYLFUR.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS. FLUSH TO SEWER WITH LARG

E AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.