

DEXTER CORP; AUTOMOTIVE MATERIALS DIVISION -- EPK 0151 RESIN AA0151 -- 8040-00-061-8303  
===== Product Identification =====

Product ID:EPK 0151 RESIN AA0151  
MSDS Date:11/02/1993  
FSC:8040  
NIIN:00-061-8303  
Kit Part:Y  
MSDS Number: BWQYV  
=== Responsible Party ===  
Company Name:DEXTER CORP; AUTOMOTIVE MATERIALS DIVISION  
Address:ONE DEXTER DRIVE  
City:SEABROOK  
State:NH  
ZIP:03874  
Country:US  
Info Phone Num:  
603-474-5541  
Emergency Phone Num:800-424-9300 (CHEMTREC)  
Preparer's Name:KEN DECOSTA  
CAGE:1JB33  
=== Contractor Identification ===  
Company Name:DEXTER CORP THE HYSOL DIV  
Address:1 DEXTER DR  
Box:City:SEABROOK  
State:NH  
ZIP:03874  
Country:US  
Phone:603-474-5541/FAX: 603-474-5545  
CAGE:1JB33

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY RESIN (THIS RESIN IS NOT REGULATED UNDER OSHA'S  
HAZARD COMMUNICATION STANDARD)  
CAS:25068-38-6  
Fraction by Wt: 60-100%  
Othe

r REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Health Hazards Acute and Chronic:EYE: MODERATELY IRRITATING. CONTACT WITH PRODUCT AT ELEVATED TEMPERATURES CAN RESULT IN THERMAL BURNS. SKIN: MODERATELY IRRITATING, CAUSE SKIN SENSITIZATION. THERMAL BURNS AT ELEVATED TEMPERATURES. INHALATION: NOT LIKELY BECAUSE OF LOW VOLATILITY. INGESTION: PRESUMED TO HAVE LOW ORDER OF ACUTE ORAL TOXICITY.

Effects of Overexposure:IRRITATION AND SKIN SENSITIZATION

(ALLERGY) MAY BE EVIDENCED BY RASHES, ESPECIALLY HIVES.

Medical Condition Aggravated by Exposure:PRE-EXISTING SKIN AND EYE DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. PRE-EXISTING SKIN OR LUNG ALLERGIES MAY INCREASE CHANCE OF DEVELOPING INCREASED ALLERGY SYMPTOMS FROM EXPOSURE.

=====  
===== First Aid Measures =====

First Aid:EYE:FLUSH W/H2O 15 MIN,HOLD EYELID OPEN.GET MED AID.IF CONTACT W/HOT PRODUCT,IMMEDIATE FLUSH

W/COOL H2O 15 MIN.GET MED

AID.SKIN:REMOVE CONTAM CLOTH/SHOES.WIPE EXCESS FROM SKIN.FLUSH

W/H2O.WASH W/SOAP & H2O .IF IRRITATED,GET MED AID.DESTROY CONTAM

LEATHER.IF CONTACT W/HOT PRODUCT,IMMEDIATE FLUSH W/COOL H2O 15

MIN.REMOVE CLOTH W/CARE,IF CONTACT W/HOT PRODUCT.IF STUCK,DON'T PULL

MATERIAL OFF,CUT AROUND BURN AREA. \*

=====  
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:155F,68C

Lower Limits:0.4

Upper Limits:1.3

Extinguishing Media:

CARBON DIOXIDE, DRY CHEMICAL FOR SMALL FIRES. FOAM FOR LARGE FIRES.

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

=====  
===== Accidental Release Measures =====

Spill Release Procedures:CLEANUP AND DISPOSAL SHOULD BE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:WARNING: MAY CAUSE SKIN SENSITIZATION AND OTHER

R ALLERGIC RESPONSES.

Other Precautions:USE ONLY WITH ADEQUATE VENTILATION, PARTICULARLY IF HEATED OR SPRAYED. AVOID CONTACT WITH SKIN OR EYES.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR SUPPLIED MASK IN CONFINED SPACE.

Ventilation:LOCAL EXHAUST PREFERRED, MECHANICAL EXHAUST ACCEPTABLE.

Protective Gloves:RUBBER OR PLASTIC GLOVES

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EYE BATH. USE COVERALLS O  
R

APRON TO PROTECT AGAINST SKIN AND CLOTHING CONTAMINATION.

Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

\* INHALATION: REMOVE TO FRESH AIR & GIVE OXYGEN IF BREATHING DIFFICULT.

GET MED AID. INGESTION: DON'T INDUCE VOMITING. IN GENERAL, NO

TREATMENT NECESSARY UNLESS LRG QTY INGESTED. HOWEVER, GET MED ADVI

CE. NOTE TO DR: IN GENERAL, EMESIS INDUCTION UNNECESSARY IN HIGH

VISCOSITY, LOW VOLAILITY PRODUCTS (NEAT EPOXY RESIN).

===

=====  
===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:284F,140C

Vapor Pres:2

Vapor Density:3.8

Spec Gravity:1.14

Evaporation Rate & Reference:>1

Solubility in Water: