View NSN Online: https://aerobasegroup.kr/nsn/6750-01-285-1770

EASTMAN KODAK COMPANY -- 809 0532, KODAK FLEXICOLOR STABILIZER & REPLENISHER LF -- 6750-01-285-1770

Product ID:809 0532, KODAK FLEXICOLOR STABILIZER & REPLENISHER LF MSDS Date:07/19/1995 FSC:6750 NIIN:01-285-1770 Kit Part:Y MSDS Number: BWRXZ === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Co untry:US Info Phone Num:716-722-5151 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

======= Composition/Informat

ion on Ingredients ==========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 70-75% Other REC Limits:NONE RECOMMENDED

Ingred Name:HEXAMINE (HEXAMETHYLENETETRAMINE) CAS:100-97-0 RTECS #:MN4725000 Fraction by Wt: 25-30% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM DODECYLBENZENE SULFONATE (CERCLA) CAS:25155-30-0 RTECS #:DB6825000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:DIPROPYLENE GLYCOL CAS:110 -98-5 RTECS #:UB8785000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:NON-IONIC SURFACTANT Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:1,2-BENZISOTHIAZOL-3(2H)-ONE CAS:2634-33-5 RTECS #:DE4620000 Fraction by Wt: 212F,>100C Vapor Pres:18 MMHG Vapor Density:0.6 AIR=1 Spec Gravity:1.06 pH:7.7 Solubility in Water:COMPLETE Appearance and Odor:LIQUID, AMBER, SLIGHT AMINE ODOR. Percent Volatiles by Volume:70-75

========== Stability and Reactivity D

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG ACIDS.
Stability Condition to Avoid:STABLE; HOWEVER, MATERIAL CAN DECOMPOSE ABOVE 295. AVOID TEMPERATURES ABOVE 195C.
Hazardous Decomposition Products:AMMONIA, FORMALDEHYDE. CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN, OXIDES OF SULFUR.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:DISC HARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek co mpetent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.