View NSN Online: https://aerobasegroup.kr/nsn/6850-01-167-4789 FUEL QUALITY SERVICES, INC. -- LTSA-15 -- 6850-01-167-4789 ============ Product Identification ========================= Product ID:LTSA-15 MSDS Date:12/19/1990 FSC:6850 NIIN:01-167-4789 MSDS Number: BWSHK === Responsible Party === Company Name: FUEL QUALITY SERVICES, INC. Address:1754 GREEN ROAD Box:317 City:BUFORD State:GA ZIP:30518 Country:US Info Phone Num:404-945-7139 Emergency Phone Num:404-945-7139 Preparer's Name:R.V .DAUM CAGE:40161 === Contractor Identification === Company Name: FUEL QUALITY SERVICES, INC. Address: 4584 CANTRELL ROAD

Box:1380

City:FLOWERY BRANCH

State:GA ZIP:30542 Country:US

Phone: (800) 827-9790 - (770) 967-9790

CAGE:40161

======= Composition/Information on Ingredients ========

Ingred Name: ALIPHATIC PETROLEUM SOLVENT

CAS:8008-20-6

RTECS #:OA5500000 Fraction by Wt: 50 - 58%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name

:TRADE SECRET COMPONENT/NJ TRADE SECRET

Fraction by Wt: 12.6-21%

Other REC Limits: NONE RECOMMENDED

Ingred Name: STYRENE MONOMER (SARA 313)

CAS:100-42-5

RTECS #:WL3675000 Fraction by Wt: 0.84%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:S,50PPM/100STEL;9596

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: N, N-DIMETHYLCYCLOHEXYLAMINE

CAS:98-94-2

RTECS #:GX1198000 Fraction by Wt: 10.5-14%

Other REC Limits: NONE RECOMMENDED

Ingred Name: N, N'DISALYCYLIDENE-1, 2 PROPANE DIAMINE

CA

S:94-91-7

RTECS #:GP3130000 Fraction by Wt: 0.8-2.1%

Other REC Limits: NONE RECOMMENDED

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)

CAS:1330-20-7

RTECS #:ZE2100000 Fraction by Wt: 0.2-.63%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9596

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: ETHYL BENZENE (SARA 313)

CAS:100-41-4

RTECS #:DA0700000 Fraction by Wt: 0.084%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/125STEL;959

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: 3,5-XYLENOL/MIXED CRESOLS AND XYLENOLS

CAS:108-68-9

RTECS #:ZE6475000

Fraction by Wt: 200 MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: NONSPECIFIC DISCOMFORT, SUCH AS

NAUSEA, HEADACHE, OR WEAKNESS; OR SKIN IRRITATION WITH DISCOMFORT OR RASH, ABNORMAL KIDNEY AND LIVER FUNCTIONS, TEMPORARY LUNG IRRITATION EFFECTS WITH COUGH, DIS

COMFORT, DIFFICULTY BREATHING,

OR SHORTNESS OFBREATH

Explanation of Carcinogenicity: NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure: SKIN BURNS OR ULCERATION. EVIDENCE SUGGESTS THAT KEROSINE CAN PERMEATE THE SKIN.

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASES OF THE LIVER MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURE.

First Aid:EYE: IMMEDIATELY FLU

SH WITH PLENTY OF WATER FOR AT LEAST 15

MINUTES. CALL A PHYSICIAN. SKIN: IMMEDIATE FLUSH WITH PLENTY OF WATER FOR 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING. CALL A PHYSICIAN. INHALATION: REMOVE TO FREAH AIR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. IMMEDIATELY GIVE TWO GLASSES OF WATER IF CONSCIOUS. CALL A PHYSICIAN.

Flash Point: 109F, 43C

Extingu

ishing Media:WATER SPRAY, CHEMICAL FOAM, DRY CHEMICAL, CARBON


DIOXIDE

Fire Fighting Procedures: EVACUATE PERSONNEL TO A SAFE AREA. WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: COMBUSTIBLE LIQUID

======== Accidental Release Measures ============

Spill Release Procedures:USE APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT BEFORE PROCEEDING WITH CLEAN-UP. SOAK UP WITH SAWDUST, SAND, OIL DRY OR OTHER ABSORBENT. THIS MATERIAL IS AN IGNITABLE, COR



tor/Materials to Avoid:YES
NONE REASONABLY FORESEEABLE
Stability Condition to Avoid:NONE REASONABLY FORESEEABLE
Hazardous Decomposition Products: DECOMPOSITION WILL NOT OCCUR

======= Disposal Considerations ============

Waste Disposal Methods:TREATMENT, STORAGE, TRANSPORTATION AND DISPOSAL MUST BE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.
THIS MATERIAL MAY BE A RCRA REGULATED HAZARDOUS WASTE UPON DISPOSAL DUE TO THE IGNITAB ILITY CHARACTERISTIC

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situ ation.