

DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV. -- HYSOL PC16M,PART A --
5970-01-099-8525

===== Product Identification =====

Product ID:HYSOL PC16M,PART A

MSDS Date:08/14/1991

FSC:5970

NIIN:01-099-8525

Kit Part:Y

MSDS Number: BWSVN

=== Responsible Party ===

Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV.

Address:211 FRANKLIN ST.

City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Info Phone

Num:716-372-6300

Emergency Phone Num:716-372-6309

Preparer's Name:JAMES P. HORNBURG

CAGE:04347

=== Contractor Identification ===

Company Name:DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV

Address:211 FRANKLIN ST.

Box:City:OLEAN

State:NY

ZIP:14760-1297

Country:US

Phone:716-372-6300/6309

CAGE:04347

Company Name:MCKEOWN ROBERT CO. INC.

Address:111 CHAMBERS BROOK RD.

Box:City:SOMERVILLE

State:NJ

ZIP:08876

Country:US

Phone:908-218-9000

CAGE:7B953

===== Composition/Information on Ingredien

ts =====

Ingred Name:BISPHENOL A-EPICHLOROHYDRIN COPOLYMER
CAS:25068-38-6
RTECS #:SL6475000
Fraction by Wt: 60-100%
Other REC Limits:NONE RECOMMENDED

Ingred Name:N-BUTYL GLYCIDYL ETHER (BGE)
CAS:2426-08-6
RTECS #:TX4200000
Fraction by Wt: 6.612%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:25 PPM; 9394

===== Hazards Identification =====

LD50 LC50 Mixture:PEL FOR THIS PRODUCT IS 50PPM
Routes of Entry: Inhalation:NO Skin:YES Ingestion:
YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE MODERATE
IRRITATION.MATERIAL AT HIGH TEMPERATURES MAY CAUSE THERMAL
BURNS.SKIN:MAY CAUSE MODERATE IRRITATION OR SENSITIZATION.MATERIAL
AT HIGH TEMPERATURE MAY CAUSE THERMAL BURNS.INGEST :MAY CAUSE GI
TRACT IRRITATION.INHAL:UNLIKELY ROUTE OF EXPOSURE.
Explanation of Carcinogenicity:INGRED #2 IS LISTED ON CALIFORNIA
PROPOSITION 65 AS A POSSIBLE CARCINOGEN.
Effects of Overexp
osure:SKIN:RASHES(EG.HIVES).
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING EYE
DISORDERS OR SKIN AND RESPIRATORY ALLERGIES MAY BE AT INCREASED
RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WIPE OFF EXCESS;FLUSH WITH
WATER;WASH WITH SOAP AND WATER.BURNS SHOULD BE TREATED AS A MEDICAL
EMERGENCY.EYES:FLUSH WITH COOL WATER FOR 15 MINUTES.INHAL:REMOVE TO
FRE SH AIR.GIVE OXYGEN

OR ARTIFICIAL RESPIRATION IF
NEEDED.INGEST:DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL
ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:155F,68C

Extinguishing Media:SMALLER FIRES-DRY CHEMICAL,CARBON DIOXIDE;LARGER
FIRES- ALCOHOL OR POLYMER FOAM.

Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard:FIRE CONDITIONS MAY EVOLVE TOXIC FU
MES.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT
ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE
CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED
PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY
FROM HEAT AND
INCOMPATIBLE MATERIALS.

Other Precautions:AVOID SKIN AND EYE CONTACT.DO NOT INHALE
VAPORS/MISTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN
ENCLOSED SPACES USE A SELF-CONTAINED BREATHING APPARATUS.

Ventilation:USE GENERAL DILUTION VENTILATION.

Protective Gloves:RUBBER OR PLASTIC

Eye Protection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING,AS NEED
ED.PROVIDE A

LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS
PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.

Supplemental Safety and Health

KEY1;F8.INGRED #2 IS LISTED IN SECTION 313 AND EMISSIONS MUST BE
INCLUDED IN EPCRA TRI REPORTING.NOTE OT PHYSICIAN:NO TREATMENT IS
NEEDED EXCEPT FOR INGESTION OF LARGE QUANTITIES OF THIS PRODUCT;IN
GE NERAL,EMESIS IS NOT NEEDED.

===== Physical/Chemical Properties =====

=====

HCC:F6

Spec Gravity:1.08

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)

Solubility in Water:INSOLUBLE

Appearance and Odor:LIQUID,MEDIUM VISCOCITY;AMBER;VERY SLIGHT
CHARACTERISTIC ODOR.

Percent Volatiles by Volume:8

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALIES,AMINES,ACIDS,WATER.

Stability Condition to Avoid:HIGH HEAT.

Hazardous Decomposition Products:CARBON DIOXIDE,CARBON
MONOXIDE,ALDEHYD

ES,ACIDS AND UNIDENTIFIED ORGANIC COMPOUNDS.

Conditions to Avoid Polymerization:EXOTHERMIC REACTION OCCURS (HEAT MAY
BE GIVEN OFF) WHEN LARGE QUANTITIES ARE MIXED WITH THE CURING
AGENT.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.