View NSN Online: https://aerobasegroup.kr/nsn/6850-01-261-6064

## STATIC CONTROL COMPONENTS INC -- 6850 A1 II CORRECT PRINT TONER -- 6850-01-261-6064

Product ID:6850 A1 II CORRECT PRINT TONER

MSDS Date:05/10/1994

FSC:6850

NIIN:01-261-6064

MSDS Number: BWZHW === Responsible Party ===

Company Name: STATIC CONTROL COMPONENTS INC

Address:330 WICKER ST

City:SANFORD

State:NC ZIP:27330 Country:US

Info Phone Num:919-774-3808

**Emergency P** 

hone Num:919-774-3808

CAGE:0GAA9

=== Contractor Identification ===

Company Name: BSC INC

Address:411 WAVERLY OAKS ROAD

Box:City:WALTHAM

State:MA ZIP:02154 Country:US CAGE:0EC53

Company Name: STATIC CONTROL COMPONENTS INC

Address:330 WICKER ST

Box:152

City:SANFORD

State:NC

ZIP:27331-0152 Country:US

Phone:919-774-3808

CAGE:0GAA9

====== Composition/Information on Ingredients ========

Ingred Name: ACRYLIC ACID BUTYL ESTER POLYMER WITH STYRENE

CAS:25767-47-9

Fraction by Wt: 60-70%

Other

CAS:68909-20-6 Fraction by Wt: 0.1-0.5% Other REC Limits:NONE RECOMMENDED	Limits:NONE RECOMMENDED
[1-((5-CHLORO-2-HYDROXY-PHENYL)AZ0)-2-NAPHTALENOLATO(2-)]-,HDROGEN, CAS:31714-55-3 Fraction by Wt: 0.1-0.5% Other REC Limits:NONE RECOMMENDED  Ingred Name:POLYPROPYLENE CAS:9003-07-0 RTECS #:TR5000000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED  Ingred Name:SILICA CAS:68909-20-6 Fraction by Wt: 0.1-0.5% Other REC Limits:NONE RECOMMENDED  =================================	1317-61-9 ion by Wt: 30-40% r REC Limits:NONE RECOMMENDED A PEL:10 MG/M3
CAS:9003-07-0 RTECS #:TR5000000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED  Ingred Name:SILICA CAS:68909-20-6 Fraction by Wt: 0.1-0.5% Other REC Limits:NONE RECOMMENDED  =================================	((5-CHLORO-2-HYDROXY-PHENYL)AZ0)-2-NAPHTALENOLATO(2-)]-,HDROGEN, 31714-55-3 ion by Wt: 0.1-0.5%
Effects of Overexposure:MINIMAL RESPIRATORY TRACT AND EYE IRRITATION MAY OCCUR WITH EXPOSURE TO LARGE AMOUNTS OF ANY NON-TOXIC DUST. Medical Cond Aggravated by Exposur e:NONE  ==================================	9003-07-0 CS #:TR5000000 ion by Wt: 1-5%
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NO KNOWN HEALTH HAZARDS WHEN USED AS INTENDED IN A PRINTING MACHINE. Effects of Overexposure:MINIMAL RESPIRATORY TRACT AND EYE IRRITATION MAY OCCUR WITH EXPOSURE TO LARGE AMOUNTS OF ANY NON-TOXIC DUST. Medical Cond Aggravated by Exposur e:NONE  ==================================	68909-20-6 ion by Wt: 0.5%
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NO KNOWN HEALTH HAZARDS WHEN USED AS INTENDED IN A PRINTING MACHINE. Effects of Overexposure:MINIMAL RESPIRATORY TRACT AND EYE IRRITATION MAY OCCUR WITH EXPOSURE TO LARGE AMOUNTS OF ANY NON-TOXIC DUST. Medical Cond Aggravated by Exposur e:NONE  ==================================	========= Hazards Identification ===============
First Aid:GET MEDICAL ASSISTANCE FOR ALL CASES OF OVEREXPOSURE. EYES-IMMEDIATELY FLUSH THOROUGHLY FOR 15 MINUTES. SKIN- WASH WITH SOAP	orts of Carcinogenicity:NTP:NO IARC:NO OSHA:NO h Hazards Acute and Chronic:NO KNOWN HEALTH HAZARDS WHEN USED AS TENDED IN A PRINTING MACHINE. ts of Overexposure:MINIMAL RESPIRATORY TRACT AND EYE IRRITATION AY OCCUR WITH EXPOSURE TO LARGE AMOUNTS OF ANY NON-TOXIC DUST. cal Cond Aggravated by Exposur NE
IMMEDIATELY FLUSH THOROUGHLY FOR 15 MINUTES. SKIN- WASH WITH SOAP	======================================
RESPIRATION IF BREATHING HAS STOPPED. INGESTION- IF CONSCIOUS GIVE WATER FREELY AND GET MEDICAL ATTENTION.	MEDIATELY FLUSH THOROUGHLY FOR 15 MINUTES. SKIN- WASH WITH SOAP ID WATER. INHALATION- REMOVE TO FRESH AIR. GIVE ARTIFICAL SPIRATION IF BREATHING HAS STOPPED. INGESTION- IF CONSCIOUS
======================================	======================================

Extinguishing Media:WATER SPR

AY, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. COOL FIRE EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:NONE
========= Accidental Release Measures ==========
Spill Release Procedures:SWEEP UP OR PICK UP WITH A VACUUM CLEANER. REMOVE RESIDUAL WITH SOAP AND WATER.
============ Handling and Storage =============
Handling and Storage Precautions:KEEP C ONTAINERS CLOSED. STORE IN COOL AND DRY PLACE. KEEP OUT OF REACH OF CHILDREN. DO NOT STORE NEAR STRONG OXIDIZING AGENTS. Other Precautions:DO NOT HANDLE IN AREAS WHERE THE WIND BLOWS; FLYING POWDER MAY ENTER INTO EYES. AVOID PROLONGED INHALATION OF EXCESSIVE DUST.
====== Exposure Controls/Personal Protection =======
Respiratory Protection:NONE NORMALLY REQUIRED. Ventilation:USE ADEQUATE VENTILATION. Protective Gloves:NONE NORMALLY REQUIRED. Eye Protection:NONE NO RMALLY REQUIRED. Other Protective Equipment:NONE Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. Supplemental Safety and Health NONE
========== Physical/Chemical Properties ==========
HCC:N1 Melt/Freeze Pt:M.P/F.P Text:266F,130C Spec Gravity:1.3 Solubility in Water:INSOLUBLE Appearance and Odor:BLACK POWDER, FAINT ODOR.  ===================================
Stability Indicator/Materials

to Avoid:YES
NONE
Stability Condition to Avoid:OPEN FLAMES
Hazardous Decomposition Products:CARBON MONOXIDE AND OTHER
DECOMPOSITION PRODUCTS IN CASE OF INCOMPLETE COMBUSTION.

======= Disposal Considerations ===========

Waste Disposal Methods:USED TONER SHOULD BE DISPOSED OF IN AN ENVIRONMENTALLY SAFE MANNER AND IN ACCORDANCE WITH ALL GOVERNMENT REGULATIONS. DO NOT INCINERATE.

Disclaimer (provided with this information by the compiling agencies): This info

rmation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.