View NSN Online: https://aerobasegroup.kr/nsn/6685-00-491-8220

UNION CARBIDE CORP., LINDE DIV. -- NITROGEN -- 6685-00-491-8220

Product ID:NITROGEN MSDS Date:08/01/1985 FSC:6685 NIIN:00-491-8220 MSDS Number: BWZLQ === Responsible Party === Company Name: UNION CARBIDE CORP., LINDE DIV. Address:39 OLD RIDGEBURY RD City:DANBURY State:CT ZIP:06817-0001 Country:US Info Phone Num:203-794-2000 Emergency Phone Num:800-822-4357 CAGE:36 346 === Contractor Identification === Company Name: UNION CARBIDE CORP LINDE DIV Address:39 OLD RIDGEBURY RD Box:City:DANBURY State:CT ZIP:06817-0001 Country:US Phone:800-822-4357; 304-744-3487 CAGE:36346 Company Name: WEKSLERIGLASS THERMOMETER CORP Address:80 MILL ROAD Box:City:FREEPORT State:NY ZIP:11520 Country:US Phone:516-623-0100 CAGE:64467

Ingred Name:NITROGEN CAS:7727-37-9 RTECS #:QW9700000 Fraction by Wt: 100% Other Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SWALLOWING-PRODUCT IS A GAS AT NORMAL TEMPERATURE/PRESSURE. INHALATION-ASPHYXIANT. SKIN-NO HARMFUL EFFECTS EXPECTED FROM VAPOR. EYE-NO HARMFUL EFFECTS EXPECTED FROM VAPOR. CHRONIC: NO EVIDENCE OF AD VERSE EFFECTS FROM AVA ILABLE

INFORMATION.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:INHALATION: HEADACHE, DROWSINESS, DIZZINESS, EXCITATION, EXCESS SALIVATION, NAUSEA, VOMITING, AND LOSS OF CONSCIOUSNESS. LACK OF OXYGEN CAN CAUSE DEATH. SKIN: LIQUID MAY CAUSE FROSTBITE.

Medical Cond Aggravated by Exposure: THE TOXICOLOGICAL/PHYSICAL PROPERTIES OF THIS MATERIAL DO NOT SUGGEST THAT OVEREXPOSURE IS

LIKELY TO AGGRAVATE EXISTING MEDICAL CONDITIONS.

First Aid:SKIN: FOR EXPOSURE TO LIQUID, IMMEDIATELY WARM FROSTBITE AREA WITH WARM WATER (NOT EXCEED 105F). CALL A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. GIVE O XYGEN IF BREATHING IS DIFFICULT. CALL APHYSICIAN. EYE: IMMEDIATELY FLUSH EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MIN. SEE A PHYSICIAN.

\_\_\_\_\_

Flash Point:NONE

Extinguishing Media:NITROGEN CANNOT CATCH FIRE. USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:EVACUATE ALL PERSONNEL FROM DANGER AREA. IMMEDIATELY DELUGE CONTAINERS WITH WATER SPRAY FROM MAXIMUM DISTANCE UNTIL COOL, THEN MOVE CONTAINERS AWAY FROM FIRE. Unusual Fire/Explosion Hazard:CONTAINER MAY RUPTURE EXPLOSIVELY WITH HEAT OF FIRE. MOST CONTAINERS ARE DESIGNED TO VENT CONTENTS

## WHEN THEY ARE EXPOSED TO ELEVATED TEMPERATURES.

Spill Release Procedures: EVACUATE ALL PERSONNEL FROM DANGER AREA. USE SELF-CONTAINED BREATHING APPARATUS WHERE NEEDED. SHUT OFF LEAK IF WITHOUT RISK. VENTILATE AREA OF LEAK OR MOVE CONTAINER TO WELL VENTILATED AREA. TEST AREA FOR SUFFICIENT OXYGEN BEFORE ENTERING.

Handling and Storage Precautio

ns:NEVER WORK ON A PRESSURIZED SYSTEM. IF

THERE IS A LEAK, CLOSE THE CYLINDER VALVE, BLOW DOWN THE SYSTEM BY VENTING TO A SAFE PLACE, THEN REPAIR LEAK.

Other Precautions: CAUTION: HIGH PRESSURE GAS. USE PIPING AND EQUIPMENT ADEQUATELY DESIGNED TO WITHSTAND PRESSURES TO BE ENCOUNTERED. CAN CAUSE RAPID SUFFOCATION DUE TO OXYGEN DEFICIENCY. STORE AND USE WITH ADEQUATE VEN TILATION. CLOSE VALVE WHEN NOT IN USE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:SELECT IN ACCORDANCE WITH OSHA 29 CFR 1910.134. RESPIRATORS SHALL BE ACCEPTABLE TO MSHA AND NIOSH. Ventilation:LOCAL EXHAUST-PREFERRED. MECHANICAL-ACCEPTABLE. Protective Gloves:PREFERRED FOR CYLINDER HANDLING. Eye Protection:SELECT IN ACCORDANCE WITH 29CFR 1910.133 Other Protective Equipment:METATARSAL SHOES FOR CYLINDER HANDLING. SELECT IN ACCORDANCE WITH OSHA 29 CFR 1910.132 AND 1910.133. Work Hygienic Practices:STANDARD HYGIENIC PRACTICES. Supplemental Safety an d Health NONE

HCC:N1 Boiling Pt:B.P. Text:-320F,-196C Melt/Freeze Pt:M.P/F.P Text:-346F,-210C Vapor Pres:GAS Vapor Density:0.967 Spec Gravity:GAS Solubility in Water:NEGLIGIBLE Appearance and Odor:COLORLESS, ODORLESS GAS AT NORMAL TEMPERATURE AND PRESSURE. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES UNDER CERTAIN CONDITION

S, NITROGEN CAN REACT VIOLENTLY WITH LITHIUM, NEODYMIUM, TITANIUM OZONE. Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES. Hazardous Decomposition Products:NONE

Waste Disposal Methods:SLOWLY RELEASE INTO ATMOSPHERE. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE EITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this

information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.