View NSN Online: https://aerobasegroup.kr/nsn/9150-01-351-9018

TEXACO REFINING AND MARKETING INC. -- 02109 URSA SUPER PLUS SAE 15W-40 -9150-01-351-9018

Product ID:02109 URSA SUPER PLUS SAE 15W-40 MSDS Date:01/01/1995 FSC:9150 NIIN:01-351-9018 MSDS Number: BWZSS === Responsible Party === Company Name: TEXACO REFINING AND MARKETING INC. Address:1111 RUSK STREET Box:4427 **City:HOUSTON** State:TX ZIP:77002-3310 Country:US Info Pho ne Num:713-650-5206 Emergency Phone Num:713-650-5206, CHEMTREC 800-424-9300 Preparer's Name: MANAGER, PRODUCT SAFETY CAGE:2R503 === Contractor Identification === Company Name: TEXACO REFINING AND MARKETING INC Address:1111 RUSK ST Box:City:HOUSTON State:TX ZIP:77002-3310 Country:US Phone:713-650-5206 CAGE:2R503

Ingred Name:SEVERELY SOLVENT REFINED, SOLVENT DEWAXED HEAVY PARAFFINIC PETROLEUM DISTILLATES CAS:64742-65-0 RTECS #:PY8038500 Fraction by Wt: 80-95% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:ALKENYLSUCCINIMIDE DISPERSANT Fraction by Wt: 3-10% Other REC Limits:NONE RECOMMENDED

Ingred Name:DIALKYLDITHIOPHOSPHORIC ACID, ZINC SALT CAS:84605-29-8 Fraction by Wt: 0.1-0.9% Other REC Limits:NONE RECOMMENDED

Ingred Name:ZINC DITHIOPHOSPHATE (ZINC 0,0-BISISODECYL DITHIOPHOSPHATE) CAS:25103-54-2 Fraction by Wt: 0.1-0.9% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5000 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: INHALATION OF HIGH CONCENTRATIONS MAY CAUSE RESPIRATORY IRRITATION, HEADACHE & NAUSEA. CONTACT WITH SKIN & EYES MAY CAUSE IRRITATION. INGESTION MAY CAUSE GI TRACT IRRITATION. CHRONIC: NO ADVERS E EFFECTS HAVE BEEN DO CUMENTED IN HUMANS AS A RESULT OF CHRONIC EXPOSURE. Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN. Effects of Overexposure:INHALED-HEADACHE, NAUSEA, IRRITATION OF NOSE & THROAT, DROWSINESS. INGESTED-ABDOMINAL DISCOMFORT, NAUSEA, DIARRHEA. EYES-TEMPORARY DISCOMFORT. SKIN-LOCAL REDNESS, SWELLING.

AN EXISTING DERMATITIS.

====

First Aid:EYES-FLUSH WITH LOTS OF WATER FOR SEVERAL MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. SKIN-WASH SKIN WITH PLENTY OF SOAP & WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INGESTED-IF C ONSCIOUS, GIVE 2 GLASSES OF WATER. GET MEDICAL ATTENTION. INHALED-IF SYMPTOMS OCCUR, REMOVE TO FRESH AIR. GET MEDICAL ATTENTION IF BREATHING BECOMES DIFFICULT OR RESPIRAATORY IRRITATION PERSISTS.

==

Flash Point Method:COC Flash Point:>435F,>224C Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL, FOAM. WATER OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER. Unusual Fire/Explosion Hazard:HYDROGEN SULFIDE MAY BE RELEASED WHEN OVERHEATED.

======= Accidental Release Measures =======

=========

Spill Release Procedures: VENTILATE AREA. AVOID BREATHING VAPOR. WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT, INCLUDING RESPIRATORY. CONTAIN SPILL IF POSSIBLE. WIPE UP OR ABSORB ON SUITABLE MATERIAL & SHOVEL UP. PREVENT ENT RY INTO SEWERS & WATERWAYS. AVOID CONTACT. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

Handling and Storage Precautions:PERIODS OF EXPOSURE TO HIGH TEMPERATURES SHOULD B E MINIMIZEDWATER CONTAMINATION SHOULD BE

AVOIDED.MINIMUM FEASIBLE HANDLING TEMPS SHOULD BE MAINTAINED Other Precautions:WHEN OVERHEATED, PRODUCT MAY RELEASE HYDROGEN SULFIDE GAS. HYDROGEN SULFIDE CONCENTRATIONS ABOVE PERMISSABLE CONCENTRATIONS CAN CAUSE IRRITATION OF EYES & RESPIRATORY TRACT, HEADACHE, DIZZINESS, NAUSE A, VOMITING, DIARRHEA, PULMONARY EDEMA.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection: IF ENGINEERING CONTROLS FAIL O

R NON-ROUTINE USE OR AN EMERGENCY OCCURS: WEAR AN MSHA/NIOSH APPROVED RESPIRATOR OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IN ACCORDANCE WITH 29 CFR 1910.13 4 AND MANUFACTURER'S RECOMMENDATIONS. Ventilation: USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S). Protective Gloves: NONE SPECIFIED BY MANUFACTURER. Eye Protection:SAFETY GLASSES/GOGGLES/FACESHIELD. Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER. Work Hygienic Pr actices:WASH HANDS AFTER HANDLING AND BEFORE EATING. DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health MORE ABOUT HYDROGEN SULFIDE: AT CONCENTRATIONS ABOVE 300 PPM, RESPIRATORY PARALYSIS, CAUSING UNCONSCIOUSNESS AND DEATH MAY OCCUR. EPA NOTES: SARA 302/304: NONE; SARA 311: NONE/N/R; SARA 313: DIALKYLDI THIOPHOSPHORIC ACID, ZINC SALT, CAS# 84605-29-8, 0.1-.99%; ZINC DITHIOPHOSPHATE, CAS# 25103-54-2, 0.1-0.99% ====== P HCC:V6 Spec Gravity:0.88 Viscosity:110 CST @ 40C Appearance and Odor: PALE LIQUID; MINERAL OIL ODOR. Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid: AVOID EXTREME TEMPERATURES OR EXTENDED STORAGE PERSIODS-HYDROGEN SULFIDE MAY ACCUMULATE IN HEAD-SPACE OF CONTAINER. Hazardous Decomposition Products: TOXIC LEVELS OF CARBON MONO XIDE. CARBON DIOXIDE, IRRITATING ALDEHYDES, KETONES & COMBUSTION PRODUCTS/CMDS OF SULFUR. Conditions to Avoid Polymerization: WILL NOT OCCUR.

Waste Disposal Methods:THIS PRODUCT HAS BEEN EVALUATED FOR RCRA CHARATERISTICS AND DOES NOT MEET THE CRITERIA OF A HAZARDOUS WASTE IN ITS PURCHASED FORM. UNDER RCRA, IT IS THE RESPONSIBILITY OF THE PURCHASER TO DETERMINE AT DISPOSAL, WHETHER PRODUCT MEETS RCRA CRI

TERIA.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.