View NSN Online: https://aerobasegroup.kr/nsn/1620-00-905-1593

Product ID:CADMIUM PLATED AIRCRAFT PART MSDS Date:12/01/1993 FSC:1620 NIIN:00-905-1593 MSDS Number: BXBMH === Responsible Party === Company Name: ALLIED SIGNAL INC., AIRCRAFT LANDING SYSTEM Address:3520 WESTMOOR STREET **City:SOUTH BEND** State:IN ZIP:46628 Country:US Info Phone Num:219-231-2302 Emergency Phone Num:219-231-2000 CAGE:55284 === Contractor Identification === Company Name: HONEYWELL INTL INC, AIRCRAFT LANDING SYSTEM ALS Address:3520 WESTMOOR STREET Box:City:SOUTH BEND State:IN ZIP:46628-1373 Country:US Phone:219-231-2201 CAGE:55284 

Ingred Name:CADMIUM (SARA 313) (CERCLA) CAS:7440-43-9 RTECS #:EU9800000 Fraction by Wt: TRACE Other REC Limits:NONE RECOMMENDED OSHA PEL:0.2 MG/M3 DUST; Z-2 ACGIH TLV:0.01 MG/M3 DUST;9495 EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic: THIS METAL AIRCRAFT PART IS PLATED W/CADMIUM. PART IS NOT HAZARDOUS. HAZARDS ARE FROM DUSTS & FUMES GENERATED IF PART IS MACHINED. AVOID CONTACT W/CADMIUM DUST & FUMES. ACUTE-ACUTE PNEUMONITIS & PU LMO NARY EDEMA. CHRONIC-KIDNEY DISEASE, LUNG & PROSTATE CANCER, REDUCED PULMONARY FUNCTION & LUNG DISEASE. Explanation of Carcinogenicity: PLATED W/CADMIUM [7440-43-9] WHICH IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN. Effects of Overexposure: EYES: REDNESS OR PAIN. SKIN: IRRITATION. INHALATION: RESPIRATORY IRRITATION, SHORTNESS OF BREATH, CHEST PAIN, FLU-LIKE SYMPTOMS, WEAKNESS, FEVER, HEADACHE, CHILLS, SWEATING, MUSCULAR PAIN. INGESTION: VOMI TING, ABDOMIN AL PAIN, NAUSEA, DIARRHEA, HEADACHE, & SORE THROAT. Medical Cond Aggravated by Exposure:MFR GAVE NO INFORMATION ON MSDS.

First Aid:GET MEDICAL ATTENTION IMMEDIATELY FOR ANY EXPOSURE. EYE:FLUSH W/WATER TO 15 MIN. SKIN:WASH W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING & LAUNDER BEFORE REUSE. INHALED:REMOVE FROM EXPOSURE. AID OR RES TORE BREATHING AS NEEDED. INGESTED:TREATMENT MUST BE ADMINISTERED BY MEDICAL P ERSONNEL. ADVICE TO PHYSICIAN:DO NOT PERFORM CHELATION THERAPY.

Extinguishing Media:DRY SAND, DRY DOLOMITE, DRY GRAPHITE, OR SODIUM CHLORIDE

Fire Fighting Procedures: WEAR A SELF-CONTAINED BREATHING APPARATUS W/FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:CADMIUM DUST CREATED DURING MACHINING MAY PRESENT A MODERATE EXPLOSION HAZARD WHEN EXPOSED TO FLAME. DUST & STRONG

## OXIDIZERS MAY CASUSE FIRE OR EXPLOSION.

Spill Release Procedures: (ALWAYS WEAR RECOMMENDED PERSONAL PROTECTIVE EQUIPMENT.) ANY NORMAL CLEAN-UP PROCEDURE IS APPLICABLE. AVOID GENERATION OF DUSTS. SPILLS & RELEASES MAY HAVE TO BE REPORTED TO FEDERAL &/OR LOCAL AUTHOR ITIES. Neutralizing Agent: MFR GAVE NO INFORMATION ON MSDS.

Handling and Storage P
recautions:SHIPPING & STORAGE CONTAINERS
CONTAINING CADMIUM, CADMIUM COMPOUNDS, CONTAMINATERD CLOTHING &
EQUIPMENT, WASTE, SCRAP, ETC. MUST BEAR WARNING LABELS.
Other Precautions:AVOID CONTACT TO SKIN, EYES & CLOTHING. AVOID
BREATHING DUST. USE ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:RESPIRATORS USED MUST BE APPROVED BY BOTH MSHA & NIOSH. AIR PURIFYING RESPIRATORS MUST B
E EQUIPPED W/HEPA FILTERS.
AIR SUPPLIED RESPIRATORS OPERATED IN POSITIVE PRESSURE MODE ARE ALSO ACCEPTABLE. SUIT EQUIPMENT TO EXPOSURE LEVEL.
Ventilation:USE GENERAL OR LOCAL EXHAUST VENTILATION TO KEEP CADMIUM DUST & FUME LEVELS BELOW THE TLV.
Protective Gloves:RUBBER
Eye Protection:SAFETY GOGGLES/FACE SHIELD REQUIRED
Other Protective Equipment:RUBBER APRON AND/OR SUIT REQUIRED. CLEAN CHANGE ROOMS, HAND WASHING FACILITIES, SHOWERS SHOULD BE AVAILABLE.
Work Hygienic Practices:MF
R:?. HMIS:USE GOOD CHEMICAL HYGIENE PRACTICES. AVOID CONTACT IF AT ALL POSSIBLE. WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health NONE

## HCC:N1

NRC/State Lic Num:NONE

Appearance and Odor:MATTED TEXTURE METALLIC TO POLISHED METAL FINISH

Stability Indicator/Materials to Avoid:YES HYDROCHLORIC &/OR NITRIC ACIDS Stability Condition to Avoid:

## MFR GAVE NO INFORMATION ON MSDS. Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:RCRA HAZARDOUS WASTE = D006. DISPOSE I/A/W FEDERAL, STATE & LOCAL REGULATIONS. NOTE:THIS MATERIAL MAY HAVE VALUE ON A RECYCLED BASIS. IF RECLAIMED, THE MATERIAL IS NOT HAZARDOUS UNDER RCRA. THIS INFOR MATION IS FOR THE PRODUCT SHIPPED.

Disclaimer (provided with this information by the compiling agencies):  $\ensuremath{\mathsf{T}}$ 

his information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.