

SHERWIN-WILLIAMS CO,KRYLON PROD GROUP,SPEC GROUP -- 1301 ACRYLIC CRYSTAL CLEAR --  
8010-00-990-7289

===== Product Identification =====

Product ID:1301 ACRYLIC CRYSTAL CLEAR

MSDS Date:07/20/1994

FSC:8010

NIIN:00-990-7289

MSDS Number: BXC BK

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO,KRYLON PROD GROUP,SPEC GROUP

Address:31500 SOLON ROAD

City:SOLON

State:OH

ZIP:44139

Country:US

Info Ph

one Num:800-247-3266

Emergency Phone Num:216-292-7400

CAGE:54636

=== Contractor Identification ===

Company Name:SAX ARTS & CRAFTS SUB OF BEATRICE COMPANIES INC

Address:2405 S CALHOUN RD

Box:City:NEW BERLIN

State:WI

ZIP:53151

Country:US

Phone:262-784-6880

CAGE:26290

Company Name:SHERWIN-WILLIAMS CO THE

Address:101 PROSPECT AVE NW

Box:City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Phone:800-251-2486/216-566-2242

CAGE:54636

===== Composition/Information on Ingredients =====

I

ingred Name:PROPANE (PROPELLANT)  
CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 13%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN; 9394

ingred Name:ISOBUTANE (PROPELLANT)  
CAS:75-28-5  
RTECS #:TZ4300000  
Fraction by Wt: 17%  
Other REC Limits:NONE RECOMMENDED

ingred Name:VM & P NAPHTHA  
CAS:64742-89-8  
Fraction by Wt: 22%  
Other REC Limits:NONE RECOMMENDED

ingred Name:ETHYL BENZENE (SARA III)  
CAS:100-41-4  
RTECS #:DA0700000  
Fraction by Wt: 2%  
Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/125STEL;9394  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 12%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM; Z-2  
ACGIH TLV:S, 50 PPM; 9394  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

ingred Name:XYLENE (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 14%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/150STEL;9394  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:10

00 LBS

Ingred Name:ACETONE (SARA III)  
CAS:67-64-1  
RTECS #:AL3150000  
Fraction by Wt: 11%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:750PPM/1000STEL;9294  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:VOLITILE ORGANIC CONTENT AS LISTED ON MSDS AS % BY WT PER  
BAAQMD RULE 49, 94%.  
RTECS #:9999999VC  
Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of

Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:IRRIT OF EYES/SKIN/RESP SYSTEM. MAY  
CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPO MAY RESULT IN  
UNCONSC & POSSIBLE DEATH. PROLONG/REPEAT OVEREXPO TO HEXANE:DAMAGE  
TO NERVE TISSUE OF ARMS/LEGS(PERI PHERAL NEUROPATHY)RESULT:MUSCULAR  
WEK,LOSS SENSATION.INCREASED BY PRESENCE OF MEK.PROLONG OVEREXPO TO  
SOLVENT:MAY (SUPP)

Explanation of Carcinogenicity:PER MSDS:NOT INGRED IN PRODUCT IS  
IARC/NTP/OSHA  
LISTED CARCINOGEN.

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, & LOSS OF  
COORDINATION ARE INDICATIONS OF EXCESSIVE EXPO TO VAP/SPRAY MISTS.  
REDNESS & ITCHING OR BURNING SENSATION MAY INDICATE EYE/EXCESSIVE  
SKIN EXPO.

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

=====  
===== First Aid Measures =====

First Aid:INHAL:REMOVE FROM EXPO. RESTORE BREATHING. KEEP WARM/QUIET.  
SKIN:WASH AREA THOROUGHLY W/SOAP/WATER. REMOVE CONTAM

IN CLOTH.

EYES:FLUSH W/LG AMTS OF WATER FOR 15MINS. GET MED ATTN. INGEST:GET  
MED ATTN.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point: