

KRYLON INDUSTRIAL -- INDUSTRIAL MAINTENANCE & TOUCH UP SPRAY COLORS, 1403 --  
8010-00-132-2862

=====  
Product Identification  
=====

Product ID:INDUSTRIAL MAINTENANCE & TOUCH UP SPRAY COLORS, 1403

MSDS Date:01/05/1994

FSC:8010

NIIN:00-132-2862

MSDS Number: BXDND

=== Responsible Party ===

Company Name:KRYLON INDUSTRIAL

Address:31500 SOLON RD

City:SOLON

State:OH

ZIP:44139

Country:US

Info Phone Num:800-

247-3266

Emergency Phone Num:216-292-7400

CAGE:DO934

=== Contractor Identification ===

Company Name:KRYLON INDUSTRIAL

Address:6830 COCHRAN ROAD

City:SOLON

State:OH

ZIP:44139

Country:US

Phone:800-247-3266

CAGE:DO934

Company Name:SHERWIN-WILLIAMS CO THE

Address:101 PROSPECT AVE NW

Box:City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Phone:800-251-2486/216-566-2242

CAGE:54636

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PROPANE; (PROPANE (PROPELLANT)). VP:760.

CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 18%  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN

Ingred Name:SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC; (HYDROCARBON SOLVENT)

CAS:64742-95-6  
RTECS #:WF3400000  
Fraction by Wt: 3%  
OSHA PEL:N/K  
ACGIH TLV:N/K

Ingred Name:VM&P NAPHTHA; (ALIPHATIC PETROLEUM DISTILLATE). VP:2.

CAS:64742-48-9  
Fraction by Wt: 14%  
OSHA PEL:100 PPM (MFR)  
ACGIH TLV:100 PPM (MFR)

Ingred Name:XYLENE (SARA 313) (CERCLA). VP:5.9.

CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt  
: 4%  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM;150 STEL  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA 313) (CERCLA). VP:180.

CAS:67-64-1  
RTECS #:AL3150000  
Fraction by Wt: 48%  
OSHA PEL:1000 PPM  
ACGIH TLV:750 PPM;1000 STEL  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:VOLATILE ORGANIC COMPOUNDS (BAAQMD RULE 49): 85%.

RTECS #:9999999VO

Ingred Name:OTHER PREC:GROUNDING PROCS. CONTENTS UNDER PRESS. DO NOT PUNCTURE, INCIN/EXPOSE TO TEMP >120F. HEAT FROM (ING 8)

RTECS #:99

99999ZZ

Inged Name:ING 7:SUNLIGHT, RADIATORS, STOVES, HOT WATER & OTHER HEAT SOURCES COULD CAUSE CNTNR TO BURST. DO NOT TAKE (ING 9)  
RTECS #:9999999ZZ

Inged Name:ING 8:INTERNALLY. USE ONLY W/ADEQ VENT. AVOID BRTHG VAP & SPRAY MIST. AVOID CONT W/SKIN & EYES. THIS COATING MAY(ING 10)  
RTECS #:9999999ZZ

Inged Name:ING 9:CONTAIN MATLS CLASSIFIED AS NUISANCE PARTICULATES WHICH MAY BE PRESENT AT HAZ LEVELS ONLY DURING SANDING/ (ING 11)  
RTECS #:9999999ZZ

Inged Name:ING 10:ABRADING OF DRIED FILM. IF NO SPECIFIC DUSTS ARE LISTED, APPLIC LIMS FOR NUISANCE DUSTS ARE ACGIH TLV (ING 12)  
RTECS #:9999999ZZ

Inged Name:ING 11:10 MG/M3 TDUST, OSHA PEL 15 MG/M3 TDUST; 5 MG/M3 RESPIRABLE FRACTION.  
RTECS #:9999999ZZ

Inged Name:RESP PROT:DUST WHICH MAY BE GENERATED FROM THIS PRODUCT, UNDERLYING PAINT OR THE ABRASIVE.  
RTECS #:9999999ZZ

Inged Name:VENT:1910.94, 1910.107, 1910.108.  
RTECS #:9999999ZZ

===== Hazards Identification =====

LD50  
LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EXPOS MAY BE BY INHAL &/OR SKIN/EYE CONT, DEPENDING ON CNDTNS OF USE. TO MIN EXPOS, FOLLOW RECS FOR PROPER USE, VENT & PERSONAL PROT EQUIP. ACUTE:IRRIT OF EYES, SKIN & RESP SYS. MAY CAUSE NERV SYS DEP RESS. EXTREME OVEREXP MAY RSLT IN UNCON& POSS DEATH. HDCH, DIZZ, NAUS & LOSS OF COORD ARE INDI

CATIONS

(EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ:OF EXCESSIVE EXPOS TO VAPS/SPRAY MISTS. REDNESS & ITCH/BURNING SENSATION MAY INDICATE EYE/EXCESSIVE SKIN EXPOS. CHRONIC:PRLNG OVEREXP TO SOLV INGS MAY CAUSE ADVERSE EFTS IN LIVER, URINARY, BL OOD-FORMING, CVS & REPRO SYS. RPTS HAVEASSOC RPTD & PRLNG OVEREXP TO SOLVS W/PERM BRAIN & NERV SYS DMG. (SUPP DATA)

Medical Cond Aggravated by Exposure:NONE GENERALLY RECOGNIZED.

=

=====  
===== First Aid Measures =====

First Aid:INHAL:REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN:WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING & LAUNDRER BEFORE RE-USE. EYES:FLUSH W/LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INGEST:GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:-18C

Vapor Pr

es:SEE INGS

Vapor Density:HVR/AIR

Evaporation Rate & Reference:FASTER THAN ETHER

Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE KNOWN.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF METALS IN INGREDIENTS SECTION.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:WASTE FROM THIS PROD MAY BE HAZ AS DEFINED UNDER RCRA 40 CFR 261. WASTE MUST BE TESTED FOR IGNITABILITY TO DETERMINE APPLIC EPA HAZ WASTE NUMBERS. DO NOT INCINERATE. DEPRESSURIZE CNTNR. DISP OF I/A/W FED, STATE & LOC REGS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever

r,  
expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.