View NSN Online: https://aerobasegroup.kr/nsn/6850-01-383-4136

MITA COPYSTAR AMERICA,INC. -- BLACK TONER FOR DC-PART NO (SEE SUPPLEMENTAL FOR PART NO.) -- 6850-01-383-4136

============= Product Identification ========================

Product ID:BLACK TONER FOR DC-PART NO (SEE SUPPLEMENTAL FOR PART NO.)

MSDS Date:04/24/1995

FSC:6850

NIIN:01-383-4136

MSDS Number: BXFZT

=== Responsible Party ===

Company Name: MITA COPYSTAR AMERICA, INC.

Address:225 SAND ROAD

Box:40008

City:FAIRFIELD (FORMAL LY IN HASBROUCK HEIGHTS

State:NJ

ZIP:07004-0008

Country:US

Info Phone Num:201-808-8444

Emergency Phone Num:201-808-8444

CAGE:0AH08

=== Contractor Identification ===

Company Name: MITA COPYSTAR AMERICA INC

Address:2930-B S FAIRVIEW ST

Box:813

City:SANTA ANA

State:CA ZIP:92704 Country:US

Di 744.5

Phone:714-556-0318

CAGE:0AH08

Company Name: MITA INDUSTRIAL CO.LTD; MITA COPYSTAR AMERICA, INC.

Address:777 TERRACE AVENUE

Box:813

City: HASBROUCK HEIGHTS

State:NJ

ZIP:07604-3110 Country:US

Phone:201-288-6900

CAGE:6567

Company Name: MITA INDUSTRIAL COMPANY

Box:UNKNOW CAGE:S9463

Company Name: MONROE SYSTEMS FOR BUSINESS

Box:UNKNOW CAGE:0MXR4

Company Name: MONROE SYSTEMS FOR BUSINESS INC

Address:3416 WEST BROAD STREET

Box:City:RICHMOND

State:VA ZIP:23230 Country:US

Phone:804-353-5500

CAGE:69964

======= Composition/Information on Ingredients ========

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000 Fraction by Wt: 8%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9

394

Ingred Name: CHROMATE(1-), BIS[1-((5-CHLORO-2-HYDROXY-PHENYL-AZO)-2-

NAPHTALENOLATO(2-)]-,HYDROGEN

CAS:31714-55-3 Fraction by Wt: 1%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:1 MG/M3 ACGIH TLV:0.5 MG/M3

Ingred Name: ALPHA-ALUMINA (ALUMINUM OXIDE) (SARA 313)

CAS:1344-28-1

RTECS #:BD1200000 Fraction by Wt: 1%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9495

Ingred Name:2-PRPENOIC ACID,2-METHYL-,BUTYL ESTER, POLYMER WITH

ETHENYLBENZENE,

CAS:25213

-39-2

Fraction by Wt: 87%

Other REC Limits: NONE RECOMMENDED

Ingred Name: SILANE, DICHLORODIMETHYL-, REACTION PRODUCTS WITH SILICA

CAS:68611-44-9 Fraction by Wt: 1%

Other REC Limits: NONE RECOMMENDED

Ingred Name: POLYPROPYLENE

CAS:9003-07-0

RTECS #:TR5000000 Fraction by Wt: 2%

Other REC Limits: NONE RECOMMENDED

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

th Hazards Acute and Chronic:TARGET-ORGANS:NONE MUTAGENICITY IS NEGATIVE.

Explanation of Carcinogenicity:MFR GAVE THE ABOVE LISTINGS ON THE MSDS BUT NO OTHER COMMENTS ABOUT CARCINOGENICITY WERE RECORDED.

Effects of Overexposure: MINIMAL RESPIRATORY TRACT IRRITATION MAY OCCUR AS WITH EXPOSURE TO LARGE AMOUNTS OF ANY NON-TOXIC DUST. Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid:SKIN:WA

SH W/SOAP & WATER. EYE:FLUSH THOROUGHLY W/WATER & SEEK MEDICAL TREATMENT. INGESTION: DILUTE STOMACH CONTENTS W/SEVERAL GLASSES OF WATER & SEEK MEDICAL TREATMENT. INHALATION: PROMPTLY REMOVE FROM EXPOSURE TO FRESH AIR.

============ Fire Fighting Measures =========================

Flash Point: NONFLAMMABLE Lower Limits: NOT GIVEN **Upper Limits:NOT GIVEN** 

Extinguishing Media: IF PRODUCT BECOMES INVOLVED IN A FIRE, USE CARBON DIOXIDE EXTINGUISHER.

Fire Fighting Procedures: WATER,

Unusual Fire/Explosion Hazard: NONE UNDER NORMAL STORAGE & USE CONDITIONS. ======== Accidental Release Measures ============ Spill Release Procedures: CLEAN UP WITH A VACUUM CLEANER. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. ============= Handling and Storage ========================== Handling and Storage Precautions: CLOSE CAP TIGHTLY AND STORE IN A COOL, DRY AND DARK PLACE. Other Precautions: AVOID COMBUSTION. ====== Expo sure Controls/Personal Protection ======= Respiratory Protection: NONE REQUIRED UNDER NORMAL USE. Ventilation: NONE REQUIRED UNDER NORMAL USE. Protective Gloves: NONE REQUIRED UNDER NORMAL USE. Eye Protection: NONE REQUIRED UNDER NORMAL USE. Other Protective Equipment: GLOVES AND DUST FILTER RESPIRATOR RECOMMENDED WHEN HANDLING BULK AMOUNTS. Work Hygienic Practices: AVOID INHALATION, INGESTION, SKIN, OR EYE CONTACT. Supplemental Safety and Health FOR DC-111, 111C, 113, 114, 142RE, 211, 213RE, 313Z, 313ZD, 1001, 1205, 1255, 1415, 1435, 1455, 1605, 1656, 1685, 1824RE, 1824ZII, 1855, 2055, 2254, 2555, 2585, 3255, 3285, 4055, 4085. PER TIR, FOR P/N RL-912/911/911Z ========= Physical/Chemical Properties ============ HCC:N1 NRC/State Lic Num:NONE Boiling Pt:B.P. Text:NOT GIVEN Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Vapor Pres:NOT GIVEN Vapor Density:NOT GIVEN Spec Gravity:1.1 Evaporation Rate & Dr. Reference: NOT GIVEN Solubility in Water: INSOLUBLE App

FOAM OR DRY CHEMICAL.

earance and Odor:FINE BLACK POWDER, PRACTICALLY ODORLESS.
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:NO STRONG OXIDIZING AGENTS Stability Condition to Avoid:NONE Hazardous Decomposition Products:NONE IN NORMAL HANDLING & USE. Conditions to Avoid Polymerization:WILL NOT OCCUR.
======= Disposal Considerations ===========
Waste Disposal Methods:DISPOSE I/A/W FEDERAL, STATE & LOCAL REGULATIONS.
Disclaim er (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.