View NSN Online: https://aerobasegroup.kr/nsn/6850-01-383-4364

Product ID:7350 BLACK TONER, 4129036; SAVIN CODES 7912, 7350

MSDS Date:11/05/1991

FSC:6850

NIIN:01-383-4364

MSDS Number: BXFZV === Responsible Party === Company Name:RICOH CO LTD

Address:5 DEDRICK PL City:WEST CALDWELL

State:NJ

ZIP:07006-6304 Country:US

Info Phone Num:201-882-20

00, 800-336-6737

Emergency Phone Num:800-336-6737 Preparer's Name:RICOH CQA/EA DIVISION

CAGE:2Z665

=== Contractor Identification ===

Company Name: PAUL B. WILLIAMS CO

Box:UNKNOW CAGE:1M162

Company Name: RICOH CO LTD

Address:5 DEDRICK PL Box:City:CALDWELL

State:NJ

ZIP:07006-6304 Country:US

Phone:973-882-2000 / 800-336-6737

CAGE:2Z665

Company Name: SAVIN CORPORATION Address: 30 W GUDE DRIVE SUITE 350

Box:12070

City:ROCKVILLE

State:MD

ZIP:20850-4015

Country:US

Phone:301-517-4272 FAX 301-517-4269

CAGE:

======= Composition/Information on Ingredients ========

Ingred Name: POLYETHYLENE (DESCRIBED AS 'WAX' BY MFR)

CAS:9002-88-4

RTECS #:TQ3325000 Fraction by Wt: 6%

Other REC Limits: NONE RECOMMENDED

Ingred Name: ACRYLIC POLYMER

CAS:25068-63-7 Fraction by Wt: 3%

Other REC Limits: NONE RECOMMENDED

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000 Fraction by Wt: 2%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9495

Ingred Name: MINERAL SPIRITS (DE

SCRIBED AS 'HYDROTREATED HEAVY NAPHTHA'

BY MFR) CAS:64475-85-0 RTECS #:PY8240000

Fraction by Wt: 89%

Other REC Limits: NONE RECOMMENDED

========== Hazards Identification ================


LD50 LC50 Mixture:LD50 (ORAL RAT) IS >12400 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:ACUTE-SLIGHT EYE CONJUNCTIVAL IRRITATION. MILD SKIN IRRITATION W/EXCESSIVE EXPOSURE. NO UN TOWARD

EFFECTS FROM INHALATION. CHRONIC-STUDIES HAVE SHOWN MANY PETROLEUM HYDROCARBONS POSE POTENTIAL HYMAN HE ALTH RISKS WHICH MAY VARY FROM PERSON TO PERSON. AS PRECAUTION MINMIZE EXPOSURE TO LIQUID, VAPOR, MIST, OR FUMES.

Explanation of Carcinogenicity:MFR GAVE THE ABOVE LISTINGS ON THE MSDS BUT NO OTHER COMMENTS WERE RECORDED.

Effects of Overexposure:HIGH VAPOR CONCENTRATIONS (GREATER THAN APPROXIMATELY 1000 PPM) ARE IRRITATIVE TO THE EYES AND RESPIRATORY TRACT, C



GENERAL):ADEQUATE VENTILATION. LOCAL

EXHAUST: NONE NEEDED UNDER NORMAL CONDITIONS OF USE.

Protective Gloves: NONE NEED UNDER NORMAL CONDITION OF USE.

Eye Protection: NONE NEED UNDER NORMAL CONDITION OF USE.

Other Protective Equipment: NONE NEEDED UNDER NORMAL CONDITIONS OF USE.

Work Hygienic Practices:MINIMIZE BREATHING VAPOR/MIST. AVOID PROLONGED &/OR REPEATED SKIN CONTACT. SEE SUPP DATA.

Supplemental Safety and Health

REMOVE CONTAMINATED CLOTNING & LAUNDER OR DRY-CLEAN BEFORE REUSE. RE

MOVE & THOROUGHLY CLEAN & DRY SHOES BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT, BEFORE BREAKS & MEALS & AT END OF WORK PERI OD. PRODUCT IS READILY REMOVED FROM SKIN BY WATERLESS HAND CLEANERS FOLLOWED BY WASHING W/SOAP & WATER.

======== Physical/Chemical Properties ===========

HCC:F4
NRC/State Lic Num:NONE
Boiling Pt:B.P. Text:322F,161C
Vapor Pres:5
Spec Gravity:0.78

Evaporation Rate & Dr. Reference:0.3, N-BUAC=1.

Solubility in Water: NEGLIGIBLE,