View NSN Online: https://aerobasegroup.kr/nsn/9150-01-052-4893 MOBIL OIL CORP -- 1 FORMULA 15W-50 ______ MSDS Safety Information _____ FSC: 9150 NIIN: 01-052-4893 MSDS Date: 05/16/1993 MSDS Num: BXGZR Product ID: 1 FORMULA 15W-50 MFN: 01 Responsible Party Cage: 3U728 Name: MOBIL OIL CORP Address: 3225 GALLONS ROAD City: FAIRFAX VA 22037 Info Phone Numb er: 800-662-4525 Emergency Phone Number: 800-424-9300(CHEMTREC) Proprietary Ind: Y Published: Y ______ Contractor Summary ______ Cage: 3U728 Name: MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING Address: 3225 GALLOWS ROAD City: FAIRFAX VA 22037 Phone: 800-662-4525/856-224-4644 _____ Item Description Information _____ _____ Item Manager: S9G Item Name: GREASE, GENERAL PURPOSE Specification Number: NONE Type/Grade/Class: NONE Unit of Issue: CO Quantitative Expression: 0000000035LB UI Container Qty: 0 Type of Container: PAIL _____

Ingredients

Name: *** PROPRIETARY ***

Health Hazards Data

=========

LD50 LC50 Mixture: LD50: >2000 MG/KG

Route Of Entry Inds - Inhalation: NO

Skin: YES Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: SLIGHT EYE IRRIT. SLIGHT SKIN IRRITATION. CHRONIC: STUDIES

HAVE SHOWN THAT MICE DEVELOPED SKIN CANCER AFTER REPEATED APPLICATION OF USED

GASOLINE ENGINE OIL TO THE SKIN FOR THE LIFETIME OF THE ANIMALS . NO EFFORT

WAS MADE TO WASH THE OIL OFF BETWEEN APPLICATIONS. USED OIL FROM D

IESEL

ENGINES DID NOT(EFTS OF OVEREXP)

Explanation Of Carcinogenicity: NOT RELEVANT.

Signs And Symptions Of Overexposure: HLTH HAZS: PRODUCE THIS EFT. BECAUSE THE EFTS OBSERVED IN THE LAB TESTS, SERVICE STATION WORKERS, ENGINE MECHANICS & LL PERS WHO REGULARLY HANDLE USED MOTOR OIL SHOULD TAKE PRECS TO MINIMIZE CONTACT W/OIL. GOOD PERS HYGIENE PRACS, INCLG WASHING ANY SKIN CONTACT AREAS & PROVING OIL SOAK CLTHG SHOULD BE FOLLOWED.

Medical Cond Aggravated By Exposure: NONE SP

ECIFIED BY MANUFACTURER.

First Aid: EYE: FLUSH THOROUGHLY W/WATER FOR AT LEAST 15 MINUTES. IF IRRIT OCCURS, CALL MD. INGEST: IF >1.2 LITER(PINT) INGESTED, IMMED GIVE 1 TO 2 GLASSES OF WATER & CALL MD, HOSPITAL EMER ROOM/POISON CONTROL C ENTER FOR ASSIST. DO NOT INDUCE VOMIT/GIVE ANYTHING BY MOUTH TO AN UNCON PERSON. SKIN: WASH CONTACT AREAS W/SOAP & WATER. INHAL: REMOVE TO FRESH AIR. SUPPORT BREATHING(GIVE O*2/ARTF RESP)(FP N).

Handling and Disposal

Spill Release Procedures: ENVIRON IMPACT: IN CASE OF ACCIDENT/ROAD SPILL NOTIFY CHEMTREC(800)424-9300. REPORT SPILLS AS REQD TO APPROP AUTHS. U.S. COAST GUARD REGS REQ IMMED REPORTING OF SPILLS THAT COULD REACH ANY WATERWAY IN CLG INTERMITTENT DRY CREEKS. REPORT SPILL(SUPDAT)

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: PROD IS SUITABLE FOR BURNING IN ENCLSD, CONTROLLED B

URNER FOR FUEL VALUE/DISP BY SUPERVISED INCIN. SUCH BURNING MAY BE LIMITED PURSUANT TO RCRA. IN ADDN, PROD IS SUITABLE FOR PROCESSING BY AN APPRVD R ECYCLING FACILITY/CAN BE DISP OF AT ANY

Handling And Storage Precautions: NONE SPECIFIED BY MANUFACTURER.

Other Precautions: NONE SPECIFIED BY MANUFACTURER.

Fire and Explosion Hazard Information

Flash Point Method: COC

Flash Point Tex

t: >420F,>216C Lower Limits: 0.6% Upper Limits: 7.0%

Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL AND WATER FOG.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPRVD SCBA & DPRVD SCBA & DPRVD FULL PROT EQUIP(FP N). WATER/FOAM MAY CAUSE FROTHING. USE WATER TO KEEP FIRE EXPOSED CNTNRS

COOL. WATER SPRAY MAY BE USED(SUPDAT)

Unusual Fire/Explosion Hazard: NONE.

Control Measures

Respirato

ry Protection: NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF

USE & amp; WITH ADEQUATE VENTILATION. USE NIOSH/MSHA APPROVED RESPIRATOR

APPROPRIATE FOR EXPOSURE OF CONCERN(FP N).

Ventilation: NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

Protective Gloves: IMPERVIOUS GLOVES(FP N).

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGS(FP N).

Other Protective Equipment: EMERGENCY EYEWASH & DELUGE SHOWER MEETING ANSI

DESIGN CRITERIA(FP N).

Work Hygieni

c Practices: GOOD PERSONAL HYGIENE PRACTICES SHOULD ALWAYS BE FOLLOWED.

Supplemental Safety and Health: USERS OF THE "L" VERSION TO CONSULT THE "LR" VERSION OF FOR FURTHER INFO(FP N). FIRE FIGHT PROC: TO FLUSH SPILLS AWAY FROM EXPOSURE. FOR RUNOFF FROM FIRE CONTROL OR DILUTION FROM ENTERING STREAMS , SEWERS OR DRINKING WATER SUPPLY. SPILL PROC: TO COAST GUARD TOLL FREE #: (800) 424-8802.

Physical/Chemical Properties

========

B.P. Text: >600F,>316C

Vapor Pres: <0.1 Spec Gravity: 0.87

Solubility in Water: NEGLIGIBLE

Appearance and Odor: AMBER LIQUID W/MILD ODOR.

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: EXTREME HEAT. Materials To Avoid: STRONG OXIDIZERS.

Hazardous Decomposition Products: CARBON MONOXIDE.

Hazardous Polymerizat

ion Indicator: NO Conditions To Avoid Polymerization: NOT RELEVANT.
Toxicological Information
Ecological Information
MSDS Transport Information
======================================
Other Information
Transportation Information
Responsible Party Cage: 3U728 Trans ID NO: 103313 Product ID: 1 FORMULA 15W-50 MSDS Prepared Date: 05/16/1993 Review Date: 09/15/1995 MFN: 1 Multiple KIT Number: 0 Review IND: Y Unit Of Issue: CO Container QTY: 0 Type Of Container: PAIL
Detail DOT Information
DOT PSN Code: ZZZ DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
Detail IMO Information

IMO PSN Code

: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

Detail IATA Information

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Information

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

Product ID: 1 FORMULA 15W-50

Cage: 3U728

Company Name: MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Street: 3225 GALLOWS ROAD

City: FAIRFAX VA Zipcode: 22037

Health Emergency Phone: 800-424-9300(CHEMTREC)

Label Required IND: Y

Date Of Label Review: 04/24/1995

Status Code: C

Label Date: 04/24/1995 Origination Code: G Chronic Hazard I

ND: Y

Eye Protection IND: YES Skin Protection IND: YES Signal Word: CAUTION

Respiratory Protection IND: YES

Health Hazard: Slight Contact Hazard: Slight Fire Hazard: Slight Reactivity Hazard: None

Hazard And Precautions: COMBUSTIBLE. ACUTE: SLIGHT EYE IRRITATION. SLIGHT SKIN IRRITATION. CHRONIC: STUDIES HAVE SHOWN THAT MICE DEVELOPED SKIN CANCER AFTER

RPTD APPLIC OF USED GASOLINE ENGINE OIL TO SKIN FOR THE LIFETIME OF ANIMALS.

Disclaim

er (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liab

ility for such use. Any person

utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.