

NILES CHEMICAL PAINT CO -- 2405A DK GRAY: 1.8: COMP A -- 8010-01-350-4744

=====
Product Identification
=====

Product ID:2405A DK GRAY: 1.8: COMP A

MSDS Date:12/20/1994

FSC:8010

NIIN:01-350-4744

Kit Part:Y

MSDS Number: BXHDK

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377

Emergency P

hone Num:219-236-5856

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:TALC

CAS:14807-96-6

RTECS #:MW2700000

Fraction by Wt: 35%

Other REC Limits:NONE RECOMMENDED

Ingred Name:BUTYL ALCOHOL (SARA 313) (CERCLA) (VAPOR PRESSURE 4.4 MM HG

@ 20C)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 30%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:POLYAMIDE/EPOXY ADDUCT
Fraction by Wt: 20%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMIDOAMINE RESIN
CAS:68443-08-3
Fraction by Wt: 1%
Other REC Limits:NONE RECOMMENDED

Ingred Name:XYLENE (SARA 313) (CERCLA) (VAPOR PRESSURE 7.0 MM HG @
20C)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 1%
Other REC Limits
:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM;STEL 150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOC: 3.50 LBS/GAL
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:79.0F,26.1C
Lower Limits:1.0
Upper Limits:11.0
Extinguishing Media:DRY CHEMICAL, FOAM, CO2
Fire Fighting Procedures:WEAR SCBA W/FULL FACPIECE (POSITIVE PRESSURE
MODE) & FULL PROTECT CLOTH. USE WATER

TO COOL CLOSED CNTNR TO
PREVENT PRESSURE BLDUP/AUTO IGNIT/EXPLOSION W/HEAT.
Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD.VAPOR HEAVY,TRAVEL ON
GRND TO IGNIT.KEEP FROM HEAT/IGNIT.CLSD CNTNR EXPLODE W/HEAT.APPLIC
TO HOT SRFCS REQ SPCL CAUTN.DECOMP PRODUCT-HEALTH HZD.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:242 TO 325F
Vapor Density:> AIR
Spec Gravity:1.307
Viscosity:99 - 108 KU
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:SLIGHT
Appearance and Odor:LIQUID, ODOR OF SOLVENTS
Percent Volatiles by Volume:51.90
Corrosion Rate:MINIMAL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
WILL SOFTEN POLYETHYLENE, POLYPROPYLENE, PVC CONTAINERS, OXIDIZERS.
Stability Condition to Avoid:HIGH TEMPERATURES

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.