

LOCTITE CORP -- LOCQUIC PRIMER GRADE N, 76471, 764 -- 8030-00-935-5816

=====  
Product Identification  
=====

Product ID:LOCQUIC PRIMER GRADE N, 76471, 764

MSDS Date:01/01/1993

FSC:8030

NIIN:00-935-5816

MSDS Number: BXJVP

=== Responsible Party ===

Company Name:LOCTITE CORP

Address:705 N MOUNTAIN RD

City:NEWINGTON

State:CT

ZIP:06111

Country:US

Info Phone Num:203-278-1280

Emergency Phone Num:203-278-12

80

CAGE:7K128

=== Contractor Identification ===

Company Name:LOCTITE CORP

Address:705 N MT RD

City:NEWINGTON

State:CT

ZIP:06111

Country:US

Phone:312-689-6200

CAGE:7K128

Company Name:LOCTITE CORPORATION

Address:1001 TROUT BROOK CROSSING

Box:City:ROCKY HILL

State:CT

ZIP:06067-3910

Country:US

Phone:860-571-5100

CAGE:05972

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHANE, 1,1,1,-TRICHLORO-; (SARA 313) (CERCLA). LEL: 7%.

UEL: 15%.

CAS:71-55-6

RTECS #:KJ2

975000  
Fraction by Wt: 95-100%  
OSHA PEL:350 PPM  
ACGIH TLV:350 PPM; 450 STEL  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS  
Ozone Depleting Chemical:1

Ingred Name:TERT-BUTYL ALCOHOL (SARA 313). LEL: 2.4%. UEL: 8%.  
CAS:75-65-0  
RTECS #:EO1925000  
Fraction by Wt: 1-3%  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM

Ingred Name:METHANE, DIMETHOXY-; LEL: 2.2%. UEL: 13.1%.  
CAS:109-87-5  
RTECS #:PA8750000  
Fraction by Wt: 1-3%  
OSHA PEL:1000 PPM  
ACGIH TLV:1000 PPM

Ingred Name:HEXANOIC ACID, 2-ETHYL-; (2-ETHYLHEXANOIC AC  
ID). LEL: 1%.  
UEL: 6.2%.  
CAS:149-57-5  
RTECS #:MO7700000  
Fraction by Wt: 0.1-1%  
OSHA PEL:N/K  
ACGIH TLV:N/K

Ingred Name:HEXANOIC ACID, 2-ETHYL-, COPPER SALT; (ORGANO-COPPER  
COMPOUND)  
CAS:22221-10-9  
RTECS #:MO7708000  
Fraction by Wt: 0.1-1%  
OSHA PEL:N/K  
ACGIH TLV:N/K

Ingred Name:TRIALKYLAMMONIUM CARBOXYLATE  
CAS:58823-74-8  
Fraction by Wt: 0.1-1%  
OSHA PEL:N/K  
ACGIH TLV:N/K

Ingred Name:VOLATILE ORGANIC COMPOUND: 4.03%; 67.98 G/L OF MATL; 98.5%;  
1283 G/L LESS EXEMPT CMPDS & EXEMPT

CMPDS INCLUDED  
RTECS #:9999999VO  
OSHA PEL:N/K  
ACGIH TLV:N/K

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:CHLOROCARBON MATERIALS HAVE PRODUCED  
SENSITIZATION OF THE MYOCARDIUM TO EPINEPHRINE IN LAB ANIMALS &  
COULD HAVE A SIMILAR EFFECT IN HUMANS. ADRENOMIMETICS (EG,  
E  
PINEPHRINE) MAY BE CONTRA-INDICATED EXC EPT FOR LIFE-SUSTAINING  
USES IN HUMANS ACUTELY/CHRONICALLY EXPOSED TO CHLOROCARBONS . (EFTS  
OF OVEREXP)  
Explanation of Carcinogenicity:NOT RELEVANT  
Effects of Overexposure:HLTH HAZ: POSSIBLE EYE IRRITANT. MODERATELY  
TOXIC BY INGESTION. HEADACHE, NAUSEA, DIZZINESS. NARCOSIS AT HIGH  
CONCENTRATION.  
Medical Cond Aggravated by Exposure:1,1,1-TRICHLOROETHANE: CNS, LIVER,  
HEART DISEASE, ALCOHOLISM, SKIN DISORDERS, EYE & RESPIRATORY  
PROBLEM  
S. 2-ETHYLHEXANOIC ACID: DERMATITIS.

=====  
===== First Aid Measures =====

First Aid:INGESTION: DO NOT INDUCE VOMITING. KEEP INDIVIDUAL CALM.  
OBTAIN MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF  
SYMPTOMS PERSIST, OBTAIN MEDICAL ATTENTION. SKIN: WASH WITH SOAP &  
WATER. EYES: F LUSH AT LEAST 15 MINUTES WITH WATER. OBTAIN MEDICAL  
ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Po  
int:NONE  
Lower Limits:SEE INGS  
Upper Limits:SEE INGS  
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED PRESSURE DEMAND SCBA  
AND FULL PROTECTIVE EQUIPMENT .  
Unusual Fire/Explosion Hazard:THERMAL DECOMPOSITION PRODUCTS MAY  
INCLUDE HCL AND PHOSGENE .

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ALLOW TO EVAPORATE WITH GOOD VENTILATION. SOAK  
UP RESIDUE IN AN INERT ABSORBENT. STORE IN

A CLOSED CONTAINER UNTIL  
DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 110F TO PROLONG SHELF  
LIFE. AVOID PROLONGED BREATHING OF VAPOR.

Other Precautions:NO SMOKING IN AREA OF USE. DO NOT USE IN THE GENERAL  
VICINITY OF ARC WELDING, OPEN FLAMES OR HOT SURFACES. HEAT AND/OR  
UV RADIATION MAY CAUSE THE FORMATION OF HCL AND/OR PHOSGENE .

=====  
===== Exp  
posure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR  
EXPOSURE OF CONCERN .

Ventilation:PROVIDE ADEQUATE VENTILATION TO MAINTAIN VAPOR  
CONCENTRATION BELOW TLV.

Protective Gloves:RUBBER OR PLASTIC GLOVES.

Eye Protection:ANSI APPRVD SAFETY GLASSES .

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health  
NONE SPECIFIED BY MANUFACTURER.

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:170F,77C

Vapor Pres: