View NSN Online: https://aerobasegroup.kr/nsn/6850-01-013-9937

ITW DEVCON/ A DYKEM COMPANY -- TOLE RED DX-296,B-I-C-81496 -- 6850-01-013-9937

Product ID:TOLE RED DX-296,B-I-C-81496

MSDS Date:06/01/1994

FSC:6850

NIIN:01-013-9937

MSDS Number: BXPVM === Responsible Party ===

Company Name: ITW DEVCON/ A DYKEM COMPANY

Address:8501 DELPORT DRIVE

City:ST. LOUIS

State:MO ZIP:63114 Country:US

Info Phone Num:314-423-0100/800-443-9536

F

mergency Phone Num:800-443-9536/800-424-9300(CHEMTREC)

Preparer's Name: JAMES A SEPER

CAGE:98148

=== Contractor Identification ===

Company Name: ITW DYKEM/ DYMON

Address:805 E OLD 56 HWY

Box:City:OLATHE

State:KS ZIP:66061 Country:US

Phone:800-443-9536

CAGE:98148

======= Composition/Information on Ingredients ========

Ingred Name: ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000 Fraction by Wt: 31 - 50%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9495

Ingred Name: N-BUTYL ACETATE (CERCLA)

CAS:123-86-4

RTECS #:AF7350000 Fraction by Wt: 31 - 50%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:150 PPM

ACGIH TLV:150 PPM/200STEL;9495

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ISOPROPYL ALCOHOL (SARA 313)

CAS:67-63-0

RTECS #:NT8050000 Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:400 PPM/500STEL;9495

Ingred Name: COLLODION (WET NITROCELLULOSE)

CAS:9004-70-0

RTECS #:QW0970000 Fraction by Wt: 1 - 5%

Other

REC Limits: NONE RECOMMENDED

Ingred Name:N-BUTYL ALCOHOL (SARA 313) (CERCLA)

CAS:71-36-3

RTECS #:EO1400000 Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9495

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:DIACETONE ALCOHOL (4-HYDROXY-4-METHYL-2-PENTANONE)

CAS:123-42-2

RTECS #:SA9100000 Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:50 PPM; 9495

Ingred Name: N-PROPYL ACETATE

CAS:109-60-4 RTECS #:AJ36750 00

Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM/250STEL;9495

Ingred Name: SOLVENT RED 125 (COBALT COMPOUND)

Fraction by Wt: 1 - 5%

Other REC Limits: NONE RECOMMENDED

Ingred Name: POLYAMIDE RESIN

CAS:68410-23-1

Other REC Limits: NONE RECOMMENDED

Ingred Name: CASTOR OIL

CAS:8001-79-4 RTECS #:FI4100000

Other REC Limits: NONE RECOMMENDED

Ingred Name: VOLITILE ORGANIC CONTENT AS LISTED ON MSDS: 6.46 LBS/GAL.

RTECS #:9999999VC

Other REC Limits: NONE RECOMMEND

ED

OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

============ Hazards Identification =========================

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, CNS,

RESPIRATORY & GI TRACTS. ACUTE- MAY CAUSE EYE & SKIN IRRITATION. INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION, CNS EFFECTS. MAY BE ABSORBED THROU

GH SKIN. CAN CAUSE G I TRACT IRRITATION.

ASPIRATION HAZARD. CHRONIC- SKIN SENSITIZATION OR DERMATITIS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, IRRITATION, REDNESS AND ITCHING OR BURNING SENSATION OF EYES OR SKIN, ABDOMINAL PAIN, WEAKNESS, CONFUSION

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED CNS OR RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PROD

UCT.
======================================
First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT IN DUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET MEDICAL ATTENTION IMMEDIATELY.
======================================
Flash Point Method:CC Flash Point:53.0F,11.7C Lower Limits:1.38 Upper Limits:12 Extinguishing Media:FOAM, DRY CHEMICAL/CARBON DIOXIDE. DON'T USE WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED. Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL CONSIDERABLE DISTANC E OR BE MOVED BY VENTILATION TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINER MAY EXPLODE.
========= Accidental Release Measures ===========
Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH. PREVENT LIQUID FROM ENTERING SEWERS. Neutralizing Agent:NOT RELEVANT
============= Handling and Storage ==============
Handling and Storage Pre cautions:STORE IN COOL, VENTILATED AREA, AWAY FROM SOURCES OF IGNITION & INCOMPATIBLE MATERIALS. KEEP OUT OF REACH OF CHILDREN. Other Precautions:HIGHLY FLAMMABLE. AVOID BREATHING VAPORS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND

BEFORE EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. LAUNDER BEFOR E REUSE.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: NONE REQUIRED WHERE ADEQUATE VE

NTILATION CONDITIONS EXIST. IF AIRBORNE CONCENTRATION IS HIGH, WEAR A NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR. Ventilation: MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S). Protective Gloves: NEOPRENE, NITRILE, POLYVINYL CHLORIDE Eye Protection: SAFETY GOGGLES WITH OPTIONAL FACE SHIELD Other Protective Equipment: EYE WASH STATION, SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING, APRON AND BARRIER CREAM FOR EXPOSED SKIN Work Hy gienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR. Supplemental Safety and Health FORMULA CHANGED. FOR PREVIOUS FORMULATIONS, SEE PNI A AND B, SAME NSN. ======== Physical/Chemical Properties ============ HCC:F2 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:163F - 275F Vapor Density:>1 Spec Gravity:0.84 Evaporation Rate & Evaporation R Solubility in Water:APPRE CIABLE Appearance and Odor: RED TRANSPARENT LOW VISCOUSITY LIQUID WITH SWEET **SOLVENT ODOR** ======== Stability and Reactivity Data =========== Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid: HEAT, SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, AND

SMOKE

======== Disposal Considerations =============

Waste Disposal Methods:DISPOSE

OF IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. INCINERATE IN
APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.