

FORD MOTOR CO; PARTS & SERVICE DIV, GOVNMNT SALES -- MOTORCRAFT - U.S XT-1-QF --
9150-01-092-9755

===== Product Identification =====

Product ID:MOTORCRAFT - U.S XT-1-QF

MSDS Date:11/23/1988

FSC:9150

NIIN:01-092-9755

MSDS Number: BXSCZ

=== Responsible Party ===

Company Name:FORD MOTOR CO; PARTS & SERVICE DIV, GOVNMNT SALES

Address:3000 SCHAEFER ROAD

Box:1902

City:DEARBORN

State:MI

ZIP:48121

Country:

US

Info Phone Num:313-337-3182 OR 313-323-0045

Emergency Phone Num:313-337-3182 OR 313-323-0045

CAGE:EO208

=== Contractor Identification ===

Company Name:COLONIAL TRUCK SALES INC

Address:1833 COMMERCE RD

Box:City:RICHMOND

State:VA

ZIP:23224-7801

Country:US

Phone:804-232-3492

CAGE:5A850

Company Name:FORD MOTOR CO, GOVERNMENT PART SALES

Address:3000 SCHAEFER ROAD

Box:1902

City:DEARBORN

State:MI

ZIP:48121

Country:US

Phone:313-323-0045

CAGE:23040

Company Name:FORD MOTOR CO; PARTS & SERVICE DIV, GOVN

MT SALES
Address:3000 SCHAEFER ROAD
Box:1902
City:DEARBORN
State:MI
ZIP:48121
Country:US
Phone:800-959-3673
CAGE:EO208

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY
PARAFFINIC
CAS:64742-65-0
RTECS #:PY8038500
Fraction by Wt: >60%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:5 MG/M3 (OIL MIST)

=====
Hazards Identification
=====

LD50 LC50 Mixture:OSHA EXPOSURE LIMIT O
F 5 MG/M3, OIL MIST
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EXPOSURE TO OIL MIST/FUME/VAPOR MAY
CAUSE RESPIRATORY TRACT IRRITATION. THIS PRODUCT MAY CAUSE CARDIAC
SENSITIZATION. PROLONGED AND/OR REPEATED SKIN CONTACT WITH THIS
PRODUCT MAY CAUSE IRRITATION/DERM ATITIS. THIS PRODUCT MAY CAUSE
IRRITATION TO THE EYES AND RESPIRATORY SYSTEM.
Explanation of Carcinogenicity:PRODUCT CONT
AINS NO INGREDIENTS
CURRENTLY CLASSIFIED BY NTP, IARC OR OSHA AS CARCINOGENIC.
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NONE KNOWN.

=====
First Aid Measures
=====

First Aid:NONE SPECIFIED BY MANUFACTURER.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:>345F,>174C
Extinguishing Media:DRY CHEMICAL, FOAM OR CARBON DIOXIDE.
Fire Fighting Procedures

:WATER OR FOAM MAY CAUSE FROTHING IF THE PRODUCT IS HEATED ABOVE 93C. USE WATER TO COOL FIRE EXPOSED CONTAINERS AND TO PROTECT PERSONNEL.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:DO NOT ALLOW THIS MATERIAL TO DRAIN INTO SEWERS/WATER SUPPLIES. ABSORB THE SPILLED MATERIAL WITH AN INERT MABSORBENT ATERIAL. USE SAND, PERLITE OR VERMICULITE AS ABSORBENT FOR LARGE SPI
LLS OF THIS MAT ERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP THIS MATERIAL IN A COOL WELL-VENTILATED PLACE. AVOID PROLONGED OR REPEATED CONTACT WITH THIS MATERIAL. AVOID THE GENERATION OF MISTS.

Other Precautions:AVOID GETTING THIS MATERIAL INTO CONTACT WITH YOUR EYES. USE THIS PRODUCT WITH ADEQUATE VENTILATION. THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NECESSARY.

Ventilation:LOCAL EXHAUST IS SUGGESTED FOR USE, WHERE POSSIBLE, IN ENCLOSED OR CONFINED SPACES.

Protective Gloves:WEAR IMPERVIOUS GLOVES.

Eye Protection:WEAR SAFETY GLASSES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

FOR EMERGENCY CALL: (313) 337-3182 OR (313) 323-0045 (FOR 24 HOUR SERVICE)

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>601F,>316C

Spec Gravity:0.870

Solubility in Water:INSOLUBLE

Appearance and Odor:LIQUID.

===== Stability and Reactivity Data =====

THIS PRODUCT MAY REACT WITH OXIDIZING AGENTS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:UPON DECOMPOSITION, THIS PRODUCT EMITS CARBON MONOXIDE, CARBON DIOXIDE AND/OR LOW MOLECULAR WEIGHT HYDROCARBONS.

=

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF WASTE MATERIAL ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS. SURFACES MAY BECOME SLIPPERY AFTER SPILLAGE. AVOID SKIN CONTACT WITH THE SPILLED MATERIAL. REMOVE SOIL SOAKED CLOTHING AND LAUNDRER BEFORE REUSE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.