View NSN Online: https://aerobasegroup.kr/nsn/5330-00-527-9898

Product ID:COMPRESSED RUBBER-BONDED ASBESTOS GASKET SHEET, S 76 MSDS Date:02/01/1991 FSC:5330 NIIN:00-527-9898 MSDS Number: BXTMQ === Responsible Party === Company Name: GERARD PACKING AND BELTING CORP Address:24 MIDLAND AVENUE City:HICKSVILLE State:NY ZIP:118 01 Country:US Info Phone Num:516-935-2400 Emergency Phone Num:516-935-2400 CAGE:2G277 === Contractor Identification === Company Name: GERARD PACKING AND BELTING CORP Address:24 MIDLAND AVENUE Box:City:HICKSVILLE State:NY ZIP:11801 Country:US Phone:516-935-2400 CAGE:2G277 Ingred Name: ASBESTOS, CHRYSOTILE CAS:12001-29-5

CAS:12001-29-5 RTECS #:CI6478500 Fraction by Wt: 60 - 90% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.2 FIBERS/CC ACGIH TLV:

2 FIBERS/CC,A1; 9495

Ingred Name:RUBBER BINDER (NEOPRENE) Fraction by Wt: TLV.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: IF TLV IS EXCEEDED OR FOR SYMPTOMS OF OVER EXPOSURE, WEAR NIOSH-APPROVED RESPIRATOR FOR DUST OR AIR-PURIFYING RESPIRATOR. IN EMERGENCY, WEAR A NIOSH-APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS. Ventilation: USE GENERAL OR LOCAL EXHAUST VENTILATION TO MEET TLV

REQUIREMENTS.

Protective Gloves:L

ATEX OR RUBBER RECOMMENDED

Eye Protection:GOGGLES

Other Protective Equipment: EYE WASH STATION; FULL BODY PROTECTION IF ABOVE TLV

Work Hygienic Practices: OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

NOTE: THE ASBESTOS AND OTHER FIBERS CONTAINED IN THIS MATERIAL ARE BONDED WITH A VULCANIZED RUBBER MATRIX. AIRBORNE ASBESTOS HAZARDS ARE ELIMINATED IF THE COMPOSITE STRUCTURE REMAINS INTACT. IF MATERI AL IS TO BE CUT OR DRILLE

D, USE ADEQUATE EXHAUST VENTILATION AND WEAR RESPIRATORY PROTECTION.

HCC:N1

NRC/State Lic Num:NOT RELEVANT Spec Gravity:1.8 - 2.2 Viscosity:NOT RELEVANT Evaporation Rate & amp; Reference:NOT RELEVANT Solubility in Water:INSOLUBLE Appearance and Odor:BLACK OR WHITE SHEET MATERIAL - ODORLESS

Stability Indicator/Materials to Avoid:YES Stability Condition to

Avoid:CREATION OF DUST OR ASBESTOS FIBERS. Hazardous Decomposition Products:EMITS TOXIC RUBBER COMBUSTION PRODUCTS. ASBESTOS FIBERS MAY BE RELEASED.

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. BURY WASTE IN SOLID LANDFILL IF PERMITTED. WASTE SHOULD BE IN SEALED CONTAINER, MARKED WITH WARNING LABEL. MAY BE INCINERATED. OBSERVE ALL LOC AL, STATE AND FEDERAL REGULATIONS.

Dis

claimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.