

AMERICAN BRAIDING AND MFG CORP -- COMPRESSED RUBBER BONDES STYLE 153 ASBESTOS  
-- 5330-00-023-7626

===== Product Identification =====

Product ID:COMPRESSED RUBBER BONDES STYLE 153 ASBESTOS

MSDS Date:10/03/1995

FSC:5330

NIIN:00-023-7626

MSDS Number: BXYCG

=== Responsible Party ===

Company Name:AMERICAN BRAIDING AND MFG CORP

Address:247 OLD TAVERN ROAD

City:HOWELL

State:NJ

ZIP:07731

Country:US

Info P

hone Num:908-938-6333 ...FAX 6377

Emergency Phone Num:908-938-6333 ...FAX 6377

CAGE:4R345

=== Contractor Identification ===

Company Name:AMERICAN BRAIDING AND MFG CORP

Address:247 OLD TAVERN ROAD

Box:City:HOWELL

State:NJ

ZIP:07731

Country:US

Phone:732-938-6333 ...FAX 6377

CAGE:4R345

===== Composition/Information on Ingredients =====

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 0.5-1.5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:3.5 MG/M3

ACGI

H TLV:3.5 MG/M3; 9495

Ingred Name:ASBESTOS (FRIABLE) (SARA 313) (CERCLA) (CHRYSOTILE ASBESTOS)

CAS:1332-21-4

RTECS #:CI6425000

Fraction by Wt: 70-90%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:0.2 FIBER/CC,A1;9495

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:BUTADIENE-STYRENE POLYMER (RUBBER)

CAS:9003-55-8

RTECS #:WL6478000

Fraction by Wt: 8-15%

Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry:

Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:THE MATERIAL IN FINISHED FORM PRESENTS NO KNOWN HEALTH HAZARD. A CHRONIC HEALTH HAZ MAY BE CREATED IF FURTHER PROCESSING OF THE SHEET ALLOWS ASBESTOS FIBERS TO BE RELEASED INTO THE ATMOSPHER. INHAL OF FREE ASBESTOS FIBERS CAN CAUSE LUNG DISORDER INCLUDING ASBESTOSIS, PLEURAL PLAQUE, LUNG CANCER, & MESOTHELIOMA.

Explanation of Carcinogenicity:CONTAIN

S A [1332-21-4] WHICH IS

LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.

Effects of Overexposure:SEE SECTION OF MSDS ON HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:NONE SPECIFIED BY MANUFACTURER. HOWEVER FOLLOW PROPER FIRST AID FROM THE AMERICAN RED CROSS; ADDITIONALLY SEEK PROFESSIONAL MEDICAL HELP.

=====  
===== Fire Fighting Measures ==

=====  
Extinguishing Media:WATER, CARBON DIOXIDE, DRY POWDER OF FOAM.  
Fire Fighting Procedures:FIREFIGHTERS SHOULD USE SELF-CONTAINED  
BREATHING EQPMT & EYE PROTECTION FOR THE RUBBER FUMES.  
Unusual Fire/Explosion Hazard:THE RUBBER, ONCE IGNITED, MAY NEED EXTRA  
COLLING TO PREVENT REIGNITION.

=====  
Accidental Release Measures

Spill Release Procedures:DUST FROM SHEET SHOULD BE TREATED AS FREE  
ASBESTOS. SECURE AREA & CLEAN UP USING HEPA FI  
LTERED VACUUM, OR WET  
SWEEP. DO NOT CLEAN UP IN A METHOD THAT GENERATES DUST INTO  
ATMOSPHERE.

=====  
Handling and Storage

Handling and Storage Precautions:MATL MUST NOT BE  
DRILLED/SAWED/GROUND/SANDED/SUGJ TO ANY OTHER DUST PRODUCING  
PROCESS W/O NECESSARY EQMPT TO ENSURE CONTAIN.  
Other Precautions:IN MFG OF COMPRESSED ASBESTOS SHEET PACKING ASBESTOS  
IS ENCAPSULATED INTO SHEET BY RUBBER MATRIX.IN NORMAL HNDLG OF  
SHEET/CUT GASKETS NO  
SIGNIFICANT RELEASE OF ASBESTOS DUST  
OCCURS.CHRYSOTILE ASBESTOS :2 FIBERS/CC >5UM IN LENGTH.

=====  
Exposure Controls/Personal Protection

Respiratory Protection:USE RESPIRATOR APPROVED PURUSANT TO 29 CFR  
1910.1001 (D) (2).  
Ventilation:IN PRODUCTION OF GASKETS;LOCAL AIR FILTRATION & GOOD  
HYGIENE MUST BE USED.  
Protective Gloves:NONE SPECIFIED BY MANUFACTURER.  
Eye Protection:NONE REQUIRED FOR NORMAL USE.  
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER  
.  
Work Hygienic Practices:WHERE APPLICABLE WETTING DOWN SHOULD BE USED TO  
ENSURE NEGLIGIBLE ASBESTOS DUST RELEASE.  
Supplemental Safety and Health

=====  
Physical/Chemical Properties

HCC:Z1  
Boiling Pt:B.P. Text:DECOMPOSES  
Spec Gravity:0.65-1.85  
Solubility in Water:INSOLUBLE  
Appearance and Odor:BLACK WITH WHITE SPOTS.

=====  
Stability and Reactivity Data

STRONG OXIDIZERS, STRONG ACIDS, OR BASES.  
Stability Condition to Avoid:TH

E MATERIAL HAS INFINITE STORAGE  
STABILITY.

Hazardous Decomposition Products: BURNING RUBBER & FREE ASBESTOS.

===== Disposal Considerations =====

Waste Disposal Methods: BURY IN SOLID LANDFILL AS REQUIRED BY 29 CFR  
1910.1001 (N)(2).

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.