View NSN Online: https://aerobasegroup.kr/nsn/5640-00-272-2995

RAMCO INSULATION, INC -- SUPERTEMP/RAMCOTE 1200 -- 5640-00-272-2995

Product ID:SUPERTEMP/RAMCOTE 1200 MSDS Date:08/15/1994 FSC:5640 NIIN:00-272-2995 **MSDS Number: BXYSH** === Responsible Party === Company Name: RAMCO INSULATION, INC Address:2021 ROOSEVELT Box:2173 City: JOPLIN State:MO ZIP:64803 Country:US Info Phone Num:417-781-8855 Emergency Phone Num:417-781-8855 Ρ reparer's Name: RICHARD MOSS CAGE:UO335 === Contractor Identification === **Company Name: RAMCO INSULATION INC** Address:2021 ROOSEVELT Box:2173 City: JOPLIN State:MI ZIP:64804 Country:US Phone:417-781-8855 CAGE:UO335

Ingred Name:MINERAL FIBERS Other REC Limits:NONE RECOMMENDED

Ingred Name:BENTONITE CAS:1302-78-9 RTECS #:CT9450000 Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 (DUST) ACGIH TLV:5 MG/M3 (DUST)

Ingred Name:CLAY C

AS:1332-58-7 Other REC Limits:NONE RECOMMENDED
Ingred Name:PORTLAND CEMENT Other REC Limits:NONE RECOMMENDED
Ingred Name:FLY ASH Other REC Limits:NONE RECOMMENDED
======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO Health Hazards Acute and Chronic:ACUTE: EYES-IRRITATION. SKIN-IRRITATION. INHALATION-RESPIRATORY IRRITATION. INGESTION-UNKNOWN. CHRONIC: INHALAYI ON-LUNG DAMAGE IF INHALED OVER LONG TERM BASIS. Explanation of Carcinogenicity:IARC HAS CLASSIFIED CRYSTALLINE SILICA AS A CLASS 2A CARCINOGEN. Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================
 First Aid:EYES-FLUSH WITH CLEAN WATER FOR 15 MINUTES. CONSULT PHYSICIAN IF IRRITATION PERSISTS. SKIN-WASH WITH CLEAN WATER AND SOAP. CONSULT PHYS ICIAN IF IRRITATION PERSISTS. INHALATION-REMOVE TO ADEQUATE VENTI LATION. SEEK MEDICAL ATTENTION. INGESTION-CONTACT PHYSICIAN. DO NOT INDUCE VOMITING.
======================================
Flash Point:NONE Extinguishing Media:NOT COMBUSTIBLE. Unusual Fire/Explosion Hazard:NONE KNOWN.
======================================
Spill Release Procedures:SWEEP OR VACUUM.

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER. Other Precautions:USE A NIOSH APPROVED RESPIRATOR WHEN WORKING WITH THIS PRODUCT.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: A NIOSH APPROVED RESPIRATOR FOR MINERAL DUSTS SHOULD BE USED AT ALL TIMES WHEN WORKING WITH THIS PRODUCT. EMPLOYEES USING A RESPIRATOR MUST BE FIT TESTED, USING OSHA QUALITATIVE FIT TESTING REQUIREMEN TS. Ventilation: GENERAL MECHANICAL VENTILATION IS ADEUQATE. Protective Gloves: NONE SPECIFIED BY MANUFACTURER. Eye Protection: GOGGLES OR SAFETY GLASSES W/SHIELDS. Other Protective Equipment: LONG-SLEEVED AND LONG-LEGGED CLOTHING SHOULD BE WORN TO PREVENT SKIN CONTACT. Work Hygienic Practices: WORK CLOTHING SHOULD BE WASHED SEPERATELY. RINSE WASHING MACHINE THOROUGHLY AFTER USE. Supplemental Safety and Health WARNING: THIS PRODUCT CONTAINS SILICA. HCC:N1 Μ elt/Freeze Pt:M.P/F.P Text:2200F,1204C Solubility in Water:TRACE. Appearance and Odor:LIGHT GRAY - CEMENT ODOR. Percent Volatiles by Volume:NONE Stability Indicator/Materials to Avoid:YES STRONG ACIDS. Stability Condition to Avoid:STABLE. Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods:LANDFILL, IN ACCORDANCE WITH STAT

E AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informatio n to their

particular situation.