

EXXON CO USA, A DIV OF EXXON CORP. -- EXXON OFF ROAD DIESEL 2; PRODUCT CODE  
072700-00787 -- 9140-00-286-5294

=====  
Product Identification  
=====

Product ID:EXXON OFF ROAD DIESEL 2; PRODUCT CODE 072700-00787

MSDS Date:01/17/1995

FSC:9140

NIIN:00-286-5294

MSDS Number: BXYSL

=== Responsible Party ===

Company Name:EXXON CO USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZI

P:77252-2180

Country:US

Info Phone Num:713-656-2443

Emergency Phone Num:713-656-3424

CAGE:29700

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM MID-DISTILLATE, FUEL, DIESEL, NO. 2

CAS:68476-34-6

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH

TLV:5 MG/M3 AS OIL MIST

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:140F,60C

Autoignition Temp:Autoignition Temp Text:>204C

Lower Limits:0.9%

Upper Limits:7%

Extinguishing Media:USE DRY CHEMICAL, FOAM OR CARBON DIOXIDE TO EXTINGUISH FIRE. WATER MAY BE INEFFECTIVE. USE WATER TO COOL CONTAINERS

Fire Fighting Procedures:IF SPILL/LEAK HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE VAPORS & PROTECT MEN ATTEMPTING TO STOP LEAK. WATER

SPRAY MAY BE USED TO FLUSH SPILL AWAY.

Unusual Fire/Explosion Hazard:MINIMIZE BREATHING OF GASES, VAPORS, FUMES OR DECOMPOSITION PRODUCTS. USE SUPPLIED-AIR BREATHING EQUIPMENT FOR ENCLOSED/CONFINED SPACES OR AS OTHERWISE NEEDED.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:160-350C

Melt/Freeze Pt:M.P/F.P Text:-0F,-18C

Vapor Pre

s:5

Spec Gravity:0.86

pH:7

Viscosity:2.7 CST

Evaporation Rate & Reference:0.02 (N-BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE;