

NILES CHEMICAL PAINT CO. -- N-1301A AIRCRAFT RED 31136 -- 8010-01-144-9884

=====
Product Identification
=====

Product ID:N-1301A AIRCRAFT RED 31136
MSDS Date:05/25/1995
FSC:8010
NIIN:01-144-9884
Kit Part:Y
MSDS Number: BYCNM
=== Responsible Party ===
Company Name:NILES CHEMICAL PAINT CO.
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Info Phone Num:616-683-3377
Emergency
Phone Num:219-236-5856
Preparer's Name:MIKE LICHATOWICH
CAGE:02388

=== Contractor Identification ===
Company Name:NILES CHEMICAL PAINT
Address:225 FORT STREET
Box:307
City:NILES
State:MI
ZIP:49120
Country:US
Phone:616-683-3377/219-236-5856
CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:DIATOMACEOUS SILICA
CAS:14464-46-1
Fraction by Wt: 25%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:0.08 MG/M3

Ingred Name:METHYL ETHYL KETONE (VP =

71.2 MM @ 20C)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 16%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/STEL 300 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:POLYESTER RESIN
Fraction by Wt: 13%
Other REC Limits:NONE RECOMMENDED

Ingred Name:BARIUM SULFATE
CAS:7727-43-7
RTECS #:CR0600000
Fraction by Wt: 12%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:NOT EST.

Ingred Name:PM ACETATE (VP = 3.7 MM @ 20C)
CAS:108-65-6
RTECS #:AI8925000
F
raction by Wt: 12%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:NOT EST.

Ingred Name:BUTYL ACETATE (VP = 10.0 MM @ 20C)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:150 PPM
ACGIH TLV:150 PPM/STEL 200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (VP = 7.0 MM @ 20C)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/STEL 150 PPM
EPA Rpt Qty:10

00 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PROPRIETARY INGREDIENTS (NON HAZ.)
Fraction by Wt: BALANCE
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EYES: SEVERE IRRITATION,
LACRIMATION, REDNESS, BLURRED VISION. SKIN: REDNESS, IRRITATION,
DEF
ATTING LEADING TO DERMATITIS. BREATHING: NASAL & RESPIRATORY
IRRITATION, CNS DEPRESSION, ASPHYXIATIO N. INGESTION:
GASTROINTESTINAL IRRITATION. CHRONIC: HISTOLOGIC FIBROSIS OF LUNGS,
NARCOSIS, COMA.
Explanation of Carcinogenicity:NOT LISTED BY NTP, IARC OR OSHA.
Effects of Overexposure:BREATHING: DIZZINESS, DROWSINESS, WEAKNESS,
FATIGUE, CONFUSION, NAUSEA, HEADACHE, VERTIGO, POSSIBLE
UNCONSCIOUSNESS. INGESTION: ABDOMINAL PAIN, NAUSEA, VOMITING,
DIARRHEA.
Medical Cond Aggr
avated by Exposure:NK. TARGET ORGANS: RESPIRATORY
SYSTEM, CNS, LUNGS, EYES, SKIN.

===== First Aid Measures =====

First Aid:INHAL: GET FRESH AIR. IF BREATHING STOPPED, START ARTIF RESP.
GET MED AID. SKIN: IMMEDIATELY FLUSH W/WATER. IF MAT'L PENETRATES
CLOTHING, REMOVE CONTAM CLOTHING, FLUSH SKIN W/WATER. GET MED AID.
EYES: IMMED FLUSH W/LRG AMT WATER 15 MIN, LIFTING EYELIDS. GET MED
AID IMMED. INGESTION: DRINK 1-2 GLASSES WATER. DON'T I
NDUCE
VOMITING. CONSULT PHYSICIAN/POISON CONTROL CENTER IMMED. TREAT
SYMPTOMATICALLY

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:20.0F,-6.7C
Lower Limits:1.0
Upper Limits:10.0
Extinguishing Media:DRY CHEMICAL, FOAM, CO2.
Fire Fighting Procedures:WEAR POS PRESS SCBA W/FULL FACEPIECE & FULL
PROTECTIVE CLOTHING. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO
PREVENT PRESS BLD UP & AUTOIGNIT/EXPLOS.
Unusual Fire/Explosion

Hazard:VAPOR HEAVIER THAN AIR, TRAVEL TO IGNIT
SOURCE. ISOLATE FROM IGNIT SOURCE. CLSD CNTNR EXPLODE W/HEAT.
APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.*

===== Accidental Release Measures =====

Spill Release Procedures:NO IGNIT SOURCES. MINIMIZE BREATHING VAPORS.
AVOID SKIN CONTACT. SM: ABSORB W/INERT MAT'L (CLAY, SOIL, COMMERC
ABSORB) SHOVEL RECLAIMED LIQ & ABSORB INTO RECOVERY/SALVAGE DRUMS.
LG: DIKE (NO FURTHER M OVENT) & RECLAIM
INTO SALVAGE DRUMS/TANK
TRUCK.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID STORAGE IN HIGH TEMP AREAS OR
NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN
USE. AVOID ROUGH HANDLING.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN
EMPTY. DO NOT WELD OR FLAME CUT ON EMPTY DRUMS. DO NOT WEAR CONTACT
LENSES WHEN WORKING W/THIS MATERIAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR APPROP (TC-23C-75) FITTED HALF-MASK FOR
FULL FACEPIECE RESPIRATOR (NIOSH/MSHA) DURING/AFTER APPLICATION
UNLESS AIR MONITERING DEMONSTRATES VAPOR/MIST LEVELS BELOW TLV.
FOLLOW RESPIRATOR MFR DIRECTIONS FOR USE.

Ventilation:PROVIDE SUFFICIENT VENTILATION (VOLUME/PATTERN) TO KEEP AIR
CONC BELOW TLV PEL. REMOVE DECOMP PROD. VENT VAPOR EMITTED.

Protective Gloves:CHEM RESISTANT, NITRILE OR VITON

Eye Protection:CHEM GOGGLES/SAFETY
GLASSES/FACE SHIELDS

Work Hygienic Practices:WASH ANY CONTAM CLOTHING OR CLOTH THAT BECOMES
WET BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING
RESTROOM.

Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175 TO 302F

Vapor Density:>AIR

Spec Gravity:1.343

pH:NA

VOC Grams/Liter:4.63

Viscosity:70-85 KU

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:LIQUID,

SOLVENT ODOR
Percent Volatiles by Volume:63.98
Corrosion Rate:MINIMAL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS, NITRATES, ALKALIES, ACIDS.
Stability Condition to Avoid:NK *OVEREXPOS TO DECOMP PROD MAY CAUSE
HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATE APPARENT. GET MEDICAL AID.
Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE &/OR
CARBON DIOXIDE.
Conditions to Avoid Polymerization:HIGH TEMPERATURES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, LOCAL
REGULATIONS. EPA HAZ WASTE CODE: D001 (IGNITABLE).

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied
, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.