

METERPAK, INC. -- METERPAK #103 -- 7930-01-367-2961

=====
Product Identification
=====

Product ID:METERPAK #103

MSDS Date:08/01/1994

FSC:7930

NIIN:01-367-2961

MSDS Number: BYCRH

=== Responsible Party ===

Company Name:METERPAK, INC.

Address:1270 FEWSTER DR., UNIT 1

City:MISSISSAUGA

State:ON

Country:CA

Info Phone Num:905-624-0366

Emergency Phone Num:800-255-3924

CAGE:LO289

=== Contractor Identifica

tion ===

Company Name:METERPAK INC.

Address:1270 FEWSTER DRIVE, UNIT 1

Box:City:MISSISSAUGA, ONTARIO

Country:CN

CAGE:0SL71

Company Name:METERPAK, INC.

Address:1270 FEWSTER DR., UNIT 1

Box:City:MISSISSAUGA

State:ON

Country:CA

Phone:905-624-0366

CAGE:LO289

=====
Composition/Information on Ingredients
=====

Ingred Name:NONE CONSIDERED HAZARDOUS

Other REC Limits:NA

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES In

gestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: PRODUCT SOLD IN WATER SOLUBLE POUCH.

DIRECT CONTACT W/POWDER UNLIKELY UNDER NORMAL USE. SKIN: MAY CAUSE IRRITATION, REDNESS. EYES: MAY CAUSE IRRITATION, STINGING.

INHALATION: MAY IRRITATE RESPIRATORY TRACT CAUSING COUGHING.

INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING & DIARRHEA.

Effects of Overexposure: SEE HEALTH HAZARDS ABOVE.

Medical Cond Aggravated by E

xposure: NONE KNOWN

===== First Aid Measures =====

First Aid: SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/WATER 15 MINUTES, HOLDING EYELIDS OPEN. SEEK MEDICAL ATTN. INHALATION: REMOVE TO FRESH AIR. SEEK MEDICAL ATTN IF SYMPTOMS PERSIST. INGESTION: DRINK 1-2 GLASSES WATER TO DILUTE. SEEK MEDICAL ATTN.

===== Fire Fighting Measures =====

Flash Point: NONFLAMMABLE

Lower Limits: NA

Upper Limits: NA

Extinguishing Media: CA

RBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures: WEAR POSITIVE PRESSURE SCBA & PROPER PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING ANY CHEMICAL SUBSTANCES.

Unusual Fire/Explosion Hazard: WATER SOLUTIONS OF PRODUCT MAY GENERATE HYDROGEN GAS IN CONTACT W/ALUMINUM & ZINC.

===== Accidental Release Measures =====

Spill Release Procedures: SPRINKLE W/SWEEPING COMPOUND TO REDUCE DUSTING WHILE SWEEPING UP.

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL, DRY & WELL-VENTILATED AREA.

Other Precautions: WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE NIOSH APPROVED RESPIRATOR IF DUSTING LIKELY.

Ventilation: LOCAL EXHAUST: STANDARD ROOM VENTILATION. MECHANICAL (GENERAL): NOT NORMALLY REQUIRED.

Protective Gloves: NOT NORMALLY REQUIRED.

Eye Protection: ONLY IF CONTACT LIKELY.

O

ther Protective Equipment:NOT NORMALLY REQUIRED.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:NA
Melt/Freeze Pt:M.P/F.P Text:NA
Vapor Pres:NA
Vapor Density:NA
Spec Gravity:0.46
Evaporation Rate & Reference:NA
Solubility in Water:COMPLETE
Appearance and Odor:WHITE POWDER, LOW ODOR, PACKAGED IN WATER SOLUBLE
POUCH.

===== Stability and Reacti
vity Data =====

Stability Indicator/Materials to Avoid:YES
NK
Hazardous Decomposition Products:MAY EMIT TOXIC FUMES OF SOX, NA20 &
OXIDES OF CARBON IF HEATED TO DECOMPOSITION.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE, LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. T
he United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.