

ELF ATOCHEM NORTH AMERICA INC -- LUPERSOL DDM-9,129 -- 6810-01-120-0408

=====  
Product Identification  
=====

Product ID:LUPERSOL DDM-9,129

MSDS Date:07/12/1995

FSC:6810

NIIN:01-120-0408

MSDS Number: BYDKH

=== Responsible Party ===

Company Name:ELF ATOCHEM NORTH AMERICA INC

Address:2000 MARKET STREET

City:PHILADELPHIA

State:PA

ZIP:19103-3222

Country:US

Info Phone Num:800-558-5575

Emergency Phone Num

:800-558-5575/800-424-9300(CHEMTREC)

CAGE:86460

=== Contractor Identification ===

Company Name:ELF ATOCHEM NORTH AMERICA INC

Address:2000 MARKET STREET

Box:City:PHILADELPHIA

State:PA

ZIP:19103-3222

Country:US

Phone:800-245-5858

CAGE:86460

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL ETHYL KETONE PEROXIDE (MEKP) (CERCLA)

CAS:1338-23-4

RTECS #:EL9450000

Fraction by Wt: 35.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:C 0.7 PPM

ACGIH TLV:C 0.2 PPM; 9495

EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

Ingred Name:DIMETHYLPHTHALATE (SARA 313) (CERCLA)  
CAS:131-11-3  
RTECS #:TI1575000  
Fraction by Wt: 32.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3; 9495  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:1,3-PENTANEDIOL,2,2,4-TRIMETHYL-,DIISOBUTYRATE  
CAS:6846-50-0  
RTECS #:SA1420000  
Fraction by Wt: 23.8%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:HEXYLENE GLYCOL  
CAS:107-41-5  
RTECS #:SA0810000  
Fraction by Wt: 6.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:C 25 PPM  
ACGIH TLV:C 25 PPM; 9495

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 1.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM  
ACGIH TLV:200 PPM/300STEL;9495  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 1.5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

Ingred Name:HYDROGEN PEROXIDE (SARA

302)  
CAS:7722-84-1  
RTECS #:MX0900000  
Fraction by Wt: 0.7%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1 PPM  
ACGIH TLV:1 PPM; 9495

===== Fire Fighting Measures =====

Flash Point:137F,58C  
Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER  
SPRAY/FOG. USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS.  
Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED  
SELF-CONTAINED BREATHING APPARATUS. IF LARGE AMOUNT IS INVOLVED,  
FIGHT FIRE  
FROM SAFE DISTANCE.  
Unusual Fire/Explosion Hazard:CONTAINERS MAY EXPLODE DUE TO  
DECOMPOSITION.

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:P1  
NRC/State Lic Num:NOT RELEVANT  
Melt/Freeze Pt:M.P/F.P Text: